



بِسْمِ اللَّهِ الرَّحْمَنِ الرَّحِيمِ



شبكة المعلومات الجامعية التوثيق الإلكتروني والميكروفيلم



شبكة المعلومات الجامعية

جامعة عين شمس

التوثيق الإلكتروني والميكروفيلم

قسم

نرسم بالله العظيم أن المادة التي تم توثيقها وتسجيلها
على هذه الأفلام قد أعدت دون أية تغيرات



يجب أن

تحفظ هذه الأفلام بعيداً عن الغبار
في درجة حرارة من ١٥-٢٥ مئوية ورطوبة نسبية من ٤٠-٢٠%
**To be Kept away from Dust in Dry Cool place of
15-25- c and relative humidity 20-40%**

بعض الوثائق
الأصلية تالفة

**بالرسالة صفحات
لم ترد بالاصل**

**TWO NOISE REDUCTION METHODS IN OPTICAL
ENGINEERING APPLICATIONS**

by

Hany Ayad Abdallah Bastawrous

A Thesis Submitted to the
Faculty of Engineering at Cairo University
in Partial Fulfillment of the
Requirement for the Degree of

MASTER OF SCIENCE

in

ELECTRONICS AND COMMUNICATIONS ENGINEERING

Under the Supervision of
Prof. Dr. Adel M. El Nadi

Chairman of Industrial Applications and Material Processing Department,
National Institute of Laser Enhanced Sciences (NILES), Cairo University.

Also

Professor of Electromagnetics, Electronics Engineering and Electrical
Communications Department, Faculty of Engineering, Cairo University.

Adel El Nadi

FACULTY OF ENGINEERING, CARIO UNIVERSITY

GIZA, EGYPT

February 2002

**TWO NOISE REDUCTION METHODS IN OPTICAL
ENGINEERING APPLICATIONS**

by

Hany Ayad Abdallah Bastawrous

A Thesis Submitted to the
Faculty of Engineering at Cairo University
in Partial Fulfillment of the
Requirement for the Degree of

MASTER OF SCIENCE

in

ELECTRONICS AND COMMUNICATIONS ENGINEERING

Approved by the Examining Committee

Adel El Nadi

Pro. Dr. Adel Mohamed El Nadi,

Thesis Main Advisor

Mahmoud Hanafi Ahmed

Pro. Dr. Mahmoud Hanafi Ahmed,

Member

Osman Lotfy El-Sayed

Pro. Dr. Osman Lotfy El-Sayed,

Member

FACULTY OF ENGINEERING, CARIO UNIVERSITY

GIZA, EGYPT

February 2002

CONTENTS

	PAGE
LIST OF FIGURES	vii
LIST OF SYMBOLS AND ABBREVIATIONS	xii
ACKNOWLEDGMENT	xiv
ABSTRACT	xv

CHAPTER ONE: "INTRODUCTION"

1-1 SOME APPLICATIONS OF INTERFERENCE PATTERNS	1
1-2 HOLOGRAPHIC INTERFEROMETRY	2
1-3 FAST FOURIER TRANSFORM	6
1-4 BISTABLE SYSTEMS	14
1-5 ELECTRONIC BISTABILITY	16

CHAPTER TWO: "USING GABOR FILTERS FOR FEATURES DETECTION OF INTERFERENCE PATTERNS"

2-1 EXAMPLE OF A DIFFUSION EXPERIMENT	22
2-2 CONVENTIONAL FILTERING	28
2-3 GABOR FILTERS	31

CHAPTER THREE: “APPLICATION OF GABOR FILTERS TO AN ARBITRARY SIGNAL”

3-1	CHOOSING AN ARBITRARY FUNCTION	49
3-2	APPLICATION OF CONVENTIONAL FILTERS	51
3-3	APPLICATION OF GABOR FILTERS AND ADJUSTMENT OF THEIR PARAMETERS	54

CHAPTER FOUR: “OPTICAL BISTABILITY”

4-1	PRINCIPLE OF OPTICAL BISTABILITY	69
4-2	ALL OPTICAL BISTABLE DEVICES	73
4-2-1	DISPERSIVE NONLINEAR ELEMENTS	73
4-2-2	DISSIPATIVE NONLINEAR ELEMENTS	79
4-3	MATERIALS OF OPTICAL BISTABLE DEVICES	80
4-4	HYBRID BISTABLE OPTICAL DEVICES	82
4-5	ADVANTAGES OF OPTICAL BISTABLE DEVICES	86
4-6	APPLICATIONS OF OPTICAL BISTABILITY	87
4-6-1	OPTICAL MEMORIES	87
4-6-2	OPTICAL LIMITERS	88
4-6-3	PULSE SHAPERS	88
4-6-4	DIFFERENTIAL AMPLIFIERS	89
4-6-5	OPTICAL TRIODES	90
4-6-6	LOGIC GATES	91
4-6-7	APPLICATION OF THA BISTABLE DEVICE AS A COMPARATOR	92

CHAPTER FIVE: “NONLINEAR MICHELSON INTERFEROMETER AS AN OPTICAL BISTABLE DEVICE”

5-1	ORDINARY MICHELSON INTERFEROMETER	95
5-2	NONLINEAR MICHELSON INTERFEROMETER	98
5-3	OPTICAL BISTABILITY PRODUCED BY NONLINEAR MICHELSON INTERFEROMETER	101
5-4	CONTROL PARAMETERS OF OPTICAL BISTABILITY	103
5-4-1	BISTABILITY ONSET	103
5-4-2	SWITCHING INTENSITIES I_{iH} & I_{iL}	105
5-5	COMPONENTS SPECIFICATION AND EXPERIMENTAL RESULTS	106
5-5-1	EXPERIMENTAL RESULTS OF HE-NE LASER	107
5-5-2	EXPERIMENTAL RESULTS OF LASER DIODE	110
5-6	IMPROVING THE PERFORMANCE OF THE OPTICAL BISTABILITY	112
5-6-1	ENHANCED EXPERIMENTAL RESULTS OF HE-NE LASER	114
5-6-2	ENHANCED EXPERIMENTAL RESULTS OF LASER DIODE	115
CHAPTER SIX: “CONCLUSIONS AND FUTURE WORK SUGGESTIONS”		116
REFERENCES		118

LIST OF FIGURES

	Page
<u>CHAPTER ONE</u>	
1-Figure (1-1) "Recording a hologram".	4
2-Figure (1-2) "Reconstruction of the image".	4
3-Figure (1-3) "The FFT decomposition".	7
4-Figure (1-4) "The FFT bit reversal sorting".	8
5-Figure (1-5) "The FFT synthesis".	10
6- Figure (1-6) "FFT synthesis flow diagram".	11
7- Figure (1-7) "The FFT butterfly".	12
8-Figure (1-8) "Flow diagram of the FFT".	13
9-Figure (1-9) "Input-Output relationship for a bistable system".	15
10-Figure (1-10) "Flip-flopping of a bistable system".	15
11-Figure (1-11) "A positive-feedback loop capable of bistable operation".	17
12-Figure (1-12) "A physical analogy for the operation of the bistable circuit".	18
13-Figure (1-13) (a) The bistable circuit of Fig. (1-11) with the negative input terminal of the op amp disconnected from ground and connected to an input signal V_I. (b) The transfer characteristic of the circuit in (a) for increasing V_I. (c) The transfer characteristic for decreasing V_I. (d) The complete transfer characteristic.	20
<u>CHAPTER TWO</u>	
1-Figure (2-1) "Composition during a diffusion experiment at t_{ref} and t_1".	23

2-Figure (2-2) “Composition difference ΔC resulting from figure (2-1)”.	24
3-Figure (2-3) “Interference pattern of a diffusion experiment”.	25
4-Figure (2-4) “Interference pattern of a diffusion experiment with noise”.	26
5-Figure (2-5) “FFT of the clean and the noisy signals”.	26
6-Figure (2-6) “The transfer function $H(f)$ of the conventional filter”.	28
7-Figure (2-7-a,b,c) “Filtered signal using conventional filter with cutoff frequency $f_t = 50, 100, \text{ and } 150$ respectively”.	29
8-Figure (2-8-a,b,c) “Transfer function of Gabor filters for $\sigma_x = 1.5 / f_0, 4 / f_0, 7 / f_0$ respectively”.	36
9- Figure (2-9) “Dominant spatial frequency for each point in the space domain”.	40
10-Figure (2-10-a,b,c,d,e) “$K(x, f_0)$ for $\sigma_x = 2 / f_0, 4 / f_0, 7 / f_0, 8 / f_0, \text{and } 9 / f_0$ respectively”.	40
11-Figure (2-11-a:f) “$K(x, f_0)$ for different values of f_0”.	43
12-Figure (2-12) “Dominant local spatial frequency curve”.	47
13-Figure (2-13) “The signal after being processed by Gabor filters”.	47
14-Figure (2-14) “Filtered signal using conventional filter with cutoff frequency $f_t = 50$”.	48

CHAPTER THREE

1-Figure (3-1) “The arbitrary signal described by Eq. (3-1)”.	50
2-Figure (3-2) “The noisy signal in the spatial domain”.	50
3-Figure (3-3) “The FFT of the clean and the noisy signals”.	51
4-Figure (3-4) “The transfer function $H(f)$ of the conventional filter”.	52

5-Figure (3-5-a, b, c) “Filtered signal using conventional filter with cutoff frequency $f_t = 25, 50$, and 75 respectively”.	53
6-Figure (3-6) “Dominant spatial frequency for each point in the space domain”.	55
7-Figure (3-7-a:e) “$K(x, f_0)$ for $\sigma_x = 0.5, 0.7, 0.92, 1$, and 2 respectively”.	56
8-Figure (3-8) “$K(x, f_0)$ for $\sigma_x = 0.7, f_0 = 4$”.	59
9-Figure (3-9) “$K(x, f_0)$ for $\sigma_x = 0.8, f_0 = 4$”.	59
10-Figure (3-10-a:e) “$K(x, f_0)$ for $\sigma_x = 1/f_0, 3/f_0, 5/f_0, 7/f_0$, and $9/f_0$ respectively”.	60
11-Figure (3-11-a:d) “$K(x, f_0)$ for $\sigma_x = 6/f_0, f_0 = 4, 7, 9$, and 12 respectively”.	63
12-Figure (3-12-a,b,c) “$K(x, f_0)$ for $\sigma_x = 0.01*f_0, 0.07*f_0$, and $0.2*f_0$ respectively”.	65
13-Figure (3-13) “$K(x, f_0)$ for $\sigma_x = 0.07*f_0, f_0 = 4$”.	66
14-Figure (3-14) “Dominant local spatial frequency curve”.	67
15-Figure (3-15) “The signal after being processed by Gabor filters”.	68
16-Figure (3-16) “The signal after being processed by conventional filters”.	68

CHAPTER FOUR

1- Figure (4-1) “An optical system whose transmittance T is a function of I_o”.	70
2-Figure (4-2) (a) Transmittance $T(I_o)$ versus output. (b) Input $I_i = I_o / T(I_o)$ versus output I_o. (c) The output I_o versus the input I_i.	70
3- Figure (4-3) “Output versus input of the bistable device shown in figure (4-1)”.	72
4-Figure (4-4) (a) Despersive bistable optical system & (b) Dissipative bistable optical system.	74

5- Figure (4-5) “A Mach-Zehnder interferometer with a nonlinear medium of refractive index n controlled by the transmitted intensity I_0 via optical Kerr effect”.	76
6- Figure (4-6) “A Fabry-Perot interferometer containing a medium of refractive index “n” controlled by the transmitted light intensity I_0”.	79
7-Figure (4-7) “A bistable device consisting of a saturable absorber in a resonator”.	80
8-Figure (4-8) “A thin layer of semiconductor with two parallel reflecting surfaces can serve as a bistable device”.	81
9-Figure (4-9) “A Fabry-Perot interferometer containing an electro-optic medium (Pockels cell)”.	82
10-Figure (4-10) “A hybrid bistable optical system uses an elecro-optic modulator with electrical feedback”.	83
11-Figure (4-11) “An optically addressed spatial light modulator operates as an array of bistable optical elements”.	84
12-Figure (4-12) “The Self-Electro-optic-Effect Device (SEED)”.	86
13-Figure (4-13) “Bistability characteristic output”.	87
14-Figure (4-14) “Power limiting optical bistable device curve”.	88
15-Figure (4-15) “Pulse shaping with a Bistable optical device”.	89
16-Figure (4-16) “Optical bistable device as a differential amplifier”.	89
17-Figure (4-17) “Schematic of the optical triode”.	90
18-Figure (4-18) “Optical gates using optical bistable switches”.	91
19-Figure (4-19) (a) Block-diagram representation and transfer characteristic for a comparator having a reference, or threshold, intensity I_R. (b) Comparator characteristic with hysteresis.	92
20-Figure (4-20) “Illustrating the use of hysteresis in the comparator characteristics as a means of rejecting interference”.	94

CHAPTER FIVE

1-Figure (5-1) "Michelson interferometer".	95
2-Figure (5-2) "Ordinary Michelson interferometer transmittance".	97
3-Figure (5-3) "Modified Michelson interferometer".	99
4-Figure (5-4) "Graphical solution of nonlinear Michelson interferometer Eqs.". 	100
5-Figure (5.5) "Computer simulation results of nonlinear Michelson interferometer".	100
6-Figure (5-6) "Optical setup for optical bistability".	101
7-Figure (5-7) "Condition of bistability onset".	104
8-Figure (5-8) "Onset of optical bistability at $\phi_0 = \phi_c = 3.605592$".	105
9-Figure (5-9) "Critical switching intensities I_{iH} & I_{iL}".	106
10-Figure (5-10) "Feedback amplifier circuit".	107
11-Figure (5-11) "Bistability curve of He-Ne laser".	108
12-Figure (5-12) "Curve of Tri-stability state".	109
13-Figure (5-13) "Bistability curve of laser diode".	110
14-Figure (5-14) "Tri-stability curve of laser diode".	111
15- Figure (5-15) (a) Simple model of a photodetector & (b) Equivalent circuit.	112
16- Figure (5-16) "Response time of the photodiode".	113
17-Figure (5-17) "Bistability and Tri-stability curves of He-Ne laser".	114
18-Figure (5-18) "Bistability and Tri-stability curves of laser diode".	115