

AIN SHAMS UNIVERSITY
FACULTY OF ENGINEERING
ELECTRICAL POWER AND MACHINES DEPARTMENT

A Microprocessor Based Reactive Power Compensator

*A Thesis Submitted in Fulfillment of the Requirement
of the Degree of Doctor of Philosophy of Science
in
Electrical Engineering
To Ain Shams University, Faculty of Engineering,
Elect. Power & Machines Dept.*

BY

ADEL ABDEL-MONEIM SAYED AHMED
*B.Sc. Elect. Eng., Ain Shams University, 1982,
M.Sc. Elect. Eng., Ain Shams University, 1988.*

621.3916

A . A

Supervised by

Prof. Dr. A. A. EL SATTAR
*Elect. Power and Machine Dept., Faculty of Engineering,
Ain Shams University*

Dr. P. MEHTA & **Dr. M. K. DARWISH**
*Electrical Engineering & Electronics,
Brunel University, U.K.*

CAIRO 1993





EXAMINERS COMMITTEE

Name, Title & Affiliation

Signature


1. **Prof. Dr. A.M. El Tobshy**

Professor, Dept. of Electrical Power and
Machines, Faculty of Engineering, Cairo
University




2. **Prof. Dr. M. S. Morsy**

Professor, Dept. of Electrical Power and
Machines, Faculty of Engineering, Ain Shams
University



3. **Prof. Dr. A. A.Sattar**

Professor, Dept. of Electrical Power and
Machines, Faculty of Engineering, Ain Shams
University



4. **Dr. P. Mehta**

Reader, Department of Electrical Engineering
and Electronics, Brunel University, U. K.

STATEMENT

This dissertation is submitted to Ain Shams University for the degree of Doctor of Philosophy in Electrical Engineering.

This work included in this thesis was carried out by the author. No part of this thesis has been submitted for a degree or a qualification at other university or institution.

Date :

Signature :

Name : Adel Abdel Moniem Sayed Ahmed

ACKNOWLEDGEMENT

The author gratefully acknowledges his indebtedness to *Prof. A. A. El-Sattar* for his invaluable guidance and encouragement throughout the course of this research work.

The author wishes to express his deep and sincere gratitude to his supervisors, *Dr. P. Mehta* and *Dr. M. Darwish* for their enlightened supervision, kind assistance, encouragement and constructive suggestion throughout the course of this research work. Thanks is due to *Dr. Mostafa Darwish* for his valuable assistance discussions and many help.

The author is grateful to the Head and all staff members of Electrical Power & Machines Departement in the Faculty of Engineering, Ain Shams University.

The author wishes to thank professor G. Musgrave, Head of Department of Electrical Engineering and Electronics, Brunel University, for providing research facilities and his agreement for open the Channel Scheme between Ain Shams University and Brunel University.

He expresses his thanks due to the Arab Student Aid International (ASAI) for providing this opportunity and finacial support. Also, he would like to take this oppotuinuity to thank HRH prince *Turki Bin Abd UL Aziz* , the Chairman of ASAI.

He wishes to thank and acknowledges his wife for her continuous encouragement and help during this study and difficult times.

CONTENTS

	Page
LIST OF FIGURES	vi
LIST OF SYMBOLS	xix
ABSTRACT	xxi
CHAPTER I : INTRODUCTION	1
1.1 General	1
1.2 Converter power factor	2
1.3 Network power factor correction	3
1.4 Converter power factor improvement	9
1.4.1 Extinction angle control	10
1.4.2 Symmetrical angle control	13
1.4.3 Pulse-width-modulation control	14
1.4.4 Sinusoidal pulse-width modulation	15
1.5 Source of harmonics and their problems	16
1.6 Harmonic elimination	18
1.6.1 Shunt filters	19
1.6.2 Series filters	19
1.6.3 Phase multiplication	21
1.6.4 Harmonic injection (active filters)	22
1.7 Control of harmonics	25
1.8 The proposed technique	28

CHAPTER II : ANALYSIS OF SINGLE PHASE

	CONVERTER AND REGULATOR CIRCUITS	30
2.1	Introduction	30
2.2	Single phase converter circuits and waveforms	31
2.3	Single phase full converters without free wheeling diode (F.W.D.) loaded with R-L series load	35
2.4	Single phase full converter with F.W.D.	38
2.4.1	Series R-L load	38
2.4.2	Series R-L load with a back e.m.f. load	51
2.4.2.1	Continuous current operation	52
2.5	Single phase uncontrolled full converter loaded with parallel R-C load	57
2.6.	Single phase ac voltage regulator with resistive load	61
	CHAPTER III : SWITCHED CAPACITOR TECHNIQUE	66
3.1	Introduction	66
3.2	Semiconductor switch	67
3.2.1	Method of controlling the semiconductor switch	68
3.3	Expression for switching function, SF, in case of a uniform pattern	69

	Page
3.4	Types of switched-capacitor circuits 71
3.4.1	General 71
3.4.2	Single - switch single - capacitor circuit 72
3.4.3	Double - switch single - capacitor circuit 73
3.4.4	Double - switch Double - capacitor circuit 74
3.4.5	Triple switched configuration 75
3.5	Analysis of triple-switch double capacitor circuit 79

CHAPTER IV : POWER FACTOR COMPENSATION AND HARMONICS REDUCTION USING TRIPLE SWITCHED CAPACITOR CIRCUIT

	90
4.1	Introduction 90
4.2	Power factor improvement in case of a single phase full converter without free wheeling diode (F.W.D.) loaded with R-L series load 92
4.3	Power factor improvement in case of a single phase full converter with free wheeling diode (F.W.D.) 97
4.3.1	series R-L load 97
4.3.2	series R-L with a back e.m.f.load 102
4.4	Power factor improvement in case of a single

	Page
phase ac regulator with resistive load	105
4.5 Harmonic current reduction in case of a single phase bridge rectifier loaded with capacitive load	108
4.5.1 General	108
4.5.2 Harmonic - current reduction by using a switched capacitor filter	110
4.5.3 Harmonic - current reduction by using a switched capacitor and a series parallel resonant filters	111

CHAPTER V : MICROPROCESSOR CONTROL OF SWITCHED CAPACITOR AND EXPERIMENTAL SET-UP

	114
5.1 Introduction	114
5.2 Microprocessor control	115
5.2.1 General	115
5.2.2 8-bit (8085) and 16-bit (8086) microprocessor	116
5.2.3 Software program	118
5.3 Experimental set-up	120
5.3.1 The zero-crossing detector (Z.C.D.)	124
5.3.2 Dead-zone and complementary switching	

	Page
function generator	126
5.4 The power MOSFET drive circuit	129
5.4.1 Optocouplers and isolation of gate-controlling signals from power circuits (MOSFETs)	129
5.4.2 The ICL 7667 CPA chip	131
5.5 Experimental results	132
5.5.1 General	132
5.5.2 Single phase full converter without F.W.D. loaded with R-L series load	134
5.5.3 Single phase full converters with F.W.D. loaded with R-L series load	141
5.5.4 Single phase full converters with F.W.D. loaded with R-L series load and a battery	146
5.6 Single phase ac regulator with pure resistive load	151
5.7 Harmonic current reduction in case of a single phase bridge rectifier with a parallel R-C load	151
CONCLUSION	159
REFERENCES	161
APPENDIX A	167
APPENDIX B	171

LIST OF FIGURES

Figure No.	TITLE	Page
Fig.(1-1)	: Static compensator of thyristor switched capacitor	8
Fig.(1-2)	: Static compensator of the thyristor controlled reactor	9
Fig.(1-3)	: Single-phase commutated semiconverter a. Circuit b. Waveforms of input voltage, output voltage, and supply current	11
Fig.(1-4)	: Single phase forced commutated full converter	12
Fig.(1-5)	: Waveforms of input voltage, output voltage, and supply current in case of symmetrical angle control	13
Fig.(1-6)	: Waveforms of input voltage, output voltage, and supply current in case of pulse-width-modulation control	14
Fig.(1-7)	: Sinusoidal pulse-width-modulation	16
Fig.(1-8)	: Basic principle of passive filter	21
Fig.(1-9)	: Basic principle of active filter	22
Fig.(1-10)	: Combination of a series active and shunt passive filter	26
Fig.(1-11)	: Principle of s-c compensator	29
Fig.(1-12)	: S-c and a series passive filters	29

Fig.(2-1)	: Single phase circuit	3 1
Fig.(2-2)	: Different types of load	3 2
Fig.(2-3)	: Waveforms of output voltage and supply current in case of : a. Fully controlled bridge rectifier loaded with resistive load. b. Fully controlled bridge rectifier loaded with highly inductive load. c. Half-controlled bridge rectifier loaded with highly inductive load d. Fully controlled bridge rectifier loaded with series highly inductive load with a back e.m.f. load e. Fully controlled bridge rectifier loaded with a parallel R-C load	3 3
Fig.(2-4)	: Single phase full wave controlled converter without F.W.D. a. Circuit b. Waveforms of output voltage, load current, and supply current	3 7
Fig.(2-5a)	: Supply current waveform and its spectra at triggering angle equals to 0° in case of a single phase full converter without F.W.D. loaded with R-L series	3 9
Fig.(2-5b)	: Supply current waveform and its spectra at triggering angle equals to 15° in case of a single phase full converter without F.W.D. loaded with R-L series load	4 0
Fig.(2-5c)	: Supply current waveform and its spectra at triggering angle equals to 30° in case of a single phase full converter without F.W.D. loaded with R-L series load	4 1

Fig.(2-5d)	: Supply current waveform and its spectra at triggering angle equals to 45° in case of a single phase full converter without F.W.D. loaded with R-L series load	4 2
Fig.(2-6)	: The variation of displacement and power factors vs the triggering angle in case of a single phase full converter without F.W.D. loaded with R-L series	4 3
Fig.(2-7)	: Single phase full wave controlled converter with F.W.D. a. Circuit b. Waveforms of output voltage, load current, and supply current	44
Fig.(2-8a)	: Supply current waveform and its spectra at triggering angle equals to 15° in case of a single phase full converter with F.W.D. loaded with R-L series load	48
Fig.(2-8b)	: Supply current waveform and its spectra at triggering angle equals to 75° in case of a single phase full converter with F.W.D. loaded with R-L series load	4 9
Fig.(2-9)	: The variation of displacement and power factors vs the triggering angle in case of a single phase full converter with F.W.D. loaded with R-L series load	5 0
Fig.(2-10)	: Single phase full converter with F.W.D. a. Circuit b. Waveforms of output voltage and load current	5 1
Fig.(2-11a)	: Supply current waveform and its spectra at triggering angle equals to 30° in case of a single	

phase full converter with F.W.D. loaded by series R-L with a back e.m.f. load	5 4
Fig.(2-11b) : Supply current waveform and its spectra at triggering angle equals to 120° in case of a single phase full converter with F.W.D. loaded by series R-L with a back e.m.f. load	5 5
Fig.(2-12) : The variation of displacement and power factors vs the triggering angle in case of a single phase full converter with F.W.D. loaded by series R-L with a back e.m.f. load	5 6
Fig.(2-13) : The circuit and the waveform of the supply current in case of ac voltage regulator with resistive load	5 7
Fig.(2-14a) : Supply current waveform and its spectra at triggering angle equals to 30° in case of ac voltage regulator with resistive load	5 8
Fig.(2-14b) : Supply current waveform and its spectra at triggering angle equals to 120° in case of ac voltage regulator with resistive load	5 9
Fig.(2-15) : The variation of the displacement and power factors vs the triggering angle in case of ac voltage regulator with resistive load	6 0
Fig.(2-16) : Single phase uncontrolled full converter a. Circuit b. Waveforms of output voltage and supply current	6 2
Fig.(2-17) : Supply current waveform and its spectra in case of a single phase uncontrolled full converter with R-C load	6 5
Fig.(3-1) : Bidirectional switch and its symbol	6 8