

**PREPARATION AND EVALUATION OF
RUBBER RESISTING
TO CHEMICALS**

BY

MAGDY MASOUD AHMED AL AKHRAS

(B.Sc. 1981, M. Sc. 1990)

60817

**SUBMITTED TO
CHEMISTRY DEPARTMENT
FACULTY OF SCIENCE
AIN SHAMS UNIVERSITY**

رابع

in the fulfilment
of the requirments for

مكتبة المعلومات الجامعية
تم التسجيل ميكرو فيلميا
التوثيق اليكرو فيلم
1

47.8426
M. M.

**THE DEGREE OF DOCTOR OF PHILOSPHY
IN CHEMISTRY**

SUPERVISORS 
Prof. Dr. **ABDELGAWAD M. RABIE**
Prof. Dr. **ABBAS ABDEL KARIM YEHIA**
Prof. Dr. **FAHIMA MOSAD HELALY**



1997



THESIS
ENTITLED

Preparation and Evaluation of Rubber resist to chemicals.

Thesis supervisors


Approved

Prof. Dr. Abdelgawad M. Rabie




Dean Faculty of Science, Ain Shams University

Prof. Dr. Abbas Abdel_Kariem Yehia




NRC, Dept. of polymer and pigments

Prof. Dr. Fahima Mosad Helaly



NRC, Dept. of polymer and pigments

HEAD OF CHEMISTRY DEPARTMENT



PROF. DR. F.A. FAHMY

Acknowledgment

This work was carried in Heliopolis company for chemicals Industries. (Military Fac.81) A.R.E.

The author wishes gratefully to thank **Prof. Dr. Abdelgawad, M. Rabie**; Dean of Faculty of Science Ain Shames University and **Prof. Dr Abbas Abdel-Kariem Yehia** Dept. of Polymers and Pigments, National Research Center for suggesting and planning this work, helpful and fruitful discussion and continuous guidance throughout this work.

The author wishes to express his deepest thanks and gratitude to **Prof. Dr. Fahima Mosad Helaly**, Dept. of Polymers and Pigments, National Research Center for her interest valuable discussion and guidance throughout this work. He also wishes to express his thanks to **Eng. Mohamed Awney Abdel Meged**, Chairman of Heliopolis Company for chemical Industries and **Eng. Sayed Tantawy**, The Technical director for their help and facilities provided.

The author also wishes to express his thanks to **All staff members and colleagues** of the Rubber Technology laboratory at Heliopolis Company for Chemical Industries for their kind co-operation.

CONTENTS

I - INTRODUCTION

1-1.	RUBBER	1
1-2.	COMPOUNDING INGREDIENTS	6
	1 - ELASTOMERS	6
	2 - FILLERS	6
	3 - ACCELERATORS	6
	4 - ANTIOXIDANTS	8
	5 - ACTIVATORS	9
	6 - VULCANIZING AGENTS	9
	7 - PROCESSING AIDS	10
	8 - MICELLANEOUS INGREDIENTS	10
1-3.	PROCESSING AND MIXING	11
	1 - PROCESSING	11
	2 - BREAKDOWN	11
	3 - MIXING	12
1-4.	VULCANIZATION	12
	1 - SULPHUR VULCANIZATION	13
	2 - SULPHURLESS VULCANIZATION	14
	3 - PEROXIDE VULCANIZATION	14
	4 - VULCANIZATION BY PHENOLIC RESINS, QUINONE, OR MELEIMIDES	15
	5 - VULCANIZATION BY RADIATION	15
1-5.	AGEING AND HEAT RESISTANCE RESINS, OF RUBBER	16
1-6.	CHEMICALLY RESISTANT RUBBERS	16
1-7.	BLENDS OF RUBBERS	17

II - LITERATURE REVIEWS

II - 1.	VULCANIZATION	18
II - 1. 1.	SULPHURE VULCANIZATION	18
II - 1. 2.	SULPHURE VULCANIZATION IN THE PRESENCE OF ACCELERATORS	20
II - 1. 3.	NON- SULPHUR VULCANIZING SYSTEM	20
II - 1. 3. 1.	REACTION WITH THIURAM DISULPHIDE	21
II - 1. 3. 2.	REACTION OF SULPHENAMIDES	22
II - 1. 3. 3.	CROSSLINKING REACTIONS WITH MBTS	25
II - 2.	EFFECT OF FILLERS IN RUBBERS	26
II - 3.	EFFECT OF SOLVENT ON THE PROPERTIES OF RUBBERS	31

II - 4.	EFFECT OF ACIDS AND ALKALIES ON RUBBER	32
II - 5.	RUBBER BLENDS	34
III - MATERIALS AND EXPERIMENTAL TECHNIQUES		
III - 1.	MATERIALS.....	36
III - 1. 1.	RUBBERS	36
III - 1. 2.	FILLERS	37
III - 1. 3.	VULCANIZING AGENTS	37
III - 1. 4.	REAGENTS	38
III - 2.	TECHNIQUES	39
III - 2. 1.	MIXING AND COMPOUNDING	39
III - 2. 2.	PREPORATION AND COMPOUNDING BLENDS	39
III - 2. 3.	RHEOLOGY MESURMENTS	40
III - 2. 4.	VULCANIZATION OF THE TEST SPECIMEN	40
III - 2. 5.	TESTS ON VULCANIZED RUBBER	41
III - 2. 6.	AGEING TEST	43
III - 2. 7.	EVALUATION OF VULCANIZATION KINETICS	43
III - 2. 8.	DETERMINATION OF APPARENT ACTIVATION ENERGY	44
III - 2. 9.	SCANNING ELECTRON MICROSCOPY	44
IV - RESULTS AND DISCUSION		
IV - 1.	EFFECT OF VULCANIZATION SYSTEMS ON THE PROPERTIES OF RUBBER VULCANIZATES	45
IV - 1. 1.	EFFECT OF VULCANIZATION SYSTEMS ON RHEOMETRIC AND PHYSICO MECHANICAL PROPERTIES ON RUBBER VULCANIZATES	46
IV - 1. 2.	DETERMINATION OF CROSSLINKING DENSITY	49
IV - 1. 3	EFFECT OF OXIDATIVE AGEING OF RUBBER VULCANIZATES CONTAINING DIFFERENT VULCANIZATION SYSTEMS	50
IV - 1. 4.	DETERMINATION OF THE APPARENT ACTIVATION ENERGY	61
IV - 2.	EFFECT OF FILLERS ON RUBBER VULCANIZATES	62
IV - 2. 1.	EFFECT OF DIFFERENT TYPES OF FILLERS ON THE PROPERTIES OF RUBBER	62
IV - 2. 2.	SURFACE PROPERTIES OF RUBBER SHEETS BEFORE IMMERSION IN CHEMICALS	65
IV - 2. 3.	EFFECT OF DIFFERENT FILLERS ON THE KINETICS OF VULCANIZATES	72

IV - 2. 4.	EFFECT OF THE TYPE OF FILLER ON NR (RSS-1) VULCANIZATES IMMERSSED IN CHEMICALS	72
	A - EFFECT OF ACIDS AT ROOM TEMPERATURE	73
	B - EFFECT OF BASE (NaOH) ON NR (RSS-1) AT ROOM TEMPERATURE	79
	C - EFFECT OF H ₂ SO ₄ AND NaOH ON THE NR VULCANIZATES AT 90 ⁰ C.	82
IV - 2. 5.	EFFECT OF THE TYPE OF FILLER ON EPDM VULCANIZATES IMMERSSED IN CHEMICAL	84
	A - ACIDS	84
	B - ALKALI	89
	C - EFFECT OF H ₂ SO ₄ AND NaOH ON THE INVESTEGATED EPDM VULCANIZATES AT 90 ⁰ C ...	92
IV - 2. 6.	SURFACE PROPERTIES OF NR AND EPDM VULCANIZATES AFTER IMMERSION IN HNO ₃	94
IV - 3.	EFFECT OF COMBINATION OF FILLERS ON THE PROPERRTIES OF NR AND EPDM COMPOUNDS IMMERSSED IN DIFFERENT CHEMICALS. ..	98
IV - 3. 1.	EFFECT OF COMBINATION OF FILLER ON RHEOMETRIC CHARACTERISTICS	98
IV - 3. 2.	EFFECT OF K/SRF COMBINATION ON THE PROPERTIES OF RUBBER VULCANIZATES SUBJECTED TO CHEMICALS	100
	A - THE PROPERTIES OF RUBBER VULCANIZATES SOAKED IN CHEMICALS AT ROOM TEMPERATURE	100
	B - EFFECT OF ALKALI (NaOH) ON RUBBER VULCANIZATES AT ROOM TEMPERATURE	109
IV - 3. 3.	EFFECT OF THERMAL OXIDATIVE AGEING ON THE PROPERTIES OF THE INVESTIGATED RUBBER SAOKED IN CHEMICALS	112
IV - 4.	EFFECT OF RUBBER BLENDS ON THE CHEMICALS RESISTAT OF THE VULCANIZATES IMMERSSED IN DIFFERENT CHEMICALS	122
IV - 4. 1.	EFFECT OF RUBBER BLENDS ON THE PROPERTIES OF VULCANIZATE ON TREATED WITH CHEMICALS.....	126
	A - EFFECT OF H ₂ SO ₄ AT ROOM TEMPERATURE	126

	B - EFFECT OF HNO ₃ AT ROOM TEMPERATURE	129
	C - EFFECT OF HCL AT ROOM TEMPERATURE	132
	D - EFFECT OF NaOH AT ROOM TEMPERATURE	136
IV - 4. 2.	EFFECT OF THERMAL OXIDATIVE AGEING ON THE PROPERTIES OF RUBBER BLENDS SOAKED IN CHEMICALS AT 90 ⁰ C	139
	A - EFFECT OF ACIDS ON THE PROPERTIES OF RUBBER BLENDS AT 90 ⁰ C	139
	B - EFFECT OF NaOH ON THE PROPERTIES OF RUBBER BLENDS AT 90 ⁰ C	145
IV - 4. 3.	SURFACE PROPERTIES OF RUBBER BLENDS LOADED WITH COMBINATION OF FILLERS BEFORE AND AFTER IMMERSION IN HCL	148
	<i>CONCLUSION</i>	151
	<i>SUMMARY</i>	152
	<i>REFFERENCES</i>	155
	<i>ARABIC SUMMARY</i>	

List of Tables

- Table (1) Formulation of rubber compound with different vulcanization systems.
- Table (2) Rheological and physico-mechanical properties of rubber compound according to vulcanization systems.
- Table (3) Calculation of M_c and crosslinking density of rubber vulcanizates according to vulcanization systems.
- Table (4) Effect of different vulcanizing system and aging time on the hardness.
- Table (5) Determination of the apparent activation energy of the rubber compounds using different vulcanization systems.
- Table (6) Formulation of rubber compounds with different fillers.
- Table (7) Rheometric and physico-mechanical properties of rubber compound with different fillers.
- Table (8) Kinetic characteristics constants of rubber vulcanizates with different fillers.
- Table (9) Effect of fillers on the hardness of rubber vulcanizates immersed in 25% chemicals at room temperature for different time.
- Table (10) Retained physico-mechanical properties of NR vulcanizates after immersion in H_2SO_4 and $NaOH$ at $90^\circ C$ for different time.
- Table (11) Retained physico-mechanical properties of EPDM vulcanizate after immersion in H_2SO_4 and $NaOH$ at $90^\circ C$ for different time.
- Table (12) Visual inspection of rubber surface of RSS-1 and EPDM after immersion in HNO_3 for 60 days at room temperature.

Table (13)	Formulations of combination of Kaolin/SRF in NR (RSS-1) and EPDM vulcanizates.
Table (14)	Rheological and physico-mechanical properties of combination of Kaolin/SRF fillers with RSS-1 and EPDM vulcanizates.
Table (15)	Weight changes of rubber vulcanizates after immersion in chemicals at different conditions.
Table (16)	Formulationsof Rubberblends with combination of fillers.
Table (17)	Rheological and physico-mechanical properties of rubber blends.
Table (18)	Hardness and relative change of weight of rubber blends containing Kaolin/SRF immersed in H_2SO_4 at room temperature.
Table (19)	Hardness and relative change of weight of rubber blends containing Kaolin/SRF immersed in HNO_3 at room temperature.
Table (20)	Hardness and relative change of weight of rubber blends containing Kaolin/SRF immersed in HCL at room temperature.
Table (21)	Hardness and relative change of weight of rubber blends containing Kaolin/SRF immersed in NaOH at room temperature.
Table (22)	Hardness and relative change of weight of rubber blends containing Kaolin/SRF immersed in H_2SO_4 and HCL at $90^{\circ}c$.
Table (23)	Hardness and relative change of weight of rubber blends containing Kaolin/SRF immersed in NaOH at $90^{\circ}c$.

LIST OF FIGURES

- Fig. 1 Retained tensile strength, a, and elongation at break, b, of RSS-1 vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 2 Retained modulus, a, and equilibrium swelling, b, of RSS-1 vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 3 Retained tensile strength, a, and elongation at break, b, of EPDM vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 4 Retained modulus, a, and equilibrium swelling, b, of EPDM vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 5 Retained tensile strength, a, and elongation at break, b, of BIIR vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 6 Retained modulus, a, and equilibrium swelling, b, of BIIR vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 7 Retained tensile strength, a, and elongation at break, b, of NBR vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 8 Retained modulus, a, and equilibrium swelling, b, of NBR vulcanizates aged at 90⁰C vs. ageing time, using different vulcanization systems.
- Fig. 9a SEM photograph of the fracture surface of RSS/SRF magnification x 200.
- b SEM photograph of the fracture surface of RSS/SRF magnification x 1000.
- c SEM photograph of the fracture surface of RSS/SRF magnification x 2000.

- Fig. 10a SEM photograph of the fracture surface of RSS/Vulkasil C., magnification x 200.
- Fig. 10b SEM photograph of the fracture surface of RSS/Vulkasil C., magnification x 1000.
- Fig. 10c SEM photograph of the fracture surface of RSS/Vulkasil C., magnification x 2000.
- Fig. 11a SEM photograph of the fracture surface of EPDM/SRF, magnification x 200.
- Fig. 11b SEM photograph of the fracture surface of RSS/Vulkasil C., magnification x 1000.
- Fig. 11c SEM photograph of the fracture surface of RSS/Vulkasil C., magnification x 2000.
- Fig. 12a SEM photograph of the fracture surface of EPDM/Vulkasil C., magnification x 200.
- Fig. 12b SEM photograph of the fracture surface of EPDM/Vulkasil C., magnification x 1000.
- Fig. 12c SEM photograph of the fracture surface of EPDM/Vulkasil C., magnification x 2000.
- Fig. 13 Effect of fillers on retained tensile strength, a, and elongation at break, b, of RSS-1 vulcanizates immersed in 25% H_2SO_4 at room temperature for different time.
- Fig. 14 Effect of fillers on retained modulus, a, and equilibrium, b, of RSS-1 vulcanizates immersed in 25% H_2SO_3 at room temperature for different time.
- Fig. 15 Effect of fillers on retained tensile strength, a, and elongation at break, b, of RSS-1 vulcanizates immersed in 25% HNO_3 at room temperature for different time.
- Fig. 16 Effect of fillers on retained modulus, a, and equilibrium, b, of RSS-1 vulcanizates immersed in 25% HNO_3 at room temperature for different time.

- Fig. 17 Effect of fillers on retained tensile strength, a, and elongation at break, b, of RSS-1 vulcanizates immersed in 25% NaOH at room temperature for different time.
- Fig. 18 Effect of fillers on retained modulus, a, and equilibrium swelling, b, of RSS-1 vulcanizates immersed in 25% NaOH at room temperature for different time.
- Fig. 19 Effect of fillers on retained tensile strength, a, and elongation at break, b, of EPDM vulcanizates immersed in 25% H₂SO₄ at room temperature for different time.
- Fig. 20 Effect of fillers on retained modulus, a, and equilibrium swelling, b, of EPDM vulcanizates immersed in 25% H₂SO₄ at room temperature for different time.
- Fig. 21 Effect of fillers on retained tensile strength, a, and elongation at break, b, of EPDM vulcanizates immersed in 25% HNO₃ at room temperature for different time.
- Fig. 22 Effect of fillers on retained modulus, a, and equilibrium swelling, b, of EPDM vulcanizates immersed in 25% HNO₃ at room temperature for different time.
- Fig. 23 Effect of fillers on retained tensile strength, a, and elongation at break, b, of EPDM vulcanizates immersed in 25% NaOH at room temperature for different time.
- Fig. 24 Effect of fillers on retained modulus, a, and equilibrium swelling, b, of EPDM vulcanizates immersed in 25% NaOH at room temperature for different time.

- Fig. 25a SEM photograph of the fracture surface of RSS/SRF after immersion in HNO_3 for 2months.
- Fig. 25b SEM photograph of the fracture surface of RSS/V.C. after immersion in HNO_3 for 2months.
- Fig. 26a SEM photograph of the fracture surface of EPDM/SRF after immersion in HNO_3 for 2months.
- Fig. 26b SEM photograph of the fracture surface of EPDM/V.C after immersion in HNO_3 for 2months.
- Fig. 27 Retained tensile strength, a, and elongation, b, of rubber vulcanizates containing combination fillers (K/SRF) immersed in 25% H_2SO_4 at room temperature for different time.
- Fig. 28 Retained modulus, a, and equilibrium swelling, b, of rubber vulcanizates containing combination fillers (K/SRF) immersed in 25% H_2SO_4 at room temperature for different time.
- Fig. 29 Retained tensile strength, a, and elongation, b, of rubber vulcanizates containing combination fillers (K/SRF) immersed in 25% HCL at room temperature for different time.
- Fig. 30 Retained modulus, a, and equilibrium swelling, b, of rubber vulcanizates containing combination fillers (K/SRF) immersed in 25% HCL at room temperature for different time.
- Fig. 31 Retained tensile strength, a, and elongation, b, of rubber vulcanizates containing combination fillers (K/SRF) immersed in 25% HNO_3 at room temperature for different time.
- Fig. 32 Retained modulus, a, and equilibrium swelling, b, of rubber vulcanizates containing combination fillers (K/SRF) immersed in 25% HNO_3 at room temperature for different time.