



“Intensifying Petrolatum Deoiling for Production of Different Types of Petroleum Products”

**A Thesis Submitted by
Fathi Samir Soliman Ibrahim
Master of Science (Chemistry-2008)**

**A Dissertation Submitted for the Degree of Doctor of
Philosophy of Science in Chemistry**

**To
Department of Chemistry, Faculty of Science,
Ain Shams University
Cairo, Egypt
(2014)**



“Intensifying Petrolatum Deoiling for Production of Different Types of Petroleum Products”

Fathi Samir Soliman Ibrahim

Master of Science (Chemistry 2008)

Submitted for the Degree of Doctor of Philosophy of
Science in Chemistry

Ph.D. Thesis

Thesis Advisors

Prof. Dr. / Said Hanafi Ahmed Aly

Prof. Dr. / Amal Said Farag

Prof. Dr. / Magdy Tadrous Zaky

Approved

Head of Chemistry Department

Prof. Dr. / Hamed Younes Derbala

CONTENTS

	Page
ACKNOWLEDGEMENT	I
AIM OF THE WORK	III
ABSTRACT	IV
LIST OF ABBREVIATIONS	
LIST OF TABLES	
LIST OF FIGURES	
CHAPTER I:	
<u>LITERATURE REVIEW</u>	1
1. PETROLEUM WAXES.....	1
1.1. Composition of Petroleum Waxes.....	3
1.1.1. Paraffin Waxes (Macro-Crystalline Waxes).....	3
1.1.2. Microcrystalline Waxes.....	4
1.2. Properties of Petroleum Waxes.....	5
1.2.1. Physical Properties.....	5
1.2.1.1. Carbon Number.....	6
1.2.1.2. Color.....	6
1.2.1.3. Melting Point.....	7
1.2.1.4. Oil Content.....	8
1.2.1.5. Viscosity.....	9
1.2.2. Mechanical Properties.....	10
1.2.2.1. Hardness	10
1.2.3. Food Grade Properties.....	11
1.3. Congealing Point – Refractive Index Relationship.....	11
2. CRYSTALLIZATION.....	14
2.1. Crystal Nucleation.....	15
2.2. Crystal Growth.....	15

2.3. Crystal Structure of Petroleum Waxes.....	19
2.3.1. Macro-crystalline Waxes (Paraffin Waxes).....	19
2.3.2. Microcrystalline waxes.....	21
3. MANUFACTURE OF PETROLEUM WAXES.....	22
3.1. Dewaxing Processes.....	23
3.1.1. Solvent Dewaxing Process.....	23
3.1.1.1. Propane Dewaxing Process.....	24
3.1.1.2. Ketone Dewaxing Process.....	25
A- Texaco Solvent Dewaxing Process.....	26
B- Exxon Dilchill Dewaxing Process.....	26
3.1.1.3. Di / Me Dewaxing Process.....	27
3.1.2. Urea Dewaxing Process.....	28
3.2. Refining of Petroleum Waxes.....	28
3.2.1. Deoiling Processes (Wax Fractionation Processes).....	29
3.2.1.1. The Sweating Process.....	29
3.2.1.2. The Wax Recrystallization Process.....	30
3.2.1.3. The Warm-Up Deoiling Process.....	31
3.2.1.4. The Spray Deoiling Process.....	32
3.2.2. Solvent Percolation Technique.....	33
3.2.3. Supercritical Fluid Fractionation.....	34
3.3. Crystal Modifiers for Dewaxing and Deoiling Improvement	34
3.4. Finishing Process.....	38
3.4.1. Adsorption Process.....	39
3.4.2. Hydrofinishing Process.....	40
3.5. Applications of Petroleum Waxes.....	41
3.5.1. The Paper Industry.....	42
3.5.2. In Household Chemicals.....	42
3.5.3. Cosmetics Industry.....	43
3.5.4. Dental Industry.....	43

3.5.5. The Match Industry.....	44
3.5.6. The Rubber Industry.....	44
3.5.7. Building Construction.....	45
3.5.8. The Electrical Industry.....	45
3.5.9. The inks Industry.....	46
3.5.9.1 Printing Inks.....	46
3.5.9.2. Carbon Paper Inks.....	46
3.5.10. Manufacture of Metals and Ceramics.....	47

CHAPTER II:

<u>EXPERIMENTAL</u>	49
1. FEED STOCKS	49
2. SEPARATION OF NON-POLAR MODIFIER CONCENTRATES...	49
2.1. Multistage Fractional Crystallization	49
2.2. Liquid-Solid Chromatographic Technique	50
2.3. Urea Adduction Technique	50
3. REFINING OF CRUDE PETROLATUMS	51
3.1. One Stage Fractional Crystallization	51
3.2. Fractional Crystallization Variables	52
3.2.1. Solvent Type	52
3.2.2. Dilution Solvent Ratio.....	52
3.2.3. Addition of Non-polar Modifiers.....	52
3.2.3.1. Individual Pure Non-Polar Modifiers	52
3.2.3.2. Mixture of Pure Non-Polar Modifiers.....	53
3.2.3.3. Prepared Non-Polar Modifier Concentrates.....	53
3.2.4. Filtration Rate Calculations.....	53
4. METHODS OF ANALYSIS	54
4.1. Physical Characteristics	54
4.2. Type of Wax	55

4.3. Molecular Type Composition.....	55
4.3.1. Aromatic Content.....	55
4.3.2. n-Paraffin Content	56
4.4. Structural Group Analysis.....	57
4.5. Thermal Characteristics.....	57
4.6. X-Ray Diffraction.....	57
4.7. Scanning Electron Microscope (SEM).....	58
5. PRODUCTION OF PETROLEUM PRODUCTS.....	58
5.1. Ceresin Formulation	58
5.2. Petrolatum formulations	59
5.2.1. Technical Petrolatum Formulation	59
5.2.2. Medicinal Petrolatum Formulation.....	59

CHAPTER III:

<u>RESULTS AND DISCUSSION</u>	61
1. CHARACTERIZATION OF SLACK WAXES.....	61
1.1. Physical Characteristics.....	61
1.2. Molecular Type Composition.....	61
1.2.1. Normal Paraffin Content.....	62
2. CHARACTERIZATION OF CRUDE PETROLATUMS.....	66
2.1. Physical Characteristics.....	66
2.2. Molecular Type Composition.....	69
3. SEPARATION OF NON-POLAR MODIFIERS.....	70
3.1. Multistage Fractional Crystallization Technique.....	70
3.1.1. Physical Characteristics of Hard Waxes.....	70
3.1.2. N-paraffin Content of Hard Waxes.....	72
3.2. Liquid-Solid Chromatographic Technique.....	79
3.3. Urea Adduction Technique.....	79
3.3.1. Physical Characteristics of Adducts.....	80

3.3.1.1. Adducts of the light Slack Wax and Its Saturates.....	80
3.3.1.2. Adducts of the Fractionated Hard Waxes.....	80
3.3.2. n-Paraffin Content of the Adducts.....	84
3.3.2.1. Adducts of the light Slack Wax and Its Saturates.....	84
3.3.2.2. Adducts of the Hard Waxes Isolated at different.....	86
Fractionated Temperatures.....	
4. REFINING OF CRUDE PETROLATUMS	90
4.1. Solvent Deoiling (Fractional Crystallization).....	90
4.1.1. Effect of Dilution Solvent Ratio.....	90
4.1.1.1. Isolated Wax Type.....	102
4.1.2. Effect of Addition of the Individual n-Alkane Modifiers	102
on Petrolatum Deoiling Process.....	
4.1.2.1. Isolated Wax Type.....	123
4.1.3. Effect of Addition of Mixtures of n-alkane Modifiers on	123
Petrolatum Deoiling Process.....	
4.1.3.1. Isolated Wax Type.....	132
4.1.4. Effect of Addition of the Prepared Non-polar Modifier	132
concentrates on Petrolatum Deoiling Process.....	
4.1.4.1. Isolated Wax Type.....	136
5. PRODUCTION OF PETROLEUM PRODUCTS	143
5.1. Formulation of Ceresins.....	143
5.2. Formulation of Petrolatum.....	146
5.2.1. Blends Containing Microcrystalline Wax and Heavy	146
Paraffin Oil.....	
5.2.2. Blends Containing Slop Wax Saturate and Light Paraffin	152
Oil.....	
SUMMARY AND CONCLUSIONS.....	159
REFERENCES.....	166
ARABIC SUMMARY.....	

LIST OF TABLES

	Page
Table 1: Physical characteristics and molecular type composition of the two slack waxes.	63
Table 2: Carbon number distribution and n-paraffin contents of the two slack waxes.	64
Table 3: Physical characteristics and structural group analysis of crude petrolatums.	67
Table 4: Molecular type composition of crude petrolatums.	68
Table 5: Physical characteristics of hard waxes separated from the light slack wax by multistage fractional crystallization at different fractionating temperatures under fixed dilution and washing solvent ratios (S/F) of 6:1 and 2:1 by weight, respectively.	71
Table 6: Carbon number distribution and n-paraffin contents of the hard wax fractions isolated from light slack wax by multistage deoiling at 35, 30, 25 & 20 °C.	77
Table 7: Carbon number distribution and n-paraffin contents of the light slack wax and its saturates and their adducts.	81
Table 8: Physical characteristics of the adducts of the light slack wax, its saturate and the hard waxes separated at different temperatures.	83
Table 9: Carbon number distribution and n-paraffin contents of the adducts of hard waxes isolated	88

from light slack wax at 35, 30 and 20 °C

Table 10:	Effect of dilution solvent ratio on the physical characteristics, molecular type composition and type of the isolated waxes by deoiling of Alexandria crude petrolatum using butyl acetate solvent at fractionating temperature of 20 °C and S/F for washing of 2:1.	91
Table 11:	Effect of dilution solvent ratio on the physical characteristics, molecular type composition and type of the isolated waxes by deoiling of Alexandria crude petrolatum using MIBK solvent at fractionating temperature of 20 °C and S/F for washing of 2:1.	92
Table 12:	Effect of n-alkane non-polar modifier type (concentration = 0.05 wt.%) on the deoiling of crude petrolatum by using butyl acetate solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 2:1 & 2:1, respectively.	106
Table 13:	Effect of n-alkane non-polar modifier type (concentration= 0.05 wt.%) on the deoiling of crude petrolatum by using MIBK solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 2:1 & 2:1, respectively.	107
Table 14:	Effect of a non-polar modifier concentrations; n-C ₂₀ ; on the deoiling of crude petrolatum by using butyl acetate solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 8:1 & 2:1, respectively.	108
Table 15:	Effect of a non-polar modifier concentrations;	109

n-C₂₀; on the deoiling of crude petrolatum by using MIBK solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 8:1 & 2:1, respectively.

Table 16: Effect of a non-polar modifier concentrations; 110

n-C₂₂; on the deoiling of crude petrolatum by using butyl acetate solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 8:1 & 2:1, respectively.

Table 17: Effect of a non-polar modifier concentrations; 111

n-C₂₂; on the deoiling of crude petrolatum by using MIBK solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 8:1 & 2:1, respectively.

Table 18: Effect of a non-polar modifier concentrations; 112

n-C₂₄; on the deoiling of crude petrolatum by using butyl acetate solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 8:1 & 2:1, respectively.

Table 19: Effect of a non-polar modifier concentrations; 113

n-C₂₄; on the deoiling of crude petrolatum by using MIBK solvent at fractionating temperature of 20 °C and S/F for dilution & washing of 8:1 & 2:1, respectively.

Table 20: Effect of addition of 1 wt.% of non-polar 131

modifiers; individual and mixtures of n-alkanes; on the deoiling of crude petrolatum using butyl acetate solvent at fractionating temperature of 20 °C and dilution solvent ratio of 8:1 by weight.

Table 21:	Effect of addition of the prepared non-polar modifier concentrates on the deoiling of crude petrolatum using butyl acetate solvent at fractionating temperature of 20 °C and dilution solvent ratio of 8:1 by weight.	134
Table 22:	The physical characteristics and molecular type composition of the produced hard and slop waxes.	142
Table 23:	Effect of the addition of low density poly ethylene polymer (LDPE) on the physical characteristics and type of microcrystalline wax.	144
Table 24:	The physical characteristics and molecular type composition of the light and heavy paraffin oils.	147
Table 25:	Blend Formulations.	148
Table 26:	Effect of the addition of heavy paraffin oil on the physical characteristics of microcrystalline wax.	149
Table 27:	The physical characteristics and molecular type composition of the produced slop wax, its saturate and the remainder oil.	153
Table 28:	Effect of the addition of light paraffin oil on the physical characteristics of slop wax saturate.	155
Table 29:	The Standard Specifications of US Pharmacopoeia & National Formulary 2011 for the Formulated Blends.	158

LIST OF FIGURES

	Page
Fig. 1: Relationship between melting point and refractive index for different types of hydrocarbons.	12
Fig. 2: Paraffin crystal arrangement.	17
Fig. 3: Stages of wax crystallization.	18
Fig. 4: Carbon number distribution versus n-paraffin contents of light and middle slack waxes.	65
Fig. 5: Effect of fractionating temperature on the yield of hard waxes isolated from light slack wax.	74
Fig. 6: Effect of fractionating temperature on the isolated hard wax quality.	75
Fig. 7: Effect of fractionating temperature on the oil content (a) and needle penetration (b) of the isolated hard waxes.	76
Fig. 8: Carbon number distribution versus n-paraffin contents of the hard waxes isolated from light slack wax at 35, 30, 25 & 20 °C.	78
Fig. 9: Carbon number distribution versus n-paraffin contents of the light slack wax and its saturates.	82
Fig. 10: Carbon number distribution versus n-paraffin contents of the adducts of light slack wax and its saturate.	85
Fig. 11: Carbon number distribution versus n-paraffin contents of the adducts of hard waxes isolated at 35, 30 & 20 °C.	89