Alexandria University
Faculty of Fine Arts
Department of Architecture

THE ROLE OF ENVIRONMENTAL COMPATIBLE MATERIALS FOR ACHIEVING THE ENVIRONMENTAL DESIGN CONCEPT

A Master's Degree Thesis Under Supervision of:

Prof. Dr. Hazem Hamed Ewais

Professor of Urban Planning and Architecture Architecture department – Faculty of Fine Arts

Prof. Dr. Hoda Abdel Kader Azzam

Professor of Urban Planning and Architecture Architecture department – Faculty of Fine Arts

Presented By:

Mai Alaa Eldin Mohammad Karram

Demonstrator in the department of Architecture Faculty of Fine Arts - Alexandria University

2009

ACKNOWLEDGEMENTS

I would like to express my gratitude to my supervisors:

Prof. Dr. Hoda Abdel Kader Azzam for her continues support, guidance, encouragement and her interest throughout the development of this thesis. And also Prof. Dr. Hazem Hamed Ewais for his help and support.

I must also express my gratitude to Dr. Salah Eldin Haridy for his helpful support in this research, and also express my gratitude to my colleagues especially Eng. Ahmad Hasan and Eng. Raham Ahmad and every one who was by my side in this work.

I would like as well to express my great thanks to my mother, father, brother and husband, who always were very patient with me and encouraged me a lot through this work.

Dedicated to my **Mother**

TABLE OF CONTENTS

Acknowledgement	i
Table of contents	iii
List of figures	iii
_ist of tables	iii
List of abbreviations	iii
Introduction	1

Part One: An Approach to Environmentally Compatible Materials

Chapter 1: Definition of Environmentally Compatible Materials and their Green Features.

1-0: Introduction	3
1-1: Principles of environmental concept	3
1-1-1: Healthful interior environment.	3
1-1-2: Energy efficiency	3
1-1-3: Ecologically safe materials	3
1-1-4: Environmental form	3
1-1-5: Good design	
1-2: Compatibility concept of environmental materials	4
1-3: Life cycle phases of environmental compatible materials	4
1-3-1: Pre-Building Phase	
1-3-1-1: Increased exploitation of smaller sources of raw materials:	6
1-3-1-2: Greater attention to unused resources and waste production:	
1-3-1-3: Increased exploitation of rich fields of researches:	
1-3-1-4: Increased use of renewable resources:	
1-3-1-5: Increased recycling of waste products during production;	
1-3-2: Building Phase	
1-3-2-1: Economical construction:	
1-3-2-2: Reduced loss of building materials:	
1-3-2-3: High durability:	
1-3-3: Post-Building Phase	
1-3-3-1: Definition of recycling process:	
1-3-3-2: Levels of recycling process:	
1-3-3-3: Assembly for disassembly (ADISA) principle:	
1-4: Green features of environmentally compatible materials along their life cyc	cle15
1-4-1: Manufacturing Process (MP)	
1-4-1-1: Waste Reduction (WR):	
1-4-1-2: Pollution Prevention (P2):	
1-4-1-3: Recycled Content (RC):	
1-4-1-4: Embodied Energy Reduction (EER):	
1-4-1-5: Natural Materials (NM):	
1-4-2: Building operations (BO)	
1-4-2-1: Energy Efficiency (EE):	
1-4-2-2: Water Treatment/conservation (WTC):	
1-4-2-3: Use of non-toxic or less-toxic materials (NT):	
1-4-2-4: Renewable Energy Source (RES):	
1-4-2-5: Longer Life (LL):	. 20

1-4-3: Waste Management (WM)	
1-4-3-1: Biodegradablility (B):	20
1-4-3-2: Recyclability (R):	20
1-4-3-3: Reusability (RU):	20
1-5: Conclusion	22
Chapter 2: Green Features of both of Conventional and Innovative Enviro	nmentally
Compatible Materials.	
	22
2-0: Introduction	
2-1: Green features of conventional environmentally compatible materials	
2-1-1: Definition of conventional environmentally compatible materials	
2-1-2: Examples for conventional environmentally compatible materials:	
2-1-3: Green features of examples for conventional environmentally compati	
materials:	
2-1-3-1 Green features of brick:	
2-1-3-2 Green features of aluminum:	
2-1-3-3 Green features of limestone:	
2-1-3-4 Green features of concrete	31
2.2. Crean factures of innovative environmentally compatible metarials.	2.4
2-2: Green features of innovative environmentally compatible materials: 2-2-1 Definition of innovative environmentally compatible materials	
2-2-2 Examples for innovative environmentally compatible materials	
2-2-2-1 Smart materials:	
2-2-2-1 Definition of smart materials:	
2-2-2-1-1 Bernhuon of smart materials:	
2-2-2-1-3 Characteristics of smart materials:	
2-2-2-1-4 Types of smart materials:	
Type 1 - Property of changing in Smart materials:	
Type 2 - Energy exchanging in smart materials:	
2-2-2-1-5 Green features of smart materials:	
2-2-2-1-6 Applications for using smart sustainable materials:	
2-2-2-2 Nanomaterials:	
2-2-2-1 Definition:	
2-2-2-2 Categories of nanomaterials:	
2-2-2-3 Classification of nanomaterials:	
2-2-2-4 Green features of nanomaterials:	
2-1-2-5 Applications for using environmental nanomaterials:	
2-3: Conclusion	
Chapter 3: The Relation between Environmental Concept and its Environmental	mental
Forces.	
3-0: Introduction	62
3-1: Definition of environmental forces	62
3-2: Classification of environmental forces	62
3-2-1: Thermal force	
3-2-2: Lighting force	
3-2-3: Acoustics force	
3-2-4: Water & waste force	63

3-3: Environmental forces of building envelope:	
3-4: The integration between environmental concept and thermal force 65	
3-4-1: Categories of thermal force: 65	
3-4-2: Strategies of heating systems:	
3-4-3: Strategies of passive cooling systems	
3-5: The integration between environmental concept and lighting force	
3-5-1: Types of lighting systems	
3-5-2: Strategies of lighting systems	
3-5-3: Strategies of natural lighting	
3-5-4: Strategies of artificial lighting	
3-6: Conclusion	
Part Two: Impact of Using Environmental Compatible Materials on Building	
Envelope to Control on the Environmental Forces	
Introduction74	
Charter A. Farrianna and I.C. and Alla Materials and Canada Harman Thomas I.F.	
Chapter 4: Environmental Compatible Materials as Controllers on Thermal Force of a Building	
or a bunding	
4-0: Introduction	
4-1: Materials of building envelope for heating systems:	
4-1-1 Thermal mass materials:	
4-1-1-1 Criteria of selecting the thermal mass materials:	
4-1-1-2 The design requests of thermal mass materials:	
4-1-1-3 Examples of thermal mass materials:	
4-1-2 Thermal insulation materials: 97	
4-1-2-1 Criteria of selecting thermal insulation materials:	
4-1-2-2 The design requests of thermal insulation materials:	
4-1-2-3 Examples for thermal insulation materials:	
4-1-2-3-1 Loadbearing thermal insulation materials (structure):	
4-1-2-3-2 Non-loadbearing thermal insulation materials:	
4-1-3 Glazing for thermal gain systems:	
4-1-3-1 Glazing design requests for thermal gain systems: 121	
4-1-3-2 Glazing examples for thermal gain systems:	
4-1-4 The calculations of composite thermal walls design (thermal mass and	
insulation material):	
4-1-4-1 The total thermal transmittance (U- value) calculations:	
· · · · · · · · · · · · · · · · · · ·	
4-1-4-2 Thermal Time Constant (TTC) Calculations: 126	
4-2: Materials of building envelope for cooling systems	
4-2-1: Thermal mass materials	
4-2-3: Glazing for cooling systems 128	
4-2-3-1 Shading elements: 128	
4-2-3-1-1 Fixing of Shading:	
4-2-3-1-2 Fixing of Shading:	
4-2-3-2: Ventilation:	
4-2-3-3: Insulation:	
4-3: Conclusion	

Chapter 5: Environmental (Compatible Materials	as Controllers on	Lighting Force
of a Building			

5-2-1 The design criteria of natural lighting:	
5-2-2 The design criteria of artificial lighting:	144
5-3: Materials of building envelope for lighting systems	144
5-3-1 Natural lighting systems:	144
5-3-2: Natural lighting materials for	147
5-3-2-1-1 Glass with coating films:	148
5-3-2-1-2 Switchable glass (smart glass):	151
5-3-2-1-3 Multiple glass:	
5-3-2-1-4 Cavity glazing:	
5-3-2-1-5 Transparent plastics:	
5-3-2-2 Materials of reflecting surfaces (shelves):	153
5-3-2-3 Glazing for optical daylight systems:	
5-3-2-3-1 Tubular skylights:	
5-3-2-3-2 Optical fibers:	
5-3-2-4 Translucent mass materials:	
5-3-2-4-1 Translucent Concrete:	
5-3-2-4-2 Prada foam:	
5-3-3 Artificial lighting systems:	
5-3-4 Artificial lighting materials for:	
5-3-4-1 Lamps with low power consumption:	
5-3-4-1-1 Incandescent light bulb with dimmer:	
5-3-4-1-2 Fluorescent:	
5-3-4-1-3 High Intensity Discharge (HID):	
5-3-4-1-4 Light Emitting Diode (LED):	
5-3-4-2 Lamps with lighting controls:	
5-3-4-2 -1 Lighting controls components:	
5-3-4-2-2 Lighting controls categories:	
5-3-4-2-2-1 Occupancy detectors:	
5-3-4-3 Lamps with sustainable energy for producing electricity:	
5-3-4-3-1 Wind energy:	
5-3-4-3-2 Solar energy:	
5-3-4-3-3 Waste energy:	
5-3-5 Integration between natural and artificial lighting:	
5-3-5-1 Location:	
5-3-5-2 Shielding:	
5-3-5-3 Control:	
5-3-5-4 Color:	
5-4: Conclusion	
Part Three: Applications for Using Environmentally Compatible Mater	rials
Chapter 6: Example for using Environmentally Compatible Materials	to control on
Environmental Forces (Mont Cenis Training Centre)	
6-0 Introduction	179

6-1: The data of project "Mont Cenis Training Centre"
6-2: The environmental design concept
6-3: Strategies of controlling the environmental forces
6-3-1: Thermal system strategies
6-3-1-1 The Strategy of heating system: 181
6-3-1-2 The strategy of cooling system:
6-3-2 Lighting system strategies
6-3-2-1 Natural lighting strategy:
6-3-2-2 Artificial lighting strategy: 183
6-4: Materials and construction of building 184
6-4-1 Structure of microclimatic envelope:
6-4-2: Building envelope
6-4-2-1 Façade elements: 185
6-4-2-2 Roof elements:
6-4-2-3 Services elements: 188
6-5: Environmental assessment of building performance
6-5-1: Energy use of microclimatic envelope
6-5-2: Temperature
6-5-3: Natural ventilation
6-6: Conclusion
Chapter 7: Assessment of Environmental Architecture Performance for
Environmentally Compatible Materials
·
7-0: Introduction
7-1: Concept of assessment
7-2: Elements of assessment
7-2-1: Physical properties
7-2-1-1: Natural properties (non-environmental properties)
7-2-1-2: Natural properties (environmental properties)
7-2-2: Climate considerations 194
7-2-2-1: Temperature
7-2-2-2: Sun
7-2-2-3: Rain
7-2-2-4: Wind
7-2-2-5: Humidity
7-2-3: Architectural requirements 196
7-2-3-1: Function
7-2-3-2: Form:
7-2-3-2. Politi
7-4: Concept of assessment
7-4-1 Assessment of environmental compatibility for thermal mass materials:201
7-4-1 Assessment of environmental compatibility for thermal insulation materials: 201
7-4-2 Assessment of environmental compatibility for glazing materials:201 7-4-3 Assessment of environmental compatibility for glazing materials:201
7-4-4 Assessment of environmental compatibility for louvers materials:201
7-5: Conclusion
Defenences
References
Glossary
English summary
Arabic summary

LIST OF FIGURES

Figure no.	
Chapter 1: Definition of Environmentally Compatible Materials and their Gr	reen
Features	

1.1: Elements of compatibility for environmental materials	
1.2: Life Cycle analysis of environmentally compatible materials	5
1.3: The three Life Cycle phases of materials	5
1.4: Examples for re-evaluated resources	7
1.5: Diagram refers to the three principles of (ADSIA)	12
1.6: Sharing layers of change	
1.7: a-Multimaterial component.	
b-monomaterial component	14
1.8: Design processes and life cycle phases of material	
1.9: Diagram for green features	
1.10: Percentages for the different reusing ways of rainwater	
1.11: Rainshow shower & bath filters	
1.12: Process of recycling rainwater	
1.13: Reusing glass bottles in constructing a wall	
Chapter 2: Green Features of both of Conventional and Innovative Environment	ntally
Compatible Materials.	<i>J</i>
•	
2. 1: The six general phases of brick manufacturing	24
2. 2: Aggregates from brick used in infrastructure works	
2. 3: Aggregates for in-situ and precast concrete and mortars	
2. 4: Reusing old brick in new buildings	
2. 5: Life cycle of Aluminum	
2. 6: The steps of bauxite mining	
2. 7: Conference Centre, Glasgow designed by Foster & Partners, constructed	
aluminum shells	
2. 8: Drinkers cans which can be recycled	
2. 9: A 27 tonne ingot made from approximately 1.5 million used drinks cans	
2.10: The heavy equipments which are used in extracting limestone	
2.11: Phases in the life cycle of a concrete	
2.12: Casting of self compacting concrete	
2.13: The original shape of material(in yellow)the transformed shape (in red)	
2.14: Thermochromic wall of "housewarming" exhibition	
2.15: Covering for chairs from thermochromic material (HeatSeats)	
2.16: Construction of type of SRT	
2.17: (a) The picture is an SRT laminate	
(b) The blue film at 75°C	40
2.18: photochromic windows respond to changes in light	
2.19: Isometric section illustrates the basic design of an electrochr	
device	
2.20: Flip a switch and an electrochromic window	
2.21: Schematic diagram of a five-layer electrocromic coating	
2.22: The parts (5 layers) that make up SPD light-control windows:	
2.23: SPD light-control window before and after passing an electrical current	
2.22. 2.2 fight condition which before and after passing an electrical cultions.	5

2.25:	Outside surface covered in 460 BIPV modules - Photovoltaic 'tree'43	3
2.26	Types of photovoltaics44	1
2.27:	Light emitting diodes44	
2.28:	LEDs are produced in an array of shapes and sizes	
	The 1,500 foot long LED display45	
	Using Phosphorescence materials to achieve Safety in public buildings and	
_,,,	workplaces at night times	
2 31	Examples for using Flexible Electroluminescent cables	
	Examples of laser types (basic principle)	
	Behavior of piezoelectric materials	
	In a Peltier device an input electrical current	
	Microscopic Diagram of the Shape Memory Effect	
	A sample of "smart" plastic	
2.3/3	This series of images show how the biodegradable shape memory polymer	
	transforms from the temporary shape	
	The convergence of parts of the smart and sustainable domains	
2.39:	Integrating a building's technology systems and constructing a sustainable	
	or "Green" building50	
	BIPV system diagram51	
2.41:	The 1,200m ² photovoltaic wall curves from the roof to the ground52	
2.42:	Evacuated Tube Solar Thermal Awning, Los Gatos CA52	
2.43:	Photovoltaic shingles look similar to asphalt shingles52	2
2.44:	System of using PVs in generating electricity, and producing hydrogen	to
	power fuel cell buses53	
2.45	Semi-Transparent PV Skylight53	
	Ricoh Stadium54	
	A picture of nanofibers shown with a human hair for reference54	
	Anti-Reflection (AR) Coated Glass for Solar56	
	Antireflective Glass for PV, Display, Framing, Lighting	
	Cubes from aerogel (frozen smoke or blue smoke)	
	Aerogel insulating a flower from a Bunsen burner flame57	
	Installed pipes with aerogel (two layers of 4 mm)	
	Aerogel interior wall panels	
	The slim solar panels were fixed on building roof	
2.55	Section in aerogel window	
	Surface of Superhydrophobic wood "Lotus Spray"60	
	The Superhydrophobic wood surface appearance under microscope60	
	The left tile is normal (not clean)60	
	Phases of self cleaning glass61	
2.60:	The difference between standard glass and treated glass (self-cleaning glass))
	after one year of exposure61	
Chapter 3	: The Relation between Environmental Concept and its Environmental	
	Forces.	
	Categories of environmental forces and their elements	
	The general and environmental requirements of building envelope64	
	Types of lighting (natural, artificial lighting)69	
	Strategies of natural lighting according to their types71	
3.5:	Strategies of artificial lighting according to their types72	

Chapter 4: Environmental Compatible Materials as Controllers on Thermal Force of a Building

4.1: Thermal mass in winter (store heat during the day and re-emit it at night)75
4.2: The influence of thermal mass
4.3: Chart illustrates the relation between different thickness for materials and
their diurnal heat capacity (dhc)77
4.4: Time lag hours of material along the day hours77
4.5: Using plants and shading elements in the southern elevations to avoid the
over heating in summer
4.6: Size south-facing overhangs to properly shade windows
4.7: The three types of stone and examples for these types80
4.8: Southern wall from stone, used in direct gain system
4.9: a) 1 st layer, Trombe wall from stone (inside the steel grid).2 nd layer
glazing83
4.10: In this building the spaces that are related to the sunspace are constructed
from stone (walls and floors)83
4.11: Types of loam building materials
4.12: Loam using as thermal mass
4.13: Shape of the newly developed unburned clay block
4.14: In this building direct gain system achieved with glazing area for south
façade and thermal mass from loam
4.15: translucent concrete blocks
4.16: Trombe wall from treated concrete90
4.17: Sunspace attached to concrete wall and concrete floor90
4.18: The hole for collecting rain water in the rain water storage91
4.19: Units of water wall. In the side of wall, points of locking between units
could appear91
4.20: (a) Thermal curtain wall with water tube storage
(b) Water wall modules by one design inc92
4. 21: Examples for constructing water wall from plastic which is related to the
building92
4.22: using water wall glazing tanks beneath south-facing windows92
4.23: Rolls filled with phase change material94
4.24: Gypsum PCM SmartBoard as a front wall plus a Micronal PCM
SmartBoard-modified chilled ceiling94
4.25: Blades filled with a phase change material94
4.26: SmartBoard plasterboard has a thickness of only 1.5 cm, of the storage94
4.27: The two uses of panel strikes95
4.28: The fine tubes set at right angles between two sheets of glass that cover the
two sides of tubes95
4.29: Cross section in the plastic translucent thermal insulation96
4.30: The system of heat transmission (the wall is screened with curtain)96
4.31: Mechanisms for heat transfer (conduction, convention and radiation)97
4.32: Difference between the outdoor temperature changing along time of day,
and the indoor temperature
4. 33: Passage of heat through thermal bridges
4.34: movable insulation at building windows to prevent heat loss100
4.34: movable insulation at building windows to prevent near loss
*
4.36: Foamed Concrete 102
4.37: Porous of aerated concrete panels

4.38: Interlocking aerated Concrete blocks
4.39: Panels and Blocks based on lightweight aggregate mixes
4.40: Fly ash talcum powder
4.41: Fly Ash Contributes to Concrete Durability and Strength
4.42: Types of straw according to their construction method, and their
loadbearing classification
4.43: Dimensions and form of two-wires straw bale
4.44: Build a rubble trench foundation
4.45: Loadbearing wall constructed from straw bales
4.46: Indirect gain windows, thermal mass floor, straw bale walls109
4.47: Using straw bales as a structural material (load-bearing)
4.48: classification of non-loadbearing insulation materials occurred to their raw
materials
4.49: IR absorber modified Polystyrene
4.50: The principle of infrared absorber
4.51: Sheets of foamglass and glasswool (used here as a wall insulator)111
4.52: Layers of vacuum insulation panel
4.53: Open-pore melamine resin foam: the pores that enable the exchange of gas
are clearly visible
4.54: Light-permeable thermal insulation panel, filled with Aerogel112
4.54. Light-permeable thermal histilation paner, fined with Aeroger
like bricks in this post-and-beam structure
4.56: Using metal wire to further tighten the metal lath after it has been sewn
into place
4.57: plastering the lower half of each wall from the ground, and did the upper
half on scaffolding
4.58: Steps of strawboards production
4.59: An example for using straw boards as wall insulators and interior partition.
4.60: Roof building thatched with straw
4.61: Cellulose fibers
4.62: Types of loam building materials
4.63: Boards of non-loadbearing loam
4.64: Processing loam plaster by machine
4.65: Boards of expanded polyurethane foam
4.66: Using polyurethane boards as building skin
4.67: Building skin from polyureythane(seamless, monolithic appearance)118
4.68: The four types of transparent thermal insulation materials
4.69: The front elevation of the bus terminal that it consists entirely of
polystyrene foam
4.70: Deformation of polystyrene building skin to be used as existing
benches
4.71: The performance of a typical single clear glass
4.72: The performance of a typical double-glazed unit with two layers of clear
glass
4.73: Transfer of heat through low-E double glazing system
4.74: The performance of a window with a very low heat loss rate (low U-
factor)
4.75: The interface of the software application that calculates U-value126
4.76: Case #1: wall with external insulation
4.77: Case #1: wall with internal insulation

4.78: Thermal mass in summer absorb heat during the day and allow cool nig	ht
breezes	
4.79: shading systems (fixing – position)	
4.80: Fixed shading to south façade can achieve sun protection along t day	he
4.81: The relationship between sun altitudes in summer and winter, and the	
suitable louver angle for them	
4.82: Movable glass louvered sun screening system in summer and winter130	
4.83: Example for sun sensor	
4.84: Example for battery pack system	
4.85: Example for Movable aluminum louvers	
4.86: Example for Movable glass louvers	
4.87:Example for Movable fabric louvers	
4.88: Examples for Movable acrylic louvers	
4.89: the five systems of movable louvers installation	
4.90: Types of insulating glass. (The shaded types are the related types to	
thermal insulation).	
4.91: The photovoltaic double-glazed systems of heat-reflective glass in	
summer and winter	
4.92: Types of Window Frames	
Chapter 5: Environmental Compatible Materials as Controllers on Lighting Force	<u>.</u>
of a Building	
5.1: Types of lighting types (natural, artificial lighting)	2
5.2: Systems of natural lighting	
5.3: Glass types (according to their light force control)147	
5.4: Difference between reflection of glass and reflection of AR film148	
5.5: Single layer AR coating on a transparent substrate (glass)149)
5.6: A three layer AR coat can be thought of as a central layer with single layer	r
anti-reflection each side149	
5.7: How the UV coating works. The UV COATING reduces the ultra-viol	
component of the emission light to a negligible value150	
5.8: Difference between reflection of glass and reflection of AG film150	
5.9: a)Glass is switched off (the liquid crystals	
5.10: Multiple glass types (systems)	
5.11: performance of light reflection on highly reflective shelve (incidence an	gle
θ 1= reflection angle θ 2)	
5.12: Reflectance values for some painting colors. Colors with high values a	
suitable to be shelves145	
5.13:Reflectance values for common building materials. Materials with high	
values are suitable to be shelves145	
5.14: Light reflectance value (LRV) runs on a scale from 0% to 100%154	
5.15: light shelves (from inside) with high reflectance, used to reflect sunligh	
onto the interior spaces (painted with white)	
5.16: performance of light reflection inside the tubular skylights (incidence angle	
from 40° to 13.8°)	
5.17: Section in a roof building with tubular skylight, the three componer appears	
5.18: The sun pipes in the british school in Abu Dhabi	
5.19: Fiber Optic Total Internal Reflection	
C12. 1 1301 Optic 1 out internal reflection	•

5 20	TEL
	The two main types of fiber
5.21	: Difference between graded-index multimode, step-index multimode and
	single-mode optical fibers
	: The two main types of fiber
5.23	: Prada foam used as a wall in a store. Light passes throw hollows in
	concrete
5.2 4	: Systems of artificial lighting (According to achievement of environmental
	concept)
5.25	: Assorted types of fluorescent lamps. Top, two Compact fluorescent lamps,
	bottom, two regular tubes. Matchstick shown for scale161
5.26	: Different high pressure sodium lamps
	: Different HID metal halide lamps
	Blue, green, and red LEDs
	: Close-up of a typical LED in its case, showing the internal structure164
	Light control components and their functions
	: The three components (Inputs, Decision-making (master lighting controller)
3.31	Outputs) of some lighting control systems
5 3 3	: Occupancy sensor control system (The relationship between the power
3.32	supply, relay, controller and motion detector)
5 22	
	: Infrared Sensor Coverage Patterns
	: Ultrasonic Sensor Coverage Patterns
	: Typical sensitivity pattern for wall-mounted ultrasonic sensor
	: Types and examples for sensor products
	: A lighting column powered by wind turbine
	Solar Tree seat and light
5.39	: Lighting units with self-charging from solar energy – used in outdoor
	lighting
5.40	: Lighting unit with PIR Solar (Post-Wall Light) made from Stainless
	Steel
5.41	: a) The interior of the hall during the daytime.
	b) The interior of the hall at night time, showing the similarity in lighting
	conditions from both daylighting and artificial lighting
5.42	: Daylight factor distribution through Brune park174
5.43	: microbial fuel cell (bacteria cell)
5.44	: Dry steam power plant system175
Chapter	6: Example for using Environmentally Compatible Materials to control on
	Environmental Forces (Mont Cenis Training Centre)
6.1:	Site plan of project
6.2:	Cross section in the project, showing the environmental requirements that
	achieved by the building envelope 'glazed envelope'180
6.3:	Section in the building illustrates heating strategy in winter181
6.4:	Section in the building illustrates cooling strategy in summer182
6.5	Lightshelves on the inner building façade
	Image from inside the truncated cones of library183
	Detail in the connection between column and beam (steel connection),
	and cables between structure elements
6.8:	The timber structure is reminiscent of Victorian boat building sheds
	-
	(columns and beams)

	of building with its glazing area and photovoltaic		
	185		
6.10: The louvered openings	and roof vents on the building façade186		
6.11: Photovoltaic cells shad	ing on floor and building walls		
6.12: Image for photovolta	ic cells (of facades) from inside the building.		
(translucent)	186		
6.13: The combination between	ween glazing and photovoltaic cells in building		
roof. Glazing is opened	in some positions to exhaust the warm air 187		
	that are installed on the roof187		
	otovoltaic cells on the roof. (Clear glass over the		
central thoroughfare)	188		
	with the varying densities of photovoltaic panels		
	ouds>>188		
6.17: The chart shows how the	he temperature varies in different season		
6.18: Simulation of air move	ment in the glass house		
	_		
Chapter 7: Assessment of Environmental Architecture Performance for			
Environmentally Comp	atible Materials		
7.1: Diagram for suggested a	assessment of environmentally compatible materials		
and its compatibility con	abination between climate and architecture192		
7.2: The combination betwe	en architecture and its climate, and the specified		
	ble material for this combination193		
	nap196		
	al compatible materials and their studied physical		
	198		
1 1	hysical properties and environmental architectural		
<u> </u>	puts)200		
` 1			