



Effect Of Ionizing Radiation On The Prepared Thermoplastic Polymer And Wax Blend For Use In Some Industrial Applicatoins

By

Ahmed Abd EL Daym Mahmoud

A Thesis Submitted in Conformity with the Requirements for the Degree of Ph.D. Degree in Science (Physics – Solid State)

Supervisors

Prof. Dr. Hayam Abd EL-Aziz Ali EL-Zahed

Prof. of Solid State Physics Dept.,
Faculty of Women for Arts, Science and Education,
Ain-Shams University.

Ass. Prof. Dr. Saleh Mahmoud Abdou

Ass. Prof. of Radiation Physics,
National Center for Radiation Research and Technology(NCRRT).

Ass. Prof. Dr. Husein Husein EL-Nahas

Ass. Prof. of polymer chemsity,
National Center for Radiation Research and Technology(NCRRT).

2016

Supervision Committee

Effect Of Ionizing Radiation On The Prepared Thermoplastic Polymer And Wax Blend For Use In Some Industrial Applicatoins

By

Ahmed Abd EL Daym Mahmoud

**A Thesis Submitted in Conformity with the Requirements for the
Degree of Ph.D. Degree in Science (Physics – Solid State).**

Approved by:

Signature

Prof. Dr. Hayam Abd EL-Aziz Ali EL-Zahed

Prof. of Solid State Physics Dept.,
Faculty of Women for Arts, Science and Education,
Ain-Shams University.

Ass. Prof. Dr. Saleh Mahmoud Abdou

Ass. Prof. of Radiation Physics,
National Center for Radiation Research and Technology (NCRRT).

Ass. Prof. Dr. Husein Husein EL-Nahas

Ass. Prof. of polymer chemsity,
National Center for Radiation Research and Technology(NCRRT).

Acknowledgement

First of all, thanks for ALLAH for enabling me to finish this work.

I wish to express my deep thanks and gratitude to ***Prof. Dr. Hayam Abd EL-Aziz Ali EL-Zahed*** Prof. of Solid State Physics Dept., Faculty of Women for Arts, Science and Education, Ain-Shams University. for her continuous encouragement, guidance, constructive comments, support and direct supervision.

I would like to express gratefulness and my deep thanks to ***Ass. Prof. Dr. Husein Husein EL-Nahas*** Ass. Prof. of polymer chemistry, National Center for Radiation Research and Technology(NCRRT). for his direct supervision, encouragement and appreciated support .

It is great pleasure to express my deep indebtedness and sincere gratitude to ***Ass. Prof. Dr. Saleh Mahmoud Abdou*** Ass. Prof. of Radiation Physics, National Center for Radiation Research and Technology (NCRRT). for his direct supervision, appreciated support, encouragement, and valuable advises towards the completion of this work.

Also Thanks to staff and members of the National Centre for Radiation Research and Technology.

List Of Publications

Contents

Contents

Acknowledgment	
List of Publications	
Contents	
List of figures	
List of tables	
Abstract	

Chapter (1) Introduction and Literature Survey

1. Introduction	1
1.2 Literature survey	4
1-3 Aim of the work	9

Chapter (2) Theoretical Considerations

2.1 Polymer blends	11
2.2 Types of Polymer Blends	11
2.3 X ray diffraction (XRD)	12
2.4 Mechanical properties of polymer	14
2.4.1 Stress-Strain Behavior	14
2.4.2 Elastic Modulus (Young's modulus)	15
2.4.3 Hardness	15
2.5 Thermal properties of polymer	15
2.5.1 Differential scanning calorimetry	15
2.6 Thermogravimetric analysis (TGA)	16
2.6.1 Method of Horowitz and Metzger	16
2.7 Uv-vis spectroscopy	19
2.7.1 Optical band gap and band tail	20
2.6 Electric properties	22
2.6.1 Dielectric properties of polymeric materials	22
2.6.3 Ionic Conduction:	24
2.6.4 Transport Mechanism	24
2.7 Effect of radiation on polymeric materials	25
2.7.1 Cross linking of polyethylene	26
2.7.2 Degradation of polyethylene	26
2.7.3 Oxidation of polyethylene	27

Chapter (3) Experimental Techniques

3.1 Materials and method	28
3.2 X- Ray diffraction (XRD)	29
3.3 Scanning Electron Microscope (SEM).	30
3.4 Mechanical measurements.	30

Contents

3.4.1 Surface Hardness.	31
3.6 Thermal properties	31
3.6.1 Differential scanning calorimetry (DSC)	31
3.6.2 Thermogravimetric analyses (TGA)	31
3.6.3 Melt flow index of blends (MFI)	32
3.7 Optical properties	32
3.8 AC conductivity	32
3.9 Gamma Irradiation	32

Chapter (4) Results and Discussions

4.1 Structure analysis X- Ray diffraction (XRD)	33
4.1.1 Crystallite size L	33
4.1.2 Dislocation density \square .	34
4.1.3 Inter-chain distance (r) and the inter-planar spacing (d)	35
4.1.4 Micro-strain ϵ and distortion parameters g	36
4.2 Surface morphology	39
4.3 Mechanical properties	44
4.3.1 Tensile Strength (TS).	44
4.3.2 Elongation at break (Eb).	45
4.3.3 Young's Modulus	47
4.3.4 Hardness Test	48
4.4 Thermal properties	49
4.4.1 Differential scanning calorimetry (DSC)	49
4.4.2 Thermogravimetric analysis (TGA)	54
4.4.3 Degradation kinetic analysis	59
4.4.4 Melt flow index (MFI)	63
4.5 Optical properties	64
4.5.1 The optical band gap (E_g^{opt})	64
4.5.2 Urbach energy E_u	69
4.6 Electrical Measurements	73
4.6.1 Dielectric Characterization	73
4.6.2 The ac conductivity (σ_{ac})	79
Conclusion	83
References	86
Arabic Summary	

List of Figures

List of Figures

Figure No.

- Fig. (4-1) Shows X- ray diffraction of the pure LDPE, pure paraffin wax and LDPE / paraffin wax blends with different paraffin wax ratios for un-irradiated samples.
- Fig. (4-2) Shows X- ray diffraction of the pure LDPE, pure paraffin wax and LDPE / paraffin wax blends with different paraffin wax irradiated at 25 kGy.
- Fig. (4-3) Shows X- ray diffraction of the pure LDPE, pure paraffin wax and LDPE / paraffin wax blends with different paraffin wax irradiated at 50 kGy.
- Fig. (4-4) Shows X- ray diffraction of the pure LDPE, pure paraffin wax and LDPE / paraffin wax blends with different paraffin wax irradiated at 75 kGy.
- Fig. (4-5) SEM micrographs of pure samples and some LDPE/paraffin wax blends with different paraffin wax ratios.
- Fig (4.6) SEM micrographs of pure samples and LDPE/paraffin wax blends with different paraffin wax ratios at different gamma irradiation doses.
- Fig. (4-7) Shows the changes in tensile strength as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4-8) shows the changes in elongation at break as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4-9) Shows the changes in Young's modulus as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4.10) Shows the changes in hardness as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.

Figure No.

- Fig. (4-11) DSC heating curves of pure samples and the LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-12) DSC heating curves of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy.
- Fig. (4-13) DSC heating curves of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy .
- Fig. (4-14) DSC heating curves of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 75 kGy .
- Fig. (4-15) Shows the changes in melting temperature (T_m) as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4-16) Shows the changes in the melting enthalpy (ΔH_m) as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4-17) TGA thermogram of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-18) TGA thermograms of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy
- Fig. (4-19) TGA thermograms pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy.
- Fig. (4-20) TGA thermograms of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation at 75 kGy.
- Fig. (4-21) shows the changes in the temperature of T_5 % degradation as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.

Figure No.

- Fig. (4-22) Plots of $\ln\{\ln[(W_0 - W_f)/(W_t - W_f)]\}$ against Θ of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-23) Plots of $\ln\{\ln[(W_0 - W_f)/(W_t - W_f)]\}$ against Θ of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy.
- Fig. (4-24) Plots of $\ln\{\ln[(W_0 - W_f)/(W_t - W_f)]\}$ against Θ of pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy.
- Fig. (4-25) Plots of $\ln\{\ln[(W_0 - W_f)/(W_t - W_f)]\}$ against Θ of pure sample and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 75 kGy.
- Fig. (4-26) Shows the changes in the activation energy (E_a) as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4-27) Shows the changes in the melt flow index (MFI) as a function of wax content for the pure LDPE and LDPE /paraffin wax blends before and after gamma irradiation.
- Fig. (4-28) The plots of $(\alpha h\nu)^2$ vs. $E = (h\nu)$ of the un-irradiated pure samples and un-irradiated LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-29) The plots of $(\alpha h\nu)^2$ vs. $E = (h\nu)$ of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy.
- Fig. (4-30) The plots of $(\alpha h\nu)^2$ vs. $E = (h\nu)$ of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy.
- Fig. (4-31) The plots of $(\alpha h\nu)^2$ vs. $E = (h\nu)$ of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 75 kGy.

Figure No.

- Fig. (4-32) The logarithm variation of absorption coefficient $\ln(\alpha)$ versus photon energy ($E=h\nu$) of the un-irradiated pure samples and Un-irradiated LDPE / paraffin wax blends with different paraffin wax.
- Fig. (4-33) The logarithm variation of absorption coefficient $\ln(\alpha)$ versus photon energy ($E=h\nu$) of the pure samples and LDPE / paraffin wax blends after irradiation with 25 kGy.
- Fig. (4-34) The logarithm variation of absorption coefficient $\ln(\alpha)$ versus photon energy ($E=h\nu$) of the samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy.
- Fig. (4-35) The logarithm variation of absorption coefficient $\ln(\alpha)$ versus photon energy ($E=h\nu$) of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 75 kGy.
- Fig. (4-36) The dielectric constant (ϵ') as versus frequency of the un-irradiated pure samples and Un-irradiated LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-37) The dielectric loss (ϵ'') versus frequency of the un-irradiated pure samples and LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-38) The dielectric constant (ϵ') as versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy.
- Fig. (4-39) The dielectric constant (ϵ') as versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax after irradiation with 50kGy.
- Fig. (4-40) The dielectric constant (ϵ') as versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 75 kGy.

Figure No.

- Fig. (4-41) The dielectric loss (ϵ'') versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy.
- Fig. (4-42) The dielectric loss (ϵ'') versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy
- Fig. (4-43) The dielectric loss (ϵ'') versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 75 kGy
- Fig. (4-44) The ac conductivity (σ_{ac}) versus frequency of the un-irradiated pure samples and LDPE / paraffin wax blends with different paraffin wax ratios.
- Fig. (4-45) The ac conductivity (σ_{ac}) versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 25 kGy.
- Fig. (4-46) The ac conductivity (σ_{ac}) versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax ratios after irradiation with 50 kGy.
- Fig. (4-47) The ac conductivity (σ_{ac}) versus frequency of the pure samples and LDPE / paraffin wax blends with different paraffin wax after irradiation with 75 kGy.

List of Tables

List of Tables

Table No.

Table (4-1) The crystallite size and dislocation density of the pure sample and LDPE/paraffin wax blend sample for both un-irradiated and irradiated samples at different gamma irradiation doses.

Table (4-2) The inter-chain distance and inter planar spacing of the pure sample and LDPE/paraffin wax blends for both un-irradiated and irradiated samples at different gamma irradiation doses.

Table (4-3) Micro-strain (ϵ) and distortion parameters (g) of the pure sample and LDPE/paraffin wax blends for un-irradiated and irradiated samples at different gamma irradiation doses.

Table (4-4) DSC results of pure samples and LDPE / paraffin wax blends for both un-irradiated and irradiated blends at different gamma irradiation doses.

Table (4-5) Temperatures of 5 % degradation of pure samples and LDPE / paraffin wax blends for both un-irradiated and irradiated blends at different gamma irradiation doses.

Table (4-6) Activation energies of thermal degradation for pure samples and LDPE / paraffin wax blends for both non radiated blends and radiated blends at different gamma irradiation doses.

Table (4-7) The optical band gap E_g^{opt} (eV) of the pure samples and LDPE /paraffin wax blends before and after gamma irradiation.

Table (4-8) Urbach energy E_u (eV) of the pure samples and LDPE /paraffin wax blends before and after gamma irradiation.