

Acknowledgments

Firstly, I would like to thank **Allah** for leading me towards this topic also I want to express my sincere gratitude to my advisor **Prof. Dr. Hisham Sameh** and **Dr. Tamer Abdel-Aziz** for the continuous support of my Thesis study and research, for their patience, motivation, enthusiasm, and immense knowledge. Their guidance helped me in all the time of research and writing of this thesis. I could not have imagined having better advisors for my Master's Degree study.

Besides my advisors, I would like to thank The Great members of **Engineering Department at Audi Bank** leaded by **Eng. Rafiq Abu-Sara** , for their encouragement, insightful comments, and hard questions.

Last but not the least; I would like to thank my family: my parents **Sayed Mohamed Ali** and **Rokaia Atta**, for giving birth to me at the first place and supporting me spiritually throughout my life

List of Contents

Contents	No.
List of Contents	
List of Figure	
List of Table	
Chapter (1): Introduction	
1.1 Research problem	
1.2 Main Goal	
1.3 Secondary Objectives	
1.4 Methodology	
Chapter (2): Banks Overview	
2.1 Historical background of banking	
2.2 Banking in Egypt	
2.2.1 Historical background about Banking in Egypt	
2.2.2 Classifications of Banks	
2.2.3 Structure of the financial system	
2.2.3.1 The regulatory agency (The central bank)	
2.3 Islamic Banking:	
2.3.1 Historical background of Islamic Banking	
2.3.2 Islamic banking main concept	
2.3.3 Case study: Faisal Islamic Bank of Egypt:	
Chapter (3): Design Criteria	
3.1 Branding and Corporate identity	
3.1.1 Branding definition	
3.1.2 Architectural techniques for Branding	
3.1.2.1 Indoor Features	
3.1.2.2 Outdoor Features	
3.1.2.3 Other Features	
3.2 Site Selection	
3.2.1 Criteria for choosing new branch's site	
3.2.2 Techniques for choosing location for new bank's branch	
3.3 Site analysis	
3.3.1 Topographic survey	
3.3.2 Site Checklist	
3.4 Creating zoning program	
3.4.1 General zoning program	
3.4.2 Small Branch zoning program	
3.4.3 Medium Branch zoning program	
3.4.4 Large Branch zoning program	
3.4.5 Other zoning programs	
3.5 Architectural Plan	
3.5.1 Small branch Architectural plan	
3.5.2 Medium branch Architectural plan	
3.5.3 Large branch Architectural plan	
3.5.4 Up-Scale branch Architectural plan	

Contents

No.

3.5.5 Drive-Up branch Architectural plan

3.5.5.1 Historical background

3.5.5.2 Modern drive up branch

3.6 Bank's areas

3.6.1 24-Hours area (Buffer zone)

3.6.1.1 Bank's Main Entrance

3.6.1.2 Automated Teller Machine (ATM)

3.6.1.3 Self-Banking (Personal teller machine)

3.6.2 Branch Front Office

3.6.2.1 Waiting Area

3.6.2.2 Teller area

3.6.2.3 Customer Service Office (CSO)

3.6.2.4 Branch manager

3.6.2.5 Assistant branch manager:

3.6.2.6 Meeting room

3.6.3 Branch Back Office

3.6.3.1 Vault Room

3.6.3.2 Cafeteria/kitchenette

3.6.3.3 Toilets

3.6.3.4 Generator Room

3.6.3.5 Archiving

3.6.3.6 Electric room

3.6.4 Elevation Design

3.6.4.1 Design criteria

3.6.4.2 Items of the Elevation

Chapter (4): Security and Administrative systems

4.1 Security Systems in banks

4.1.1 Physical Security

4.1.1.1 Exterior physical security systems

4.1.1.2 Interior physical security systems

4.1.2 Information Security

4.2 Administrative Systems in banks

Chapter (5): Case Studies

5.1 National Case Studies:

5.1.1 Audi Bank:

5.1.1.1 Reasons of Choosing Audi Bank as Case study

5.1.1.2 Historical Background

5.1.1.3 General Concepts

5.1.1.4 Planning layout

5.1.1.5 Elevations

5.1.1.6 Materials

5.1.1.7 Special Items

5.1.1.8 Electrical Systems

5.1.1.9 Mechanical

5.1.1.10 Furnishing

5.1.1.11 Services

Contents

No.

5.1.2 The National bank of Egypt (NBE)

5.1.2.1 Reasons of Choosing The National Bank of Egypt as Case study

5.1.2.2 Historical Background

5.1.2.3 General Concepts

5.1.2.4 Planning Layout

5.1.2.5 Elevations

5.1.2.6 Materials

5.1.2.7 Special Items

5.2 International Case Studies

5.2.1 Norlarco credit union fort collins , colorado EHS design

5.2.2 Mountain State Bank Gunning, Georgia

5.2.3 Home State Bank Willmar, Minnesota

Chapter (6): Bank's Design Process

6.1 Location and site analysis

6.1.1 Site considerations

6.1.2 Bubble Diagram and space relationship

6.1.3 Architectural Plan

6.1.3.1 24-Hours Zone

6.1.3.2 Branch Front Office

6.1.3.3 Branch Back Office

6.1.4 Materials

6.1.5 Main Concept of the Elevations

6.1.6 Systems Inside Banks:

6.1.6.1 Security Systems

6.1.6.1 Mechanical Systems

Chapter (7): Discussion and Conclusions

References

List of Figure

No.	Figure	Page
Chapter (1): Introduction		
Figure (1.1)	Example for Self-Banking retail branch	
Figure (1.2)	Diagram showing the methodology taken during the research process	
Chapter (2): Banks Overview		
Figure (2.1)	Grain harvesting and storage dealings at ancient Egyptian era were similar to the current banking operations nowadays	
Figure (2.2)	Example figure showing history of money and banking timeline	
Figure (2.3)	Palazzo Medici-Riccardi elevation drawing	
Figure (2.4)	Luxurious interior rooms for palazzo Medici-Riccardi	
Figure (2.5)	Strong looking for the palace from the outside	
Figure (2.6)	Bank of England model by George Sampson at 1694	
Figure (2.7)	Bank of England model by Sir John Soane	
Figure (2.8)	The Bank of England, the London office	
Figure (2.9)	Floor Plan of the Bank of England in 1833 by Sir John Soane	
Figure (2.10)	The Old National Bank of Egypt - Cairo in 1900's	
Figure (2.11)	The French bank Crédit Lyonnais picture in 1920 in Cairo	
Figure (2.12)	Picture of the first branch of Banque Misr in 1920	
Figure (2.13)	Picture showing Typical Interior for banks during the occupation period	
Figure (2.14)	The National bank of Egypt branch's elevation	
Figure (2.15)	for Banque Misr	
Figure (2.16)	Bank Piraeus Branch	
Figure (2.17)	HSBC branch in Hurgada	
Figure (2.18)	Diagram show the timeline of the history of the political system inside Egypt	
Figure (2.19)	Banking Supervision Sector Organizational Chart	
Figure (2.20)	Faisal Islamic Bank in Giza	
Figure (2.21)	Calligraphy of "Ribah" verses printed at the elevation of the building	
Figure (2.22)	Ground Floor for Faisal Bank	
Chapter (3): Design Criteria		
Figure (3.1)	Graph Example showing that the strongest branding system has much more business performance than less branding system over time	
Figure (3.2)	Branch Layout architectural plan	
Figure (3.3)	Example of the Teller oriented branch design	
Figure (3.4)	Example for kid's zone inside the bank branch	
Figure (3.5)	Waiting area zone integrated with a lot of branding stuff such as advertisement board and multi-media screen	
Figure (3.6)	Example for Brochure stand located at Audi Bank	
Figure (3.7)	Plan view for Brochure stand at Audi bank	
Figure (3.8)	Section view for brochure stand added inside Audi bank	
Figure (3.9)	Elevation view for brochure stand located at Audi bank	

No.	Figure	Page
Figure (3.10)	Example for the locations of the customer service inside HSBC bank with their red color scheme and circular shape	
Figure (3.11)	The circular partitions that contain the customer service desks can be used for advertising	
Figure (3.12)	Picture showing the location of CSO at Audi bank	
Figure (3.13)	Example for Pylon location	
Figure (3.14)	Picture showing Monument signs which had no impact on advertising as The Pylons	
Figure (3.15)	Example for Pylon dimensions for Audi bank	
Figure (3.16)	Example showing canopy could be part of the logo and part of bank's image	
Figure (3.17)	Example for canopies used for solar cells	
Figure (3.18)	HSBC signage	
Figure (3.19)	Metal door installed in Audi bank facade	
Figure (3.20)	Example for branding ways that shown inside a branch	
Figure (3.21)	Example for typical landscape plan example for Bank of America Hanover Park	
Figure (3.22)	Diagram showing the relationship between different rooms inside the branch	
Figure (3.23)	Bubble diagram showing the relationship between different areas inside small branch	
Figure (3.24)	Bubble diagram showing the relationship between different areas inside Medium branch	
Figure (3.25)	Bubble diagram showing the relationship between different areas inside large branch	
Figure (3.26)	Program diagram for Florida bank	
Figure (3.27)	Example prototype plan for Small branch	
Figure (3.28)	Example prototype plan for Medium branch	
Figure (3.29)	Example of medium branch architectural plan application	
Figure (3.30)	Example prototype plan for large branch	
Figure (3.31)	Example prototype plan for Up-scale branch	
Figure (3.32)	Example for old plan for Central National Bank in Kansas	
Figure (3.33)	Example for drive up tellers added within the architectural plan	
Figure (3.34)	Legend showing the Main three zones of the bank branch	
Figure (3.35)	Example for Bank's Entrance	
Figure (3.36)	Example for the branch entrance leading first to ATM window	
Figure (3.37)	Picture showing the Mantrap door style which is a need for any bank branch entrance	
Figure (3.38)	Entrance attached with ATM	
Figure (3.39)	Example of circular vestibule also linked with ATM machine	
Figure (3.40)	Example of Mantrap entrance knowing that there are no certain dimensions for it as it could be customized based on the available space	
Figure (3.41)	Picture showing Mantrap entrance attached with Ramp for handicapped	
Figure (3.42)	Man-trap design features	
Figure (3.43)	Man-trap front view	
Figure (3.44)	Man-trap design side view	
Figure (3.45)	Man-trap Top view	
Figure (3.46)	Diagram showing the Vestibule zone that need to be armored during the	

No.	Figure	Page
	night with shutter door	
Figure (3.47)	Example for shutter door	
Figure (3.48)	Example for shutter door	
Figure (3.49)	Picture showing shutter door from outside	
Figure (3.50)	Picture showing best locations for camera and it appeared that two cameras added to the main entrance of the bank	
Figure (3.51)	Picture showing the location of the cameras at the entrance of bank branch	
Figure (3.52)	View from Camera located at the entrance of the bank	
Figure (3.53)	Picture showing the location of the alarm besides the camera and security kiosk	
Figure (3.54)	Picture showing the location of metal detector added at the entrance of the bank	
Figure (3.55)	Picture showing the Greeter disk	
Figure (3.56)	Bankograph invented by Luther Simjian	
Figure (3.57)	Free standing data sheet dimensions	
Figure (3.58)	Figure showing ATM through wall	
Figure (3.59)	Figure showing the different between Drive-up ATMs	
Figure (3.60)	Figure showing the Human standards related to the ATM's Keys best position	
Figure (3.61)	showing the location of ATM machines inside the branch	
Figure (3.62)	showing different allocation for ATM's	
Figure (3.63)	Example showing ATM for the National Bank of Egypt	
Figure (3.64)	Example showing ATM outdoor cover	
Figure (3.65)	Different example for ATM covers	
Figure (3.66)	Location of Personal Teller machine inside the branch	
Figure (3.67)	Personal teller machine	
Figure (3.68)	A "Personal Teller Machine" capable of two-way video interactions	
Figure (3.69)	Legend showing the Main three zones of the bank branch	
Figure (3.70)	Picture showing modern waiting area design	
Figure (3.71)	Plan of branch of Aloha Pacific bank where different approach of waiting area is added as the designer put small internt cafe with bar for serving coffe	
Figure (3.72)	Example showing First floor of existing Audi bank branch before adding the private waiting area	
Figure (3.73)	Audi Branch after modifying the existing branch and adding the affluent waiting area	
Figure (3.74)	Picture showing the Affluent area (Private waiting area) added to the existing branch	
Figure (3.75)	Closer diagram showing the specifications of the new affluent area added	
Figure (3.76)	showing the location of teller showing mistake number one in locating the teller	
Figure (3.77)	Example for Mistake number two in locating the teller	
Figure (3.78)	Example showing the L-Shaped layout	
Figure (3.79)	Example showing the open plan concept	
Figure (3.80)	German standards about Teller desks	
Figure (3.81)	Swedish standards about teller desks	
Figure (3.82)	Accessible Teller desk height	
Figure (3.83)	Example showing teller counter for accessible	

No.	Figure	Page
Figure (3.84)	showing linear arrangement	
Figure (3.85)	same as (Fig.3.84) but side desk is added	
Figure (3.86)	Zeg-Zag arrangement	
Figure (3.87)	showing space needed for accessible in plan view	
Figure (3.88)	showing the main arrangement of teller stations with lighting arrangement	
Figure (3.89)	showing Teller counter at Audi bank from Customers side	
Figure (3.90)	showing Teller counter at Audi bank from banker side	
Figure (3.91)	Section detail for Audi Bank teller	
Figure (3.92)	Figure showing location of safe room in relation to Teller	
Figure (3.93)	In case of lack of space	
Figure (3.94)	showing location of safe room in relation to larger teller	
Figure (3.95)	Example of Foot-Rail System	
Figure (3.96)	Example of drive-up Teller counter standards	
Figure (3.97)	Customer Service booths at HSBC	
Figure (3.98)	Customer services desk at Audi Bank	
Figure (3.99)	Example of Desk Dimensions	
Figure (3.100)	Example for desks arrangement inside the branch	
Figure (3.101)	Example showing Branch manager Layout	
Figure (3.102)	Example of Furniture used inside branch manager office	
Figure (3.103)	Branch manager layout attached with small meeting zone	
Figure (3.104)	Branch manager attached with Toilet	
Figure (3.105)	Branch manager room with glass partitions	
Figure (3.106)	Example of branch manager room	
Figure (3.107)	large meeting room inside headquarter bank	
Figure (3.108)	Meeting room example	
Figure (3.109)	Location of the meeting room inside the branch	
Figure (3.110)	Location of Branch Back Office	
Figure (3.111)	Example showing the route to the vault room	
Figure (3.112)	Example showing the location of the vault at the back of the branch passing by several obstacles in its route	
Figure (3.113)	Example for layout design for the Vault	
Figure (3.114)	Main zones inside the Vault Area	
Figure (3.115)	Motion sensor device	
Figure (3.116)	Example showing the items inside the safe deposit room	
Figure (3.117)	Example showing the vault room layout	
Figure (3.118)	Roll front cabinet	
Figure (3.119)	Bank deposit boxes	
Figure (3.120)	Roll Front cabinet	
Figure (3.121)	Safe deposit boxes inside the vault	
Figure (3.122)	Data sheet example for safe model HS4 150	
Figure (3.123)	Data sheet example for carena safes	
Figure (3.124)	Rotary Wedge vault door model	
Figure (3.125)	Example for emergency vault door	
Figure (3.126)	Hollow blocks used in the construction process	
Figure (3.127)	Sheets used inside the vault	
Figure (3.128)	Doors during fixation process	

No.	Figure	Page
Figure (3.129)	showing Modular panel concrete vault	
Figure (3.130)	Example for Kitchenette layout with the equipments used inside it	
Figure (3.131)	Example layout for toilet	
Figure (3.132)	Generator set room	
Figure (3.133)	Example of fire proofing cabinets used inside the branch	
Figure (3.134)	showing the Electrical room layout with equipments used inside	
Figure (3.135)	Picture showing devices used inside the electrical room	
Figure (3.136)	Example of the traditional Elevation system	
Figure (3.137)	showing the same financial institutions but by applying modern style on their branches elevations	
Figure (3.138)	Example of items of the elevation	
Figure (3.139)	Film added to glass's elevation to make it stronger	
Figure (3.140)	Camera monitoring ATM device	
Figure (3.141)	Advertising tools could be added through the window	
Figure (3.142)	showing CIB bank which is famous by its materials and color scheme used at the elevation	
Chapter (4): Security and Administrative systems		
Figure (4.1)	Physical security systems act as deterrent for intruders	
Figure (4.2)	Perimeter Physical Security	
Figure (4.3)	Zig-Zag pattern of chain link fence	
Figure (4.4)	showing the parts of Chain link Fence	
Figure (4.5)	Fencing used in large headquarters for bank's institutions	
Figure (4.6)	Fixed guard posts in front of gates	
Figure (4.7)	Protective lighting at the back of the bank	
Figure (4.8)	Bank branch during night	
Figure (4.9)	Example showing the double door emergency door system	
Figure (4.10)	Windows unit types	
Figure (4.11)	Typical windows unit component	
Figure (4.12)	cameras facing ATM for safety	
Figure (4.13)	Diagram showing the location of cameras system outside the bank	
Figure (4.14)	Picture showing the location of the camera at the bank's entrance	
Figure (4.15)	Picture showing the location of the camera at the critical corners at the bank	
Figure (4.16)	Typical CCTV shape	
Figure (4.17)	Camera protection	
Figure (4.18)	Example of camera locations at small bank	
Figure (4.19)	List of the alarm systems and access control systems used inside the branch and applied next page on a plan	
Figure (4.20)	Location of the alarm systems and access control that referred at figure 4.19	
Figure (4.21)	Access control doors for restricted areas	
Figure (4.22)	Picture showing glass break sensor location	
Figure (4.23)	Control room at the branch	
Figure (4.24)	Hierarchy of bank's Employees	
Chapter (5): Case Studies		
Figure (5.1)	showing Audi Bank's Head Office at Lebanon	

No.	Figure	Page
Figure (5.2)	showing Audi Bank's Head Office at Egypt existing on Cairo-Alexandria Road leading more than 34 branches all over Egypt (Founded in Egypt in 2006)	
Figure (5.3)	showing Bank design concept and identity that is shown through materials and color scheme of the bank	
Figure (5.4)	showing the Facade Items and concept of bank Audi also showing the Human scale related to the Facade Scale	
Figure (5.5)	showing the pylon location as it perpendicular on the branch to catch pedestrian's eyes	
Figure (5.6)	showing the main entrance of Audi branch at Abbas Al-Akaad	
Figure (5.7)	Showing the Canopy found on the ATM for shading at Lebanon-Square branch	
Figure (5.8)	showing one floor facade	
Figure (5.9)	showing two- floor facade	
Figure (5.10)	Showing two-floors with multiple windows	
Figure (5.11)	Showing 2 floors & pylon	
Figure (5.12)	Showing 2 floors with multiple windows	
Figure (5.13)	Showing Multiple & windows	
Figure (5.14)	Diagram of Extraction of lines and modules on the external elevation	
Figure (5.15)	showing Facade elements and concepts for different cases vary between small, medium and large branches	
Figure (5.16)	showing The Signage design of Audi Bank	
Figure (5.17)	Showing Different locations for Bank Audi Signage	
Figure (5.18)	showing the extraction of lines and modules in the internal facade	
Figure (5.19)	showing how flooring tiles can be used in order to guide clients towards the Teller desk	
Figure (5.20)	showing longitudinal section showing the relation between the internal and the external facade	
Figure (5.21)	showing longitudinal section showing the relation between the internal and the external facade	
Figure (5.22)	showing different Ceiling types used inside Audi bank branch based on the function of each space	
Figure (5.23)	showing the false ceiling during construction phase	
Figure (5.24)	Diagram Showing ATM dimensions and fixations at Audi Bank	
Figure (5.25)	showing the application of ATM on Glass knowing that this glass must be secured glass covered with special films which made the glass highly resistant and unbreakable	
Figure (5.26)	showing The ATM from inside the room that is placed inside it, usually this room is closed and it is opened only for feeding the ATM with money or for maintenance	
Figure (5.27)	showing the application of ATM on a sherry wood cladding wall	
Figure (5.28)	showing the application of ATM on Stone	
Figure (5.29)	showing the application of the ATM cover with the Bank's facade and besides being eye catcher and shelter for the client it acts also as buffer zone between the street and the ATM machine that is required for security issues	
Figure (5.30)	showing the elements of the vault	
Figure (5.31)	showing tang bar reinforcement during construction phases	
Figure (5.32)	Main vault Door at the left and at the right a picture showing Grill-Gate	

No.	Figure	Page
Figure (5.33)	showing the emergency door applied at the vault room also the dimensions of it and direction of opening the door	
Figure (5.34)	showing fire proof area layout	
Figure (5.35)	showing shelves used in the fire proofing area	
Figure (5.36)	showing the pylon position related to the street and the branch	
Figure (5.37)	showing the relation of the safe room related to the teller based on the size of the teller counter	
Figure (5.38)	showing the relation of the teller with the canopy hanged from ceiling	
Figure (5.39)	showing detailed drawing for tellers counter installed at Audi bank branch	
Figure (5.40)	showing the stairs during construction phase	
Figure (5.41)	showing the stairs at Audi bank branch	
Figure (5.42)	showing different location for canopy related to the elevations	
Figure (5.43)	showing Internal Canopy details and shaping	
Figure (5.44)	showing glass door located inside the branch mainly its used for the branch manager room	
Figure (5.45)	showing the floor box used inside Audi branches	
Figure (5.46)	Lighting fixture diagram	
Figure (5.47)	Legend for workstation & Power system	
Figure (5.48)	showing the Distribution of Low Current System Along a random branch at Audi Bank	
Figure (5.49)	showing the Distribution of Low Current System Along a random branch at Audi Bank	
Figure (5.50)	Requirements and elements diagram	
Figure (5.51)	layout diagram of equipment	
Figure (5.52)	showing example of data sheet related to choosing Safes	
Figure (5.53)	show safe location in the relation to the branch size	
Figure (5.54)	showing Data sheet for different type of safes based on the location that is used inside Audi Branch	
Figure (5.55)	Fire Proof Cabinet	
Figure (5.56)	showing random kitchenette inside Audi branch	
Figure (5.57)	showing toilets and Audi branch	
Figure (5.58)	showing electric room layout	
Figure (5.59)	Showing the panels inside the electric room	
Figure (5.60)	showing the Archive Room	
Figure (5.61)	showing the electronic archiving	
Figure (5.62)	showing the oldest branch for national bank of Egypt located at Cairo	
Figure (5.63)	showing two towers related to the National Bank of Egypt's head offices facing the Nile River	
Figure (5.64)	showing the Logo of the National Bank of Egypt	
Figure (5.65)	Showing Ground Floor Plan for KASR AL-Nile Branch for NBE bank	
Figure (5.66)	Showing First Floor Plan for KASR AL-Nile Branch for NBE bank	
Figure (5.67)	showing Ground Floor Plan for East Cairo Branch	
Figure (5.68)	showing First Floor Plan for East Cairo Branch	
Figure (5.69)	showing Basement Floor Plan for East Cairo Branch	
Figure (5.70)	showing Typical Floor Plan for East Cairo Branch	
Figure (5.71)	Showing Ground Floor Plan for the branch	
Figure (5.72)	Showing First Floor Plan for the branch	

No.	Figure	Page
Figure (5.73)	showing Ground Floor Plan	
Figure (5.74)	showing Basement Floor Plan	
Figure (5.75)	showing First Floor Plan	
Figure (5.76)	showing site analysis for the bank branch	
Figure (5.77)	Showing Basement Floor level for the branch	
Figure (5.78)	showing Ground Floor plan for the branch	
Figure (5.79)	showing First Floor Plan for the branch	
Figure (5.80)	showing the Second & Third Floor plan which acting as rest zone for the managers and audit leading to these floors through external stairs as shown in the figures	
Figure (5.81)	Explaining the concept of the National Bank of Egypt's elevation	
Figure (5.82)	showing the significant influence of the logo on the elevation of SADAT branch	
Figure (5.83)	showing the elevation elements of KASR AL-Nile & ZAGAZEG Branches	
Figure (5.84)	showing the Front and side elevation of The National Bank of Egypt	
Figure (5.85)	showing the Logo of the National Bank of Egypt	
Figure (5.86)	showing the Interior facade concept at random National bank of Egypt	
Figure (5.87)	showing the Flooring tiles used at Waiting Area	
Figure (5.88)	showing wooden wall cladding could be used at customer service area	
Figure (5.89)	showing valuable materials used at wall finishes at waiting area zone also showing the Logo hanged from the ceiling	
Figure (5.90)	Showing the wall cladding used at Employee zone (Staff Zone) figures	
Figure (5.91)	showing Marble used at wall cladding at Teller counter zone	
Figure (5.92)	showing how the designer tries to emphasis the teller zone through ceiling design	
Figure (5.93)	showing Ceiling tiles used at waiting area	
Figure (5.94)	showing the window ATM attached with the branch	
Figure (5.95)	showing the new Design for the ATM attached with the Elevation using ATM Cover	
Figure (5.96)	showing different Designs of free standing ATM	
Figure (5.97)	showing the location of vaults at small branches and how's it connected with the tellers also for possible second floor for branch separate stairs is located beside the vault for safely transferee the money from first floor vault	
Figure (5.98)	showing the location of the vault at second floor of the branch connected with separate stair to the Ground floor	
Figure (5.99)	showing Type 2 of vaults where you can find two types of vaults one for main uses and the other one for client's daily uses	
Figure (5.100)	showing the relation of the safe room towards to the teller Counter	
Figure (5.101)	showing the module of the teller	
Figure (5.102)	showing different forms of the teller counter at National bank of Egypt	
Figure (5.103)	Showing plan of the branch	
Figure (5.104)	Showing Interior design of the branch	
Figure (5.105)	Floor plan, Mountain State Bank Cumming, Georgia. The traditional teller line is immediately visible from the main entrance and surrounding offices as well. The main safe deposit vault is adjacent to a cash vault that is accessible by the drive-up tellers. The manager's office has a small conference table for Jess formal discussions, and the plan features a	

No.	Figure	Page
	separate record vault for file storage. The vestibule entrance that helps keep comfort higher and energy costs lower is a good idea even in the southern part of the United States. Foreman Seeley Fountain Architects	
Figure (5.106)	Mountatin State Bank exterior view	
Figure (5.107)	A Site plan, Name State Bank, Willmar, Minnesota. The corner location along the highway and thoroughfare provides an opportunity for showcasing the bank to a large group of potential customers. The drive-up exit to the side street behind helps reduce the traffic within the site. KKE Architects	
Figure (5.108)	Second-floor plan, Home State Bank, Willmar, - Minnesota. The president's office and boardroom are to the left of the break room and assistant areas. A folding wall opens this space for special - events. Additional offices, a server room, a storage room, and records are adjacent to a large processing room and work area to round out the second floor. KKE Architects	
Figure (5.109)	First-floor plan, Home State - Bank, Willmar, Minnesota. The unusual plan places interior spaces at different juxtaposed angles than the usual rectangular room design. The _ open lobby extends up through the second floor to the roof above. KKE Architects	
Chapter (6): Bank's Guidelines		
Figure (6.1)	Bank branch layout	
Figure (6.2)	Diagram showing the main zones needed inside the bank's branch	
Figure (6.3)	Typical Bubble diagram showing the functions needed for a branch and the relation between each space	
Figure (6.4)	Typical branch plan and analysis	
Figure (6.5)	Typical layout	
Figure (6.6)	showing the typical design for 24-hours zone and the bank branch	
Figure (6.7)	Different designs for 24-hour zone	
Figure (6.8)	showing sectional 3D for shutter doors	
Figure (6.9)	24 hour zone different design	
Figure (6.10)	showing vestibule standards	
Figure (6.11)	ADA guidelines for vestibule designs	
Figure (6.12)	Case of Revolving door existence	
Figure (6.13)	Maneuvering Clearances at Manual Swinging Doors and Gates	
Figure (6.14)	Portable Ramp could be used at inaccessible building entrance	
Figure (6.15)	ADA regulations for ramps	
Figure (6.16)	Man- trap layout design	
Figure (6.17)	Single vestibule for both entrance and exit	
Figure (6.18)	Double vestibule ways one for entrance and the other for exit	
Figure (6.19)	The simplest design of a mantrap contains two doors: one connects the vestibule to the secure area, and one connects to the non-secure area	
Figure (6.20)	Free standing ATM design specifications.	
Figure (6.21)	Through wall ATM design specifications	
Figure (6.22)	Free standing ATM locations	
Figure (6.23)	Routes towards the ATM should be easily accessed	

No.	Figure	Page
Figure (6.24)	Through wall ATM locations	
Figure (6.25)	showing main zones at the bank's branch	
Figure (6.26)	Diagram showing zones inside the branch front office.	
Figure (6.27)	Standards for reception desk at the waiting zone	
Figure (6.28)	different arrangement of waiting area	
Figure (6.29)	German standards about Teller desks	
Figure (6.30)	Swedish standards about Teller desks	
Figure (6.31)	ADA regulations for teller counter design	
Figure (6.32)	Teller Equipment	
Figure (6.33)	Different arrangement for teller inside the bank	
Figure (6.34)	Standards for Customer service zone	
Figure (6.35)	Branch manager desk standards	
Figure (6.36)	Branch manager rooms different designs and arrangement	
Figure (6.37)	Meeting room standards	
Figure (6.38)	meeting room arrangement	
Figure (6.39)	showing main zones at the bank's branch	
Figure (6.40)	showing different zones inside branch back of office	
Figure (6.41)	Vault room reinforcement standards	
Figure (6.42)	Vault design	
Figure (6.43)	Main Vault Room Standards	
Figure (6.44)	Emergency door standards	
Figure (6.45)	Cafeteria standards	
Figure (6.46)	Handicapped Toilet dimensions	
Figure (6.47)	Toilets standards	
Figure (6.48)	Fire rated drawer	
Figure (6.49)	Toilets standards	
Figure (6.50)	Typical elevation of the bank branch	
Figure (6.51)	cross section for laminated glass	
Figure (6.52)	Different design for classic branch design	
Figure (6.53)	Different designs for modern bank's elevation	
Figure (6.54)	intrusions systems inside the bank	
Figure (6.55)	intrusions systems inside the bank	
Figure (6.56)	layout showing the HVAC positions inside the bank	

List of Table

No.	Table	Page
Chapter (2): Banks Overview		
Table (2.1)	List of Banks Registered with the Central Bank of Egypt	
Chapter (3): Design Criteria		
Table (3.1)	UL Classifications for burglary resistant	
Table (3.2)	Showing Vault Areas in related to branches sizes	
Table (3.3)	Example for different dimensions for both Main vault and emergency vault doors	
Table (3.4)	Example for dimensions used inside the branch for fire proofing cabinets	
Chapter (5): Case Studies		
Table (5.1)	showing the material schedule Location based the function for each zone at the branch	
Table (5.2)	showing the material schedule Location based the function for each zone at the branch	
Table (5.3)	showing the material schedule Location based the function for each zone at the branch	
Table (5.4)	Showing the Type of Chairs used inside the branch based on the Function of each space	
Chapter (6): Bank's Guidelines		
Table (6.1)	checklist needed during the sit planning and selection for new branch	
Table (6.2)	showing the relation between the whole branch area and 24-hours zone area	
Table (6.3)	showing the relation between the whole branch area and 24-hours zone area	
Table (6.4)	showing the square areas for different zones inside the bank's branch front of office	
Table (6.5)	showing the estimated areas for different zone inside branch back of office	
Table (6.6)	showing specs for fire rated drawer	
Table (6.7)	Material Example data sheet	
Table (6.8)	specs for laminated glass	