

بسم الله الرحمن الرحيم



-C-02-50-2-





شبكة المعلومات الجامعية التوثيق الالكتروني والميكرونيلم





جامعة عين شمس

التوثيق الإلكتروني والميكروفيلم

قسم

نقسم بالله العظيم أن المادة التي تم توثيقها وتسجيلها علي هذه الأقراص المدمجة قد أعدت دون أية تغيرات



يجب أن

تحفظ هذه الأقراص المدمجة يعيدا عن الغيار







بالرسالة صفحات لم ترد بالأصل









fin shane



Effect of Tin and Aluminum Deposition on porcelain / cement shear bond strength.

Thesis

Submitted to the Facutly of Oral and Dental Medicine .

Cairo University .

In Partial Fulfilment For
The Requirements of Doctor's Degree In
Fixed Prosthodontics

Ву

Jylan Fouad EL- Guindy

B. D. S., M.Sc. (Cairo University)

Department of Fixed Prosthodontics

Facutly of Oral & Dental Medicine

Cairo University

2001

و. مرد عا عداكم

, ch

C'sel

Supervisors

Dr. Badawi Abou EL- Mahasen Badawi

Professor of Fixed prothodontics
Facutly of Oral & Dental medicine
Cairo University

Dr. Azza Mohamed Abd EL- Zaher Hashem

Assistant professor of Dental Materials
Facutly of Oral & Dental medicine
Cairo University

Dr. Mohamed Atta Abd EL- Halim

Lecturer of applied physics

National Institute of Laser Enhanced Science

Cairo University

OF DICATION

This work is gratefully dedicated

To the memory of my father who I always wished he could share this occasion with me.

To my everlasting support my mother for her constant encouragement and motivation.

To my partner in life my husband for his patience and understanding.

And to the smile in my life my children for missing me sometimes during the course of my study.

Acknowledgement

First of all , thanks to **ALLAH** who enabled me to overcome all problems which faced me throughout the work .

I would like to express my sincere gratitude to *Dr. Badawi Abou EL-Mahasen Badawi*, Professor of the Fixed Prosthodontics, Faculty of Oral and Dental Medicine, Cairo University, for whom I owe a special appreciation and thanks for his continuous encouragement, constructive effort, valuable suggestions and for the time he freely gave for guiding me throughout the study.

My sincere gratitude and deep appreciation are extended to *Dr.*Azza Mohamed Abd EL- Zaher Hashem , Assistant Professor of Dental Materials, Faculty of Oral and Dental Medicine , Cairo University , for her kind help , experience , meticulous teaching , superb advices and

useful remarks she willingly gave me during my work.

Special apperciation is dedicated to *Dr. Mohamed Atta Abd EL-Halim* Letcurer of applied physics, National Institute of Laser Enhanced Science, Cairo University for his kind supervision during this study.

Special thanks and gratitude are expressed to *Dr. Ahmed Zaki Maher*, Professor of fixed prosthodontics and Vice Dean of Faculty of Oral and Dental Medicine and To *Dr. Hany Halim Nasr*, Professor and Chairman of Fixed Prosthodontics Department, Faculty of Oral and Dental Medicine, Cairo University, for their active support and sincere guidance.

I feel thankful to Engineer **Ahmed Fouad EL- Guindy** for his generous assistance in placing the facilities of his office at my disposal.

I am also grateful to Miss **Doaa Sayed** and to **Dr. Mohamed khallil** who gave me a lot of their time, unlimited effort and cooperation to accomplish this work.

I feel grateful to *Dr. Rasha Nabil* for her kind help she always offered during the course of this study .

Finally , I am indebted to all the members of Fixed Prosthodontics Department , Faculty of Oral and Dental Medicine , Cairo University, for their great help, cooperation and understanding.

LIST OF CONTENTS

	<u>Page</u>
Introduction	1 -
Review of Literature	3 -
Aim of The study	- 46 -
Materials and Methods	47-
Results	85 -
Discussion	134 -
Summary	149 -
Conclusion	153 -
Recommendations	155-
References	156 -
Arabic Summary	175 -

LIST OF FIGURES

LIST Of Figures

Figure No.	TITLE	Page No	0
Figure (1): N	Munsell scales of Hue, Value and Chroma in color spac	e. 3	35
Figure (2) : L	_*a*b* color space.	3	39
Figure (3) : (C.I.E. L*a*b* color arrangement.	4	1
. , ,	The copper mold with a hole of 6mm internal diameter and 3 mm thickness.	5	51
Figure (5) : I	Boxing of the copper mold.	5	51
Figure (6) : I	Boxing of the duplicate mold.	;	51
	The refractory mold containing the Ducera ceramic sample.	Ę	51
Figure (8):	The copper holder used with the microblasting machine	ə ;	53
• , ,	he copper holder carrying the ceramic sample and ttached to the microblasting machine	,	53
Figure (10):	The split copper mold in the form of two plates assembled at both ends by 2 screws.		55
Figure (11)	The split copper mold containing the In-ceram slip samples.		55
Figure (12)	The screws were untightened and the mold was disassembled to introduce the In-ceram slip.		55
Figure (13)	: The Coating System.		59
Figure (14)	: A schematic diagram for the coating unit.		59
Figure (15)	: A- The uncoated ceramic samples. B- The Coated Ceramic samples.		62
Figure (16)	: The Scanning Electron Microscope and Energy Dispersive X-ray Analysis Unit (S.E.M. & EDAX).		62
Figure (17)	 A- The Teflon mold used for the construction of self cured acrylic resin block B-The ceramic sample embedded centrally in the block 	ck	65

Figure No.	TITLE		Page No	
Figure (18) :	The cementation device A-The solid stainless steel cylinder of load 2 B-The hollow cylinder to support the load	2 kilogram	s 65	
Figure (19) :	A-The solid stainless steel cylinder of load 2 B-The hollow cylinder to support the load C. The copper base inside which the trip as			
	C-The copper base inside which the twin ce	ramic san	npies are pia	icea
Figure (20) :	The universal testing machine used for sheatesting.	ar bond	70	
Figure (21) :	The Special designed attachment used with universal testing machine.	the	70	
Figure (22) :	The Copper mold with 1.6 mm thickness and Diameter.	d 15mm	74	
Figure (23) :	The thickness adjustment copper mold with	1.5 mm	74	
	thickness and 15mm internal diameter.			
Figure (24) :	Boxing of the copper mold.		74	
Figure (25) :	Boxing of the duplicate mold.		74	
Figure (26) :	The refractory mold containing the Ducera s dentin shade A3.	ample	74	
Figure (27)	The thickness adjustment copper mold contact ceramic sample.	aining the	74	
Figure (28)	The Split copper mold with a hole of 1mm th 15 mm internal diameter.	ickness a	nd 77	
Figure (29) :	The Copper mold containing the In-ceram s	slip.	77	
Figure (30) :	The split copper mold was disassembled To the In-ceram slip.	introduce	e 77	
Figure (31) :	The split Copper mold of 1.6mm thickness a internal diameter used for firing 0.6mm Vitad dentin shade A3 on the 1mm In-ceram core	dur Alpha	n 77	
Figure (32)	The thickness adjustment copper mold contact ceramic sample.	aining the	77	•
Figure (33):	The copper holder used with the microblastin	ng machi	ne. 79)
Figure (34) :	The copper holder carrying the ceramic san attached to the microblasting machine.	nple and	79)

LIST OF TABLES