

بسم الله الرحمن الرحيم

صدق الله العظيم

(سورة طه - آية ٢٤-٢٨)

EFFECT OF DIFFERENT SURFACE TREATMENTS ON SHEAR BOND STRENGTH OF HIGH STRENGTH CERAMIC WITH RESIN CEMENT

A Thesis Submitted to the Faculty of Oral and Dental
Medicine, Cairo University, for Partial Fulfillment of the
Requirements for Master Degree in Dental Science
(Fixed Prosthodontics)

YamenShareef Al-Qassem
B.D.S (October 6 University)
2004

Faculty of Oral and Dental Medicine
Cairo University
2011

Supervisors

Supervisors

PROF.DR. AHMAD HASANEIN KHALEL

*Professor of Fixed Prosthodontics,
Faculty of Oral and Dental Medicine
Cairo University*

DR. Mona Attia Mohammed Mokbel

*Assistant Professor of Fixed Prosthodontics,
Faculty of Oral and Dental Medicine
Cairo University*

Contents

	<i>Page</i>
<i>Acknowledgment</i>	i
<i>Dedication</i>	ii
<i>List of Tables</i>	iii
<i>List of Figures</i>	iv
<i>Introduction</i>	1
<i>Review of literature</i>	4
<i>Aim of the study</i>	32
<i>Materials and Methods</i>	33
<i>Results</i>	79
<i>Discussion</i>	101
<i>Summary and Conclusion</i>	111
<i>References</i>	114
<i>Arabic summary</i>	

Acknowledgement

ACKNOWLEDGEMENT

First and forever , I would like to thank god for his generosity prevails my life , his guidance and help to finish this work.

I have the great honor to thank and express my deep feeling to *Dr. Ahmed Hasanein Khalil*, professor of fixed prosthodontics ,faculty of oral and dental medicine, cairo university , for his guidance, valuable facilities, advices, and unlimited time offered to me during this work. That without his help wouldn't have come true.

Also I have the pleasure to express my deep respect and gratitude to *Dr. Mona Attia Mohammed Mokbel*, Assistant of professor of fixed prosthodontics ,faculty of oral and dental medicine, cairo university, for her support, continous help and enthusiastic stimulation through this work.

Finally, I would like to thank staff members of Fixed Prosthodontics Department in Cairo University and all my friends and every one participated in this work for their help and support.

Delication

This work Dedicated To

**My lovely family for the endless love,
Support and encouragement**

LIST OF TABLES

Table Number	Title	Page Number
(1 – a)	Materials used in this study.	33
(1 – b)	Materials used in this study.	34
(2)	Samples Grouping.	36
(3)	Results of regression analysis for the effect of material, surface treatment and their interactions on mean shear bond strength	80
(4)	The means, standard deviation (SD) values and results of comparison between materials regardless of surface treatment	81
(5)	The means, standard deviation (SD) values and results of comparison between materials with each surface treatment	82
(6)	The means, standard deviation (SD) values and results of comparison between surface treatments regardless of material	84
(7)	The means, standard deviation (SD) values and results of comparison between surface treatments at each aging period	87
(8)	The means, standard deviation (SD) values and results of comparison between the different interactions	88
(9)	mean (Ra) values in microns for different surface treatments of In-Ceram Zirconia, YTZP-Zirconia and IPS-EmpressII	90

LIST OF FIGURES

Figure number	Title	Page number
(1)	<i>Assembled and disassembled split copper mold</i>	37
(2)	<i>T-Rigid composite resin</i>	38
(3)	<i>Special light curing unit</i>	38
(4)	<i>Copper mold and pattern resin</i>	39
(5)	<i>Zirconzahn milling unit</i>	39
(6)	<i>Zirconzahn block</i>	40
(7)	<i>Milling of zirconia block</i>	40
(8)	<i>Zircon lamp</i>	41
(9)	<i>Sinter furnace</i>	42
(10)	<i>A:In-Ceram additive.</i> <i>B:In-Ceramliquid.</i> <i>C:In-Ceram Zirconia powder</i>	44

(11)	<i>Steps for slip mixing</i> <i>a) Mixing of In-Ceram liquid and additive.</i> <i>b) Progressive addition of In-Ceram Zirconia powder into the liquid.</i> <i>c) Interruption of mixing and putting the glass beaker in the VITASONIC II.</i> <i>d) Holding the mixture under vacuum.</i>	45
(12)	<i>Slip left to dry in the copper mold</i>	46
(13)	<i>Disassembling the mold for retrieving slip</i>	47
(14)	<i>The VITA INCERAMAT</i>	47
(15)	<i>VITA In-Cearm testing liquid</i>	49
(16)	<i>VITA In-Ceram glass powder</i>	51
(17)	<i>Disc shaped core after glass infiltration firing</i>	51
(18)	<i>Disassembled split copper mold with blue inlay wax discs</i>	52
(19)	<i>The investment assembly</i> <i>A-The investment rubber ring.</i> <i>B-The plastic ring base.</i> <i>C -The plastic leveling ring.</i>	54
(20)	<i>Disc shaped wax patterns sprued and attached to the plastic ring base.</i>	54

(21)	<i>Vacuum mixer</i>	55
(22)	<i>Preheating furnace</i>	56
(23)	<i>AlO_x plunger (a) and Investment ring assembly (b) [containing sprued wax samples within it] placed inside preheating furnace .</i>	57
(24)	<i>The press furnace</i>	57
(25)	<i>IPS Empress 2 small ingot</i>	59
(26)	<i>IPS Empress 2 ingot inside the heated investment</i>	59
(27)	<i>Placing the heated AlO_x plunger on the IPS Empress 2 ingot.</i>	60
(28)	<i>The pressing furnace with the assembly inside</i>	60
(29)	<p><i>Investment assembly [cast samples + AlO_x plunger] after pressing in press furnace from top to base:</i></p> <p><i>A- End of the AlO_x plunger extruded outside the investment ring.</i></p> <p><i>B- Investment ring.</i></p> <p><i>C- Pressing furnace</i></p>	61
(30)	<i>Marking the length of the ALO_x plunger</i>	63
(31)	<i>Cutting the investment ring at the predetermined point</i>	63

(32)	<i>light-curing, radiopaque composite Te-Econom Plus</i>	65
(33)	<i>Disassembled split copper mold with light cured composite resin discs.</i>	65
(34)	<i>Airborn-particles abrasion device</i>	67
(35)	<i>Ceramic discs were mounted in a metal holder ready for airborne blasting</i>	68
(36)	<i>Hydrofluoric acid etching gel</i>	68
(37)	<i>Profilometer</i>	69
(38)	<i>Disassembled cementing device.</i>	71
(39)	<i>Monobond-S silane coupling agent</i>	71
(40)	<i>Dual-curing luting composite system Variolink II</i>	72
(41)	<i>Assembled cementing device with cemented ceramic and composite discs</i>	73
(42)	<i>Cemented ceramic and composite discs</i>	73
(43)	<i>LLOYD Universal Testing Machine</i>	75
(44,A)	<i>Disassembled holding device</i>	76
(44,B)	<i>Assembled holding device</i>	76
(45)	<i>The holding device attached to the LLOYD universal testing machine</i>	77

(46)	<i>Scanning Electron Microscope</i>	78
(47)	<i>Histogram representing mean shear bond strength with different materials</i>	81
(48)	<i>Histogram representing mean shear bond strength of the three materials with each surface treatment</i>	83
(49)	<i>Histogram representing mean shear bond strength with different types of surface treatment</i>	85
(50)	<i>Histogram representing mean shear bond strength with different surface treatments at each aging period</i>	87
(51)	<i>Histogram representing mean shear bond strength with different variables interactions</i>	89
(52)	<i>Scanning electron photomicrograph of In-Ceram Zirconia after sandblasting with 110µm AL₂O₃</i>	93
(53)	<i>Scanning electron photomicrograph of In-Ceram Zirconia after sandblasting with 50µm AL₂O₃</i>	93
(54)	<i>Scanning electron photomicrograph of In-Ceram Zirconia after sandblasting with 110µm AL₂O₃ + Etching</i>	94
(55)	<i>(Figure-55):Scanning electron photomicrograph of In-Ceram Zirco after sandblasting with 50µm AL₂O₃ + Etching</i>	94
(56)	<i>Scanning electron photomicrograph of YTZP- Zirconia after sandblasting with 110µm AL₂O₃</i>	96
(57)	<i>Scanning electron photomicrograph of YTZP- Zirconia after sandblasting with 50µm AL₂O₃</i>	96
(58)	<i>Scanning electron photomicrograph of YTZP- Zirconia after sandblasting with 110µm AL₂O₃ +Etching</i>	97

(59)	<i>Scanning electron photomicrograph of YTZP- Zirconia after sandblasting with 50μm AL₂O₃ +Etching</i>	97
(60)	<i>Scanning electron photomicrograph of IPS-Empress 2 after sandblasting with 110μm AL₂O₃</i>	99
(61)	<i>Scanning electron photomicrograph of IPS-Empress 2 after sandblasting with 50μm AL₂O₃</i>	99
(62)	<i>Scanning electron photomicrograph of IPS-Empress 2 after sandblasting with 110μm AL₂O₃ + Etching</i>	100
(63)	<i>Scanning electron photomicrograph of IPS-Empress 2 after sandblasting with 50μm AL₂O₃ + Etching</i>	100