



Ain Shams University
Women's College for
(Arts, Science and Education)

Synthesis and Study of Crystal, Magnetic and Electric Properties of (Copper –Zinc –Gallium) Ferrites

A Thesis Submitted to

*Women's College for Arts, Science and Education
Ain Shams University
For the Ph. D. Degree in Science "Solid State Physics"*

By

Salwa Mohamed Ismail

*Assistant Lecturer of Solid State Physics,
Reactor Physics Department
Atomic Energy Authority*

Under Supervision

Prof. Dr. H.A. Zayed

*Physics Department, University College of Women
(Arts, Science and Education)- Ain Shams University.*

Prof. Dr. M.K. Fayek

*Department of Reactor Physics,
Atomic Energy Authority.*

Prof. Dr. S.S. Ata –Allah

*Department of Reactor Physics,
Atomic Energy Authority.*

(٢٠٠٨)



*Ain Shams University
Women's College for
(Arts, Science and Education)*

***Synthesis and Study of Crystal, Magnetic and
Electric Properties of
(Copper– Zinc- Gallium) Ferrites***

Submitted By

Salwa Mohamed Ismail

Supervisor Committee

Signature

١- Prof. Dr. H. A. Zayed.

Physics Department,
University College of Women.
(Arts, Science and Education)
Ain Shams University.

٢- Prof. Dr. M. K. Fayek

Reactor Physics Department,
Nuclear Research Center,
Atomic Energy Authority.

٣- Prof. Dr. S. S. Ata –Allah

Reactor Physics Department,
Nuclear Research Center,
Atomic Energy Authority.

Date of Research: / / ٢٠٠٨

Approval Stamp:

Date of Approval: / / ٢٠٠٨

Approval of Faculty Council:

Approval of University Council:



*Ain Shams University
Women's College for
(Arts, Science and Education)*

Name of Student: *Salwa Mohamed Ismail*
*Assistant Lecturer of Solid State Physics,
Reactor Physics Department
Atomic Energy Authority*

Title of Thesis: *Synthesis and Study of Crystal, Magnetic
and Electric Properties of
(Copper –Zinc –Gallium) Ferrites*

Scientific Degree: Doctor of Philosophy in Science
“Solid State Physics”

Department: Physics

Name of Faculty: University College of Women
(Arts, Science and Education)

University: Ain Shams University.

B.S.C. Graduation Date: ١٩٧٨

M.S.C. Graduation Date: ١٩٩٩

Ph. D. Graduation Date: ٢٠٠٨

ACKNOWLEDGEMENTS

I'm greatly indebted to ***Prof. Dr. H. A. Zayed***, the Ex /Dean of University College of Women, (Arts, Science and Education)-Ain Shams University for encouragement and supervision of this work.

I would like to express my deep gratitude to ***Prof. Dr. M. K. Fayek***, the former vice chairman of the Atomic Energy Authority of Egypt for his keen interest, valuable suggestions encouragement, supervision and critical remarks he made during this work. I'm greatly honored to get opportunity to work with him.

I am grateful to ***Prof. Dr. S. S. Ata-Allah***, Head of Nuclear Solid State Group, Reactor Physics Department, Atomic Energy Authority for continuous supervision, valuable suggestions, encouragement and fruitful advice through this work.

I am grateful to Dr. M. Kaiser for her continuous help and encouragement during this work.

I wish to express my deeply thanks to Prof. Dr. N. Zahran, Head of Central Laboratory for Elemental and Isotopic Analysis, for her encouragement and helping in some of the measurements.

This work has been done at laboratory of “Nuclear Solid State Group, Reactor Physics Department, Atomic Energy Authority” so I would like to express my deep thank for all colleagues at the laboratory for their encouragement.

CONTENTS

	Page No.
Aim of work	
Abstract	
Summary	
Chapter I:	
۱.۱. Introduction	۱
۱.۲. General outline on ferrites	۲
۱.۳. Literature review	۴
Chapter II: Structure properties	۱۱
۲.۱ Structure aspects of spinel ferrites	۱۱
۲.۱.۱ Crystal Structure	۱۱
۲.۱.۲. Distribution of the metal ions in spinel cubic unit cell	۱۷
۲.۱.۳ Factors affecting the cation distribution in spinel unit cell	۱۸
۲.۲. Crystal field theory	۲۰
Jahn-Teller distortion	۲۵
۲.۳. Magnetic properties	۲۷
۲.۳.۱. Néel theory of ferrimagnetism	۲۷
۲.۳.۲. Types of interactions in ferrimagnetics	۲۹
۲.۴. Electrical properties	۳۲
۲.۴.۱. Mechanisms of the electrical conduction in transition metal oxides	۳۴
i) <i>Band and hopping mechanisms</i>	۳۴
ii) <i>Verwey model</i>	۳۵
iii) <i>Polaron model</i>	۳۵
۲.۴.۲. Dielectric losses	۳۷
۲.۴.۳. Frequency dependence of the loss tangent ($\tan\delta$)	۴۰
Chapter III: Experimental details.	

۳.۱. Preparation of samples.	۴۲
۳.۱.۱ X-ray powder diffraction.	۴۴
۳.۱.۲ Elemental analysis using Energy Dispersive X-ray (EDX)	۴۴
۳.۲. Mössbauer effect spectroscopy	۴۶
۳.۲.۱ Introduction	۴۶
I) Nuclear decay of ^{57}Co isotope	۴۶
II) Recoil and line broadening.	۴۷
III) Resonant absorption.	۴۸
IV) Recoilless emission and absorption.	۴۹
V) Doppler shift.	۴۹
VI) Recoil-free events.	۵۰
۳.۲.۲ Mössbauer effect parameters.	۵۱
I) Isomer shift	۵۱
II) Quadrupole splitting	۵۳
III) Magnetic hyperfine splitting	۵۵
۳.۲.۳ Description of the Mössbauer effect spectrometer	۵۹
۳.۲.۴ Calibration of the ME spectrometer	۶۵
۳.۳ Electrical measurements.	۷۲

Chapter IV: Results and discussion

۴.۱ Structural and compositional analysis	۷۷
۴.۱.۱ X-Ray diffraction results.	۷۷
۴.۱.۲ Energy Dispersive X-ray (EDX) analysis.	۸۱
۴.۱.۳ Composition dependence on density, porosity and grain size:	۸۲
۴.۲ Mössbauer effect results	۸۵
۴.۲.۱. Cation distribution	۸۸
۴.۲.۲. Quadrupole interaction	۸۹

4.2.4. Hyperfine magnetic fields H_{hf}	91
4.3 Results of the electrical measurements	95
4.3.1 Temperature and frequency dependence of conductivity.	95
4.3.2 Frequency dependence of the dielectric parameters.	110
I) Dielectric loss tangent ' $\tan\delta$ '	110
II) Real part ϵ' and imaginary part ϵ'' of dielectric constant ϵ	117
4.3.3 Temperature dependence of the dielectric parameters	122
I) Dielectric loss tangent $\tan(\delta)$	122
II) Dielectric constant ϵ' and imaginary part of dielectric constant	122
4.4 Transition temperature T_N	130
General conclusion	132
References	135
Arabic summary	

LIST OF TABLES

	Page No.
Table (۲.۱)	۱۵
The crystallographic data for the cubic unit cell of the spinel structure.	
Table (۲.۲)	۱۶
The crystallographic data for the tetragonal unit cell of spinel structure.	
Table (۳.۱)	۴۳
Prefirring and sintering temperature for CuFe_xO_4 and $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ samples	
Table (۳.۲)	۶۵
ME parameters of the standard materials (α - Fe_xO_y , Metallic iron and Stainless steel at room temperature)	
Table (۴.۱)	۷۷
Lattice parameters and unit cell volume for tetragonal unit cell CuFe_xO_4 and $\text{Cu}_{1-x}\text{Zn}_x\text{Fe}_{0.5}\text{Ga}_{0.5}\text{O}_4$ ($0 \leq x \leq 1$).	
Table (۴.۲)	۸۰
Lattice parameters and unit cell volume for the cubic unit cell $\text{Cu}_{1-x}\text{Zn}_x\text{Fe}_{0.5}\text{Ga}_{0.5}\text{O}_4$ ($0.2 \leq x \leq 0.5$).	
Table (۴.۳)	۸۲
Values of the elemental analysis obtained from (EDX) (Exp.) and the calculated (Cal) for CuFe_xO_4 and $\text{Cu}_{1-x}\text{Zn}_x\text{Fe}_{0.5}\text{Ga}_{0.5}\text{O}_4$ ($0 \leq x \leq 1$) ferrite samples.	
Table (۴.۴)	۸۴
Density, porosity and grain size data for the spinel ferrite CuFe_xO_4 and $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$	
Table (۴.۵)	۸۹
Cation distribution over A –and B –sites for $\text{Cu}_{1-x}\text{Zn}_x\text{Fe}_{0.5}\text{Ga}_{0.5}\text{O}_4$ spinel system.	
Table (۴.۶)	۹۳
ME parameters at ۲۹۳ K for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ spinel ferrite.	
Table (۴.۷)	۹۴
ME parameters at ۱۲ K for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ spinel ferrite	
Table (۴.۸)	۱۱۷
Activation energy at low and high frequencies for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ spinel ferrites	

LIST OF FIGURES

	Page No.
Fig.(٢.١)	١٢
(a) The cubic unit cell of the spinel structure (b) Two octants of the spinel unit cell	
Fig.(٢.٢):	١٣
(a) Cubic close- packed structure. (b) Tetrahedral site. (c) Octahedral site.	
Fig.(٢.٣)	٢١
(i) Metal atom in octahedral B- and tetrahedral A-site (ii) The angular distribution of the d orbital.	
Fig.(٢.٤)	٢٢
The crystal field originates from an electrostatic interactions; (a) The d_{xy} orbital in lower energy (b) The $d_{x^2-y^2}$ orbital in octahedral environment.	
Fig.(٢.٥)	٢٣
The crystal field in an (a) Octahedral (b) Tetrahedral environment.	
Fig.(٢.٦)	٢٤
Electronic configurations for the (a) high-spin (weak-field) (b) low-spin (strong-field) cases for a 3d^1 ion.	
Fig.(٢.٧)	٢٦
Jahn –Teller distortion.	
Fig.(٢.٨)	٢٧
Interatomic distances and inter bond angles in the spinel where p, q, r, s are the distance between metal ions Me and Oxygen ions.	
Fig.(٢.٩)	٢٨
Nèel model of ferromagnetism.	
Fig.(٢.١٠)	٢٩
Nearest neighbor to an oxygen ion showing $A-B$ interaction through the oxygen ion.	
Fig.(٢.١١)	٣٠
Superexchange interaction.	
Fig.(٢.١٢)	٣١
Double-exchange interaction. (a) Before exchange. (b) After exchange,	

Fig.(۲.۱۳)	The shape of the polarization well.	۳۷
Fig.(۲.۱۴)	a) Equivalent circuit for dielectric losses b) Variations of $\tan \delta$ with frequency with normal resonance like behavior c) Variation of $\tan \delta$ with frequency at constant temperature	۳۹
Fig.(۳.۱)	Construction of Energy Dispersive X-Ray detector	۴۵
Fig.(۳.۲)	Nuclear decay scheme for ^{60}Co isotope	۴۶
Fig.(۳.۳)	Recoil in a free nucleus during gamma ray emission.	۴۷
Fig.(۳.۴)	Gamma Emission and Absorption in free atoms R: is the energy shift produced by the recoil effect E_r : is the resonance energy, δ : is the Doppler width.	۴۸
Fig.(۳.۵)	Nuclear energy levels and the isomer shift.	۵۲
Fig.(۳.۶)	Nuclear energy levels and the quadrupole splitting	۵۴
Fig.(۳.۷)	Hyperfine splitting of nuclear energy levels in a magnetic field	۵۸
Fig.(۳.۸)	The wave forms relative to the incoming bistable signal; a)- The high square waveform created by <i>BOR+</i> generator integrated by the 7 Hz generator b)- The velocity waveform. c)- The drive waveform.	۶۱
Fig.(۳.۹)	a)- The gamma-ray spectrum for the used ^{60}Co source in the PHA mode for the PCA-II analyzer. b)- The spectrum after the separation of 14.4 keV .	۶۴
Fig.(۳.۱۰)	ME spectra at room temperature of (a) $\alpha\text{-Fe}_2\text{O}_3$, (b) Metallic iron (c) Stainless steel.	۶۶
Fig.(۳.۱۱)	Block diagram for the installed closed cycle cryogenic variable temperature workstation attached with the ME equipment.	۶۹

Fig.(٢.١٢)	The ME spectra of the natural pure iron foil at room temperature and at ١٢ K.	٧١
Fig.(٣.١٣)	Block diagram of the adaptive technique used for ac and dc electrical measurements.	٧٣
Fig (٣.١٤)	Block diagram for the circuit used in the ac electrical measurements for CuFe_yO_z sample	٧٤
Fig.(٤.١)	X-ray powder diffraction patterns for CuFe_yO_z and $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ spinel ferrite.	٧٨
Fig.(٤.٢)	Tetragonal distortion of MO_6 octahedron and the $3d$ orbital energy splitting by the octahedron (O_h) and the tetrahedral site symmetries for $\text{Cu}^{2+} (d^9)$.	٧٩
Fig.(٤.٣)	Elemental analysis for CuFe_yO_z , $\text{CuGa}_{1-y}\text{Fe}_y\text{O}_z$ and $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ ferrite samples.	٨١
Fig.(٤.٤)	ME spectrum for CuFe_yO_z at ٢٩٣ K.	٨٦
Fig.(٤.٥)	ME spectra for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ compounds	٨٧
Fig.(٤.٦)	ME parameters for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ spinel at ١٢ K	٩٢
Fig.(٤.٧)	Variation of conductivity as $\ln \sigma$ verses reciprocal of temperature $1000/T$ at the frequency range 10^2 to 10^5 Hz for CuFe_yO_z ferrite.	٩٦
Fig.(٤.٨)	$\ln \sigma$ versus $1000/T$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ ($x=0.1, 0.2$ and 0.3) at different frequencies.	٩٧
Fig.(٤.٩)	$\ln \sigma$ versus $1000/T$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ ($x=0.3, 0.4$ and 0.5) at different frequencies	٩٨
Fig.(٤.١٠)	Activation energy versus Zn^{2+} content for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$ at different frequencies.	١٠٢
Fig.(٤.١١)	Plot of dc conductivity as $(\ln \sigma)$ verses reciprocal of temperature ($1/T$) for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$	١٠٤
Fig.(٤.١٢)	Activation energy versus Zn content of $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{1-y}\text{Fe}_y\text{O}_z$	١٠٥

Fig.(٤.١٣)	Variation of conductivity as $\ln(\sigma_{ac})$ with frequency as $\ln(\omega)$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$ at different temperatures.	١٠٧
Fig.(٤.١٤)	Variation of the exponent S of the power law and $\ln B$ versus temperature for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$	١٠٩
Fig.(٤.١٥)	Dielectric loss tangent $\tan(\delta)$ versus $\log F(\text{Hz})$ for $\text{CuFe}_\gamma\text{O}_\xi$ and $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$ at room temperature a) at the frequency range ($10^2 - 10^5 \text{ Hz}$) b) at the frequency range ($1 - 10^5 \text{ Hz}$)	١١١
Fig.(٤.١٦)	Variation of dielectric loss tangent $\tan(\delta)$ with frequency as $\log F$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$; ($x=0.1, 0.2$) at different temperatures.	١١٣
Fig.(٤.١٧)	Variation of dielectric loss tangent $\tan(\delta)$ with frequency as $\log F$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$; ($x=0.3, 0.4, 0.5$) at different temperature.	١١٤
Fig.(٤.١٨)	Relaxation time $\ln(\tau)$ versus reciprocal of temperature $1/T$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$	١١٨
Fig.(٤.١٩)	Variation of dielectric constant ϵ' and the imaginary part of dielectric constant ϵ'' with frequency as $\ln(\omega)$ for $\text{CuFe}_\gamma\text{O}_\xi$ and $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$ at room temperature.	١١٩
Fig.(٤.٢٠)	Variation of dielectric constant ϵ' versus frequency as $\ln(\omega)$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$; at different temperatures.	١٢٠
Fig.(٤.٢١)	Variation of the imaginary part of the dielectric constant ϵ'' versus frequency as $\ln(\omega)$ for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$; at different temperatures.	١٢١
Fig.(٤.٢٢)	Variation of dielectric loss tangent $\tan(\delta)$ with temperature for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$ at different frequencies.	١٢٣
Fig.(٤.٢٣)	Variation of dielectric constant ϵ' versus temperature for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_\xi$ ($x=0.1, 0.2$, and 0.3) at different frequencies.	١٢٤

Fig.(٤.٢٤)	Variation of dielectric constant ϵ' versus temperature for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ ($x=0.3, 0.4$, and 0.5) at different frequencies.	١٢٥
Fig.(٤.٢٥)	Variation of the imaginary part of the dielectric constant ϵ'' versus temperature for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ ($x=0.1, 0.1$, and 0.2) at different frequencies.	١٢٨
Fig.(٤.٢٦)	Variation of the imaginary part of the dielectric constant ϵ'' versus temperature for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ ($x=0.3, 0.4$, and 0.5) at different frequencies.	١٢٩
Fig.(٤.٢٧)	The plot of transition temperature (T_N) against Zn^{2+} content x for $\text{Cu}_{1-x}\text{Zn}_x\text{Ga}_{0.5}\text{Fe}_{0.5}\text{O}_4$ ($0.1 \leq x \leq 0.5$).	١٣١

AIM OF WORK