



AIN SHAMS UNIVERSITY  
FACULTY OF ENGINEERING  
Design and Production Engineering

**Formability and Rolling of Ductile Iron Subjected to Different  
Thermo-Mechanical Treatments**

A Thesis submitted in partial fulfillment of the requirements of the  
degree of

Master of Science in Mechanical Engineering

(Design and Production Engineering)

By

**Marwan Faisal Zaki Abdelwahed**

Bachelor of Science in Mechanical Engineering

(Design and Production Engineering)

Faculty of Engineering, Ain Shams University, 2014

Supervised By

**Prof. Dr. Mohamed Ahmed Taha**

**Dr. Eman El - Shenawy**

Cairo - (2017)



AIN SHAMS UNIVERSITY  
FACULTY OF ENGINEERING  
Design and Production Engineering

**Formability and Rolling of Ductile Iron Subjected to Different  
Thermo-Mechanical Treatments**

By

**Marwan Faisal Zaki Abdelwahed**

Bachelor of Science in Mechanical Engineering  
(Design and Production Engineering)  
Faculty of Engineering, Ain Shams University, 2014

**Supervising' Committee**

| <b>Name and Affiliation</b>                                                                               | <b>Signature</b> |
|-----------------------------------------------------------------------------------------------------------|------------------|
| <b>Prof. Dr. Mohamed Ahmed Taha</b><br>Design and Production , Ain Shams University                       | .....            |
| <b>Dr. Eman El - Shenawy</b><br>Department of Plastic Deformation, Central<br>Metallurgical R&D Institute | .....            |

Date:



AIN SHAMS UNIVERSITY  
FACULTY OF ENGINEERING  
Design and Production Engineering

**Formability and Rolling of Ductile Iron Subjected to Different  
Thermo-Mechanical Treatments**

By

**Marwan Faisal Zaki Abdelwahed**

Bachelor of Science in Mechanical Engineering  
(Design and Production Engineering)  
Faculty of Engineering, Ain Shams University, 2014

**Examiners' Committee**

**Name and Affiliation**

**Signature**

**Prof. Dr. Iman El - Mahallawi**

Professor of Materials and Metallurgical Engineering,  
Faculty of Engineering, Cairo University.

.....

**Prof. Dr. Ahmed Moneeb ElSabbagh**

Professor of Materials and Metallurgical Engineering,  
Faculty of Engineering, Ain Shams University.

.....

**Prof. Dr. Mohamed Ahmed Taha**

Professor of Materials and Metallurgical Engineering,  
Faculty of Engineering, Ain Shams University.

.....

Date:

## Statement

This thesis is submitted as a partial fulfillment of Master of Science in Mechanical Engineering, Faculty of Engineering, Ain shams University.

The author carried out the work included in this thesis, and no part of it has been submitted for a degree or a qualification at any other scientific entity.

Signature

.....

**Marwan Faisal Zaki**

Date:

## Acknowledgments

This dissertation would not have been possible without the guidance and help of several persons who contributed and extended their valuable assistance in the preparation and completion of this study.

I would like to start by thanking my supervisor Prof. Dr. Mohamed Ahmed Taha for his remarkable patience, helpful comments and enthusiastic support to finalize this work.

Thank are also extended to Dr. Eman El-Shenawy for her constant supervision and help throughout my work and furthermore for providing me with a motivating and warm environment to work in.

Finally, I would like to thank my family, friends and colleagues especially Eng. Alaa Mohsen, Eng. Ahmed Awad and Mr. Mohamed Zaki for their motivation and assurance at hard times.

## Researcher Data

**Name** : Marwan Faisal Zaki Abdelwahed  
**Date of birth** : 22/07/1992  
**Place of birth** : Cairo, Egypt  
**Last academic degree** : Bilateral Bachelor Degree  
**Field of specialization** : Materials Engineering  
**University issued the degree** : Ain Shams University and Clausthal University of Technology  
**Date of issued degree** : July, 2014  
**Current job** : Demonstrator, Design and Production Engineering Department, Faculty of Engineering, Ain Shams University at Cairo, Egypt.

## Abstract

Ductile cast iron (DI) is an iron-carbon alloy, in which the structure is composed of graphite nodules embedded in a steel matrix. The thermo-mechanical behavior of ductile cast iron was studied by using the thermomechanical simulator Gleeble-3500 and Dilatometer Dil 805D. This was to predict the rolling condition for producing sheets and strips. The physical simulation of hot rolling process was conducted on specimens at a range of deformation temperatures 950 to 800 °C at three different strain rates; namely 0.05, 0.1 and 0.5 s<sup>-1</sup>. The results obtained from the tests at the applied strain rates, showed minimum values of compressive stresses at 850 °C. By increasing the deformation temperature up to 900 °C, the compressive stresses increased to reach the maximum values, beyond which the compressive stresses decreased again. Furthermore, remarkable dynamic recrystallization was observed at deformation temperatures of 800 and 850 °C with applied strain rates of 0.05 and 0.1 s<sup>-1</sup>. Moreover, three deformation hits were successively applied on a test-specimen at temperatures namely; 900, 850 and 750 °C with the same strain rate of 0.1 s<sup>-1</sup>. No cracks were observed, up to 50% deformation, after the three-consecutive hits. Gleeble test results were correlated with the microstructure observations on the quenched specimens at their deformation temperatures; where the changes in structure and graphite morphology were reported. The results were analyzed so that to determine the suitable rolling conditions required for safe rolling of the ductile iron plates. As a conclusion, ductile iron could be safely rolled at different deformation temperatures and strain rates studied in this work. The rolled sheets and strips exhibit Ferritic - Martensitic structure in which graphite nodules were somewhere elongated.

### **Keywords:**

Ductile Cast Iron, Thermo-mechanical behavior, Gleeble-3500, Hot Rolling, Physical simulation

# Table of Content

|                                                                                                   |           |
|---------------------------------------------------------------------------------------------------|-----------|
| Acknowledgments .....                                                                             | v         |
| Researcher Data .....                                                                             | vi        |
| Abstract .....                                                                                    | vii       |
| Table of Content .....                                                                            | viii      |
| List of Figures .....                                                                             | x         |
| List of Tables .....                                                                              | xiv       |
| List of Abbreviations .....                                                                       | xi        |
| List of Symbols .....                                                                             | xii       |
| <b>Chapter 1 : Introduction .....</b>                                                             | <b>1</b>  |
| <b>Chapter 2 : Literature Survey .....</b>                                                        | <b>3</b>  |
| 2.1 Cast Iron .....                                                                               | 4         |
| 2.1.1 The Iron-Graphite System .....                                                              | 5         |
| 2.1.2 Types of Cast Iron .....                                                                    | 7         |
| 2.2 Ductile Iron .....                                                                            | 10        |
| 2.2.1 Treatment of Ductile Iron .....                                                             | 10        |
| 2.2.1.1 The Sandwich Cover Process .....                                                          | 11        |
| 2.2.1.2 The Cored Wire Process .....                                                              | 12        |
| 2.2.2 Microstructural Phases in Ductile Iron .....                                                | 13        |
| 2.2.3 Heat Treatment of Ductile Iron .....                                                        | 16        |
| 2.2.4 Properties of Ductile Iron .....                                                            | 18        |
| 2.2.5 Applications of Ductile Iron .....                                                          | 20        |
| 2.3 Relevant work .....                                                                           | 21        |
| 2.4 Scientific aims and objective .....                                                           | 23        |
| 2.4.1 Scientific aims .....                                                                       | 23        |
| 2.4.2 Objective of this work .....                                                                | 23        |
| <b>Chapter 3 : Experimental Work .....</b>                                                        | <b>25</b> |
| 3.1 Material .....                                                                                | 26        |
| 3.2 Experimental Work .....                                                                       | 26        |
| 3.2.1 Differential Dilatometer .....                                                              | 26        |
| 3.2.2 Heat Treatment of DI-I specimens .....                                                      | 27        |
| 3.2.3 Thermomechanical Processing .....                                                           | 28        |
| 3.2.3.1 Gleeble-3500 thermomechanical simulator .....                                             | 28        |
| 3.2.3.2 Dilatometer Dil 805D thermomechanical simulator .....                                     | 34        |
| 3.2.4 Microstructure Investigation and Phases Identification .....                                | 35        |
| 3.2.4.1 Light Optical Microscope .....                                                            | 35        |
| 3.2.4.2 Environmental Scanning Electron Microscope (ESEM) and Energy Dispersive X-Ray (EDX) ..... | 36        |

|                                                                                         |           |
|-----------------------------------------------------------------------------------------|-----------|
| 3.2.4.3 Micro-hardness Test .....                                                       | 36        |
| 3.2.5 Rolling experiment and Tensile Test .....                                         | 36        |
| <b>Chapter 4 : Results and Discussion .....</b>                                         | <b>37</b> |
| 4.1 Dilation test and Heat Treatment .....                                              | 38        |
| 4.1.1 Dilation Test .....                                                               | 38        |
| 4.1.2 Heat Treatment and Microstructure Investigation .....                             | 48        |
| 4.2 Thermo-mechanical behavior of DI .....                                              | 50        |
| 4.2.1 Deformation Behavior of DI-I (CE = 4.48) .....                                    | 50        |
| 4.2.1.1 Single deformation step .....                                                   | 50        |
| 4.2.1.1.1 Effect of deformation temperature on thermo-mechanical behavior of DI-I ..... | 50        |
| 4.2.1.1.1.1 True stress – true strain curves .....                                      | 50        |
| 4.2.1.1.1.2 Microstructure Evolution .....                                              | 54        |
| 4.2.1.1.1.3 Elastic Modulus and Proof strength .....                                    | 66        |
| 4.2.1.1.1.4 Strain hardening & Dynamic Recrystallization .....                          | 67        |
| 4.2.1.1.2 Effect of applied strain rates on thermo-mechanical behavior of DI-I .....    | 70        |
| 4.2.1.1.2.1 True stress – true strain curves .....                                      | 70        |
| 4.2.1.1.2.2 Elastic Modulus and Proof strength .....                                    | 72        |
| 4.2.1.1.2.3 Strain hardening & Dynamic Recrystallization .....                          | 74        |
| 4.2.1.1.2.4 Microstructure Evolution .....                                              | 77        |
| 4.2.1.2 Successive deformation steps .....                                              | 79        |
| 4.2.2 Deformation Behavior of DI-II (CE = 4.64) .....                                   | 81        |
| 4.2.3 Deformation Behavior of DI-III (CE = 4.35) .....                                  | 83        |
| 4.2.4 Comparison with Previous Data in Literature .....                                 | 85        |
| 4.3 Hot Rolling of Ductile Iron .....                                                   | 86        |
| <b>Chapter 5 : Conclusion and Future Work.....</b>                                      | <b>90</b> |
| 5.1 Conclusions.....                                                                    | 91        |
| 5.2 Future work.....                                                                    | 93        |
| <b>References .....</b>                                                                 | <b>94</b> |

## List of Figures

|                                                                                                                                                              |    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Fig. 2.1: Cast iron family [15] .....                                                                                                                        | 4  |
| Fig. 2.2: Fe-C phase diagram [18] .....                                                                                                                      | 5  |
| Fig. 2.3: Effect of alloying contents on microstructure of CI [16].....                                                                                      | 7  |
| Fig. 2.4: Different types of CI & their microstructure at different CR [17] .....                                                                            | 8  |
| Fig. 2.5: Classification of CI depending on CR [20] .....                                                                                                    | 9  |
| Fig. 2.6: Microstructure of pearlitic + ferritic matrix DI [23].....                                                                                         | 10 |
| Fig. 2.7: Sandwich Cover Process [26].....                                                                                                                   | 11 |
| Fig. 2.8: Hollow wires containing Mg metal found in cored wire process [31] ...                                                                              | 12 |
| Fig. 2.9: Fe-Fe <sub>3</sub> C: phase diagram with 2% silicon [32].....                                                                                      | 13 |
| Fig. 2.10: 3.6% C, 1.72% Si and 0.27% Mn [8] .....                                                                                                           | 14 |
| Fig. 2.11: Graphite nodules acts as crack-arresters in DI [34] .....                                                                                         | 16 |
| Fig. 2.12: CCT diagram represents annealing, normalizing, and quenching [17]                                                                                 | 17 |
| Fig. 2.13: Mechanical properties & microstructure of DI [40].....                                                                                            | 19 |
| Fig. 3.1: Treatment schedules applied on differential dilatometer specimen.....                                                                              | 27 |
| Fig. 3.2: Gleeble test specimen .....                                                                                                                        | 29 |
| Fig. 3.3: Plane view of Gleeble test machine chamber .....                                                                                                   | 29 |
| Fig. 3.4: Schematic plane view of Gleeble machine chamber .....                                                                                              | 30 |
| Fig. 3.5: Schematic presentation of deformation schedules applied on DI-I specimens .....                                                                    | 31 |
| Fig. 3.6: Time – temperature of 2-consecutive hits applied on DI-I .....                                                                                     | 33 |
| Fig. 3.7: (Time – temperature) of 3-consecutive hits applied on DI-II .....                                                                                  | 33 |
| Fig. 3.8: Gleeble test specimen after deformation .....                                                                                                      | 33 |
| Fig. 3.9: Section A-A & section B-B are directions perpendicular & parallel to the applied deformation force respectively.....                               | 34 |
| Fig. 3.10: Dilatometer Dil 805D (Plan view).....                                                                                                             | 35 |
| Fig. 4.1 (a): (Relative change in length – Time – Temperature) of T-I.....                                                                                   | 38 |
| Fig. 4.1 (b): (Relative change in length – Time – Temperature) of T-II.....                                                                                  | 38 |
| Fig. 4.1 (c): (Relative change in length – Time – Temperature) of T-III .....                                                                                | 39 |
| Fig. 4.1 (d): (Relative change in length – Time – Temperature) of T-IV .....                                                                                 | 40 |
| Fig. 4.2: Enlarged part from (Relative change in length – Temperature) during heating for T-I specimen .....                                                 | 41 |
| Fig. 4.3: Critical transformation temperatures obtained from dilation test during heating are imposed on (Iron – Carbon) phase diagram with 3% Si [54] ..... | 41 |
| Fig. 4.4 (a): (Relative change in length – Time – Temperature) while soaking of T-I specimen.....                                                            | 43 |

|                                                                                                                                                                                         |    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Fig. 4.4 (b): (Relative change in length – Time – Temperature) while soaking of T-II specimen .....                                                                                     | 43 |
| Fig. 4.4 (c): (Relative change in length – Time – Temperature) while soaking of T-III specimen .....                                                                                    | 44 |
| Fig. 4.4 (d): (Relative change in length – Time – Temperature) while soaking of T-IV specimen .....                                                                                     | 44 |
| Fig. 4.5: Enlarged part form (Relative change in length – Temperature) during cooling of T-I from 950 °C.....                                                                           | 45 |
| Fig. 4.6: Enlarged part form (Relative change in length – Temperature) during cooling of T-III from 850 °C.....                                                                         | 46 |
| Fig. 4.7: Enlarged part form (Relative change in length – Temperature) during cooling of T-IV from 800 °C.....                                                                          | 46 |
| Fig. 4.8 (a): Volume fraction of transformed austenite as function of time .....                                                                                                        | 47 |
| Fig. 4.8 (b): Volume fraction of transformed austenite as function of temperature .....                                                                                                 | 47 |
| Fig. 4.9: Continuous cooling diagram (CCT) of DI-I is imposed on TTT [55] .....                                                                                                         | 48 |
| Fig. 4.10: (a), (b), (c), (d) & (e): Microstructures of as-cast, H-I, H-II, H-III & H-IV respectively .....                                                                             | 49 |
| Fig. 4.11: (a): TMB of DI-I at applied strain rate of 0.05 s <sup>-1</sup> .....                                                                                                        | 51 |
| Fig. 4.11: (b): TMB of DI-I at applied strain rate of 0.1 s <sup>-1</sup> .....                                                                                                         | 51 |
| Fig. 4.11: (c): TMB of DI-I at applied strain rate of 0.5 s <sup>-1</sup> .....                                                                                                         | 52 |
| Fig. 4.12: True stress – true strain curve of DI (CE = 4.8) at different deformation temperatures with applied strain rate of 10 s <sup>-1</sup> in other work [12] .....               | 53 |
| Fig. 4.13: (a): The obtained microstructure of DI-I specimens in direction perpendicular to applied force with applied strain rate of 0.05 s <sup>-1</sup> and without deformation..... | 55 |
| Fig. 4.13: (b): The obtained microstructure of the specimens in direction perpendicular to applied force with applied strain rate of 0.1 s <sup>-1</sup> and without deformation.....   | 56 |
| Fig. 4.13: (c): The obtained microstructure of the specimens in direction perpendicular to applied force with applied strain rate of 0.5 s <sup>-1</sup> and without deformation.....   | 57 |
| Fig. 4.14 (a): The obtained microstructure of DI-I specimens in direction perpendicular and parallel to applied force with applied strain rate of 0.05 s <sup>-1</sup> .....            | 58 |
| Fig. 4.14 (b): The obtained microstructure of DI-I specimens in direction perpendicular & parallel to applied force with applied strain rate of 0.1 s <sup>-1</sup> .....               | 59 |
| Fig. 4.14 (c): The obtained microstructure of DI-I specimens in direction perpendicular & parallel to applied force with applied strain rate of 0.5 s <sup>-1</sup> .....               | 60 |

|                                                                                                                                                                            |    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Fig. 4.15 (a): ESEM of specimen deformed at 850 °C with applied strain rate of 0.05 s <sup>-1</sup> and EDX analysis of fine ferrite surrounding Gr nodules .....          | 61 |
| Fig. 4.15 (b): ESEM of specimen deformed at 850 °C with applied strain rate of 0.05 s <sup>-1</sup> and EDX analysis of fine ferrite within matrix .....                   | 62 |
| Fig. 4.15 (c): ESEM of specimen deformed at 850 °C with applied strain rate of 0.05 s <sup>-1</sup> and EDX analysis of fine pearlite transformed after deformation. ....  | 63 |
| Fig. 4.16: (a): ESEM of specimen deformed at 800 °C with applied strain rate of 0.05 s <sup>-1</sup> and EDX analysis of fine ferrite within matrix .....                  | 64 |
| Fig. 4.16: (b): ESEM of specimen deformed at 800 °C with applied strain rate of 0.05 s <sup>-1</sup> and EDX analysis of fine pearlite transformed after deformation. .... | 65 |
| Fig. 4.17: Effect of deformation temperature on Elastic modulus of DI-I at applied strain rates of 0.05, 0.1 & 0.5 s <sup>-1</sup> .....                                   | 66 |
| Fig. 4.18: Effect of deformation temperature on the proof strength of DI-I at applied strain rates of 0.05, 0.1 & 0.5 s <sup>-1</sup> .....                                | 67 |
| Fig. 4.19: (a): Effect of deformation temperature while applying strain rate of 0.05 s <sup>-1</sup> .....                                                                 | 68 |
| Fig. 4.19: (b): Effect of deformation temperature while applying strain rate of 0.1 s <sup>-1</sup> .....                                                                  | 69 |
| Fig. 4.19: (c): Effect of deformation temperature while applying strain rate of 0.5 s <sup>-1</sup> .....                                                                  | 69 |
| Fig. 4.20: (a): Effect of applied strain rate on TMB of DI-I at 950 °C .....                                                                                               | 70 |
| Fig. 4.20: (b): Effect of applied strain rate on TMB of DI-I at 900 °C .....                                                                                               | 71 |
| Fig. 4.20: (c): Effect of applied strain rate on TMB of DI-I at 850 °C .....                                                                                               | 71 |
| Fig. 4.20: (d): Effect of applied strain rate on TMB of DI-I at 800 °C .....                                                                                               | 72 |
| Fig. 4.21: Effect of applied strain rate on Elastic modulus of DI-I at elevated deformation temperatures of 950, 900, 850 & 800 °C .....                                   | 73 |
| Fig. 4.22: Effect of applied strain rate on proof strength of DI-I at elevated deformation temperatures of 950, 900, 850 & 800 °C .....                                    | 73 |
| Fig. 4.23: (a): Effect of applied strain rate during deformation process of DI-I at 950 °C .....                                                                           | 75 |
| Fig. 4.23: (b): Effect of applied strain rate during deformation process of DI-I at 900 °C .....                                                                           | 75 |
| Fig. 4.23: (c): Effect of applied strain rate during deformation process of DI-I at 850 °C .....                                                                           | 76 |
| Fig. 4.23: (d): Effect of applied strain rate during deformation process of DI-I at 800 °C .....                                                                           | 76 |
| Fig. 4.24: True stress true strain curve resulted from two successive deformation steps at 950 and 900 °C with applied strain rate of 0.1 s <sup>-1</sup> .....            | 79 |

|                                                                                                                                                                                             |    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Fig. 4.25: Single deformation step & successive deformation steps at 950 & 900 °C with applied strain rate of 0.1 s <sup>-1</sup> .....                                                     | 80 |
| Fig. 4.26: Microstructure obtained (DI-I) of single step deformation at 950 °C and two successive deformation steps at 950 & 900 °C with applied strain rate of 0.1 s <sup>-1</sup> .....   | 80 |
| Fig. 4.27: True stress true strain curve (DI-II) of three successive deformation steps at 900, 850 & 750 °C with applied strain rate of 0.1 s <sup>-1</sup> .....                           | 82 |
| Fig. 4.28: (a) and (b): Heat treated specimen and thermo-mechanical treated specimen respectively .....                                                                                     | 82 |
| Fig. 4.29: True stress true strain curve of DI-III at 950 °C with applied strain rate of 0.07 s <sup>-1</sup> .....                                                                         | 83 |
| Fig. 4.30: Two successive deformation steps of DI-III at 950 & 900 °C with applied strain rate of 0.07 s <sup>-1</sup> .....                                                                | 84 |
| Fig. 4.31: Microstructure obtained (DI-III) of single step deformation at 950 °C and two successive deformation steps at 950 & 900 °C with applied strain rate of 0.1 s <sup>-1</sup> ..... | 84 |
| Fig. 4.32: Hot deformation behavior of DI-I, D-II and DI-III compared to Kai Qi work [12].....                                                                                              | 85 |
| Fig. 4.33: Hot deformation behavior of DI-I and DI-II compared to Kai Qi work [12] .....                                                                                                    | 86 |
| Fig. 4.34: DI-III specimen before and after applying the rolling process .....                                                                                                              | 87 |
| Fig. 4.35: Stress strain curve of as-rolled specimen 3.9 mm thick (3 steps reduction, each 20% reduction) and as-cast (received) 12 mm thick specimen.....                                  | 87 |
| Fig. 4.36: Stress strain curve of as-cast specimen & heat treated specimen after rolling .....                                                                                              | 88 |
| Fig. 4.37: Relationship between the reduction (%), ductility and UTS of DI-III in as-cast and as-rolled condition .....                                                                     | 88 |
| Fig. 4.38: (a) and (b): Microstructure of DI-III obtained after rolling process and subjecting the rolled specimen to heat treatment .....                                                  | 89 |

**List of Tables**

Table 2.1: Classification of CI depending on graphite form [14]. .....8

Table 2.2: Properties of different grades of DI [40] .....19

Table 2.3: Mechanical properties related to DI microstructure [40] .....20

Table 3.1: Chemical composition of DI alloys .....26

Table 3.2: Treatment procedures on differential dilatometer specimens .....27

Table 3.3: DI-I heat treatment schedules .....28

Table 3.4: Deformation schedules of DI-I specimens.....31

Table 4.1: The SH exponent values calculated form resulted curves.....77

Table 4.2: The resulted microstructure of the deformed specimens before etching  
.....78

## List of Abbreviations

|       |                                              |
|-------|----------------------------------------------|
| ASU   | : Ain Shams University                       |
| CCT   | : Continuous Cooling Transformation          |
| CE    | : Carbon Equivalent                          |
| CI    | : Cast Iron                                  |
| CMRDI | : Central Metallurgical Research Institute   |
| CR    | : Cooling Rate                               |
| DI    | : Ductile cast iron                          |
| DRX   | : Dynamic Recrystallization                  |
| EDX   | : Energy Dispersive X-ray Spectroscopy       |
| ESEM  | : Environmental Scanning Electron Microscope |
| GCI   | : Grey Cast Iron                             |
| Gr    | : Graphite                                   |
| IMET  | : Institute of Metallurgy                    |
| LVDT  | : Linear Variable Differential Transformer   |
| SH    | : Strain Hardening                           |
| Temp. | : Temperature                                |
| TMB   | : Thermomechanical Behavior                  |
| TTT   | : Time Temperature Transformation            |
| TUC   | : Clausthal University of Technology         |
| UTS   | : Ultimate Tensile Strength                  |