

Ain Shams University Faculty of Science Physics Department

# "Structural and Physical Properties of Synthesized (Nickel- Zinc- Gallium) Ferrites Doped with Rare-Earth Elements"

A thesis

Submitted in Partial Fulfillment for the requirements of Master of Science in (Solid State Physics)

 $\mathcal{B}_{\mathcal{I}}$ 

# Shimaa Hamdy Ahmed Kelany

**Under Supervision** 

Prof. Dr. K. M. El-Sayed

Professor of Solid State physics Physics Department Faculty of science Ain Shams University Prof. Dr. S.S. Ata –Allah

Professor of Solid State physics Chairman of Egyptian Nuclear and Radiological Regulatory Authority


### Prof. Dr. Ali Abed El-Rahman Ahmed Abou Shama

Professor of Solid State physics
Physics Department Faculty of science
Ain Shams University

#### Dr. Mohamed Bakr Mohamed

Assistant Professor of Solid State physics Physics Department Faculty of science Ain Shams University

(2017)



## **Approval sheet**

**Student Name:** Shimaa Hamdy Ahmed Kelany

B.Sc. in physics, (2007)

#### Thesis title:

"Structural and Physical Properties of Synthesized (Nickel-Zinc-Gallium) Ferrites Doped with Rare-Earth Elements"

#### **Supervisors Committee:**

Signature

1- Prof.Dr. Karimat El-Sayed

Professor of Solid state physics, Physics Department, Faculty of science, Ain Shams University

2- Prof.Dr. Samy Shaaban Ata-Allah

Professor of Solid State physics, Chairman of Egyptian

Nuclear and Radiological Regulatory Authority

3- Prof.Dr. Ali Abed El-Rahman Ahmed Abou Shama

Professor of Solid state physics, Physics Department,

Faculty of science, Ain Shams University

4- Dr. Mohamed Baker Mahmoud

Assistant Professor of Solid State physics, Physics Department Faculty of science, Ain Shams University

Date of research: / / 2017

Postgraduate Studies Department

Approval Stamp Approval Date
/ / 2017 / / 2017

# Acknowledgement

First of all thanks to **ALLAH** who gave us knowledge and blessings, and prayer and peace be upon **Mohammed** the messenger of **ALLAH**.

I would like to express my deepest thanks and gratitude to *Prof. Dr. K. M. El- sayed* Professor of Solid State physics, Physics Department Faculty of science, Ain Shams University for her continuous help, and also for her stimulating advices and support to go ahead with my thesis, and for her care, kindness and scientific comments, and encouragement and supervision of this work.

I owe my deepest gratitude to my supervisor *Prof. Dr. S. S. Ata-Allah*, Chairman of Nuclear and Radiation Regulatory Authority of Egypt for his support guidance and for giving me the opportunity to perform this research in Nuclear Solid State

Group, I also thank him for his constant interest in the progress of this work., and for his continuous help, for his continuous encouragement.

I am grateful to *Prof.Dr. Ali Abed El-Rahman Ahmed Abou Shama*, Professor of Solid physics, Physics Department Faculty of science, Ain Shams University for his continuous help for her friendly guidance, support and continuous help and encouragement during this work.

It is a pleasure to acknowledge to *Dr. Mohamed Bakr Mohamed*, Assistant Professor of Solid physics, Physics Department, Faculty of science, Ain Shams University for valuable suggestions, encouragement and fruitful advice through this work, and continuous help in research.

I am grateful to *Dr. Salwa Mohamed Ismail*, Assistant Professor of Solid physics, Reactor Physics Department, Nuclear Research Center, Egyptian Atomic Energy Authority for her continuous help and encouragement during this work. For her friendly guidance, support and continuous help in writing this thesis.

I am grateful to *Dr. Adel Hashhash*, Assistant Professor of Solid physics, Reactor Physics Department, Nuclear Research Center, Egyptian Atomic Energy Authority for his continuous help, for his continuous encouragement and continuous help in writing this thesis.

I would like to express my deep thanks to *Prof.Dr. M. K. Fayek, Dr. M. Yehia, Dr. Hassan Elshemy , Dr NancyNigibe and Dr. Sh. Labib* for their usefule discussion, comments , and continuous encouragement.

Special thanks for my family: **Father, Mother, brother and sister** for their patience, understanding, continuous assistance, encouragement and support.

# **CONTENTS**

|  | Page |
|--|------|
|  | No   |
| Aim of work  |      |
| Abstract   |      |
| Summary  |      |
| Chapter I: Introduction and Literature<br>Review                         | 1    |
| 1.1. Nano crystalline ferrites   | 1    |
| 1.2. Some applications of the nanocrystalline Ferrites                   | 1    |
| 1.3. Literature Survey   | 3    |
| Chapter II: Structural, microstructural analysis and magnetic properties | 10   |
| 2.1. Introduction to X-ray diffraction                                   | 10   |
| 2.1.1 Profile analysis   | 10   |
| 2.1.2 Diffraction line parameters  | 10   |
| 2.1.3 Profile shape function   | 12   |
| 2.1.4 Instrumental broadening correction                                 | 16   |
| 2.1.5 Modeling of powder diffraction data                                | 16   |
| 2.1.6 Pattern decomposition  | 16   |

| 2.1.7. Pattern deconvelution                             | 17 |
|--|----|
| 2.1.8. The reliability factors (R-factors)               | 20 |
| 2.1.9. Structural Analysis                               | 21 |
| 2.1.10. Microstructural analysis                         | 25 |
| 2.1.11. comparison between neutron and X-ray Diffraction | 28 |
| 2.2 Magnetic properties                                  | 31 |
| 2.2.1. Introduction                                      | 31 |
| 2.2.2. Classification of the magnetic materials.         | 32 |
| 2.2.3. Domain structure and hysteresis loop              | 37 |
| 2.2.4. Magnetic properties of nanomaterials              | 40 |
| Chapter III: Experimental Work                           | 43 |
| 3.1. Method of samples preparation                       | 43 |
| 3.1.1. Solid state Method                                | 43 |
| 3.1.2. Citrate method (CA)                               | 44 |
| 3.1.1. Sol gel method (SG)                               | 45 |
| 3.2. The characterization methods                        | 46 |
| 3.2.1. X-ray powder diffraction (XRD)                    | 46 |
| 3.2.2. Neutron Diffraction                               | 47 |
| 3.2.3. Fourier transform infrared spectroscopy (FTIR)    | 53 |
| 3.2.4. Transmission electron microscope (TEM)            | 55 |

| 3.2.5. Vibrating Sample Magnetometer (VSM)  | 56  |
|---|-----|
| 3.2.6. Mössbauer Effect spectroscopy  | 58  |
| 3.2.6.1. Introduction   | 58  |
| 3.2.6.2 Mossbauer effect parameters   | 60  |
| 3.2.6.3. Description of Mössbauer effect Spectrometer                                 | 63  |
| 3.2.6.4. Calibration of the Mössbauer effect Spectrometer                             | 70  |
| 3.2.7. Electrical properties of Ferrites  | 73  |
| 3.2.7.1. Introduction   | 73  |
| 3.2.7.2. Mechanisms of the electrical conduction in transition metal oxides           | 74  |
| 3.2.7.3. Dielectric Properties  | 76  |
| 3.2.7.4. Electrical measurements  | 84  |
| Chapter IV: characterization of NiFe <sub>2</sub> O <sub>4</sub>                      | 89  |
| 4.1. Structural and micro-structural analysis   | 89  |
| 4.2. Cation distributions determination   | 94  |
| I) Mössbauer spectra analysis   | 94  |
| II) Bertaut method  | 99  |
| 4.3. Magnetic Properties  | 104 |
| Chapter V: Part I:  | 108 |
| 5.1.1. Structural and micro-structural analysis of Ga substituted nickel Zinc ferrite | 108 |

| 5.1.2. FT-IR spectroscopy  | 111 |
|--|-----|
| 5.1.3. Mössbauer spectra analysis  | 111 |
| 5.1.4. Magnetic Properties   | 114 |
| 5.1.5. Neutron diffraction analysis  | 115 |
| Part II:   |     |
| 5.2.1. Structural and micro-structural analysis of substituted Nickel Gadolinium Gallium Ferrite | 119 |
| 5.2.2. FT-IR spectroscopy  | 124 |
| 5.2.3. Mössbauer spectra analysis  | 128 |
| 5.2.4. Magnetic Properties   | 133 |
| 5.2.5. Electrical properties   | 137 |
| General conclusion   | 145 |
| References   | 147 |
| Arabic summary   |     |

# LIST OF FIGURES

|            |   | Page<br>No. |
|------------|---|-------------|
| Fig.( 2.1) | X-ray powder diffraction and for NiFe <sub>2</sub> O <sub>4</sub> sample.   | 11          |
| Fig.(2.2)  | The shape of profile parameters.  | 11          |
| Fig.(2.3)  | The Gaussian profile function.  | 13          |
| Fig.(2.4)  | The Lorentzian profile function.  | 14          |
| Fig.(2.5)  | The Person VII profile function plotted for different values of m; m=1 approximately Lorentzian and m=10 approximately Gaussian.  | 15          |
| Fig.(2.6)  | A diagram illustrating the process of extracting the sample broadening from the broadening of the profiles $h(s)$ and $g(s)$ .  | 18          |
| Fig.(2.7)  | Schematic representation of neutron versus x-ray scattering of various nuclei.  | 30          |
| Fig.( 2.8) | Form-factor of Cr [57]. On the Å length scale of the thermal neutron wavelength, the nucleus is point-like, therefore, nuclear scattering is independent of the scattering angle. For x-rays and magnetic neutron scattering, the form factor falls off with increasing scattering angle. | 30          |
| Fig.(2.9)  | Configuration of magnetic dipole moment with and without applying external magnetic field for (a) diamagnetic material and (b) paramagnetic material.   | 34          |
| Fig.(2.10) | (a) The alignment of atomic dipole moment in the absence of applying an external magnetic field and (b) Temperature dependence of magnetic susceptibility for a ferromagnetic material.   | 35          |

| Fig.(2.11) | (a) antiparallel alignment of spin magnetic moments, (b) Temperature dependence of magnetic susceptibility of antiferromagnetic Material.  |    |  |
|------------|--|----|--|
| Fig.(2.12) | (a) configuration of the spin magnetic moment for $Fe^{3+}$ and $Fe^{2+}$ ions in $Fe_3O_4$ . (b) Temperature dependence of magnetic susceptibility of ferrimagnetic material.   | 37 |  |
| Fig.(2.13) | Graphic represents domains in a ferromagnetic or ferrimagnetic material; arrows represent atomic magnetic dipoles. Inside each domain all dipoles are alignment, where note that; the direction of alignment changes from one domain to another. | 38 |  |
| Fig.(2.14) | The B-versus-H behavior and Domain configurations for magnetic samples.  | 39 |  |
| Fig.(2.15) | The hysteresis loop, Magnetic flux versus the appalling magnetic field strength for a ferromagnetic material.  | 39 |  |
| Fig.(2.16) | Overview of the size dependence of coercivity presented by magnetic particles.   | 41 |  |
| Fig.(3.1)  | Citrate method of (a) reactant mixture (b) dark brown powder.  | 45 |  |
| Fig.(3.2)  | Light brown powder of Sol gel method.  | 45 |  |
| Fig.( 3.3) | X-ray path in a Bragg-Brentano diffractometer  | 46 |  |
| Fig.(3.4)  | Schematic of x-ray diffractometer  | 47 |  |
| Fig.( 3.5) | Schematic view of neutron diffraction instrument.  | 48 |  |
| Fig.( 3.6) | IBR-2 reactor.   | 49 |  |
| Fig.( 3.7) | The layout of the high-resolution Fourier diffractometer (HRFD) at the IBR-2 pulsed reactor.   | 52 |  |
| Fig.( 3.8) | Shimadzu ,FTIR-8400S.  | 53 |  |
| Fig.( 3.9) | TEM diagram .  | 55 |  |

| Fig.( 3.10) | Schematic represent Vibrating sample magnetometer (VSM)   | 56 |
|-------------|---|----|
| Fig.( 3.11) | Vibrating sample magnetometer (Lake Shore -7400) used in measurement of the magnetic properties of samples.   | 57 |
| Fig.( 3.12) | Nuclear decay schem for <sup>57</sup> Co  | 58 |
| Fig.(3.13)  | Nuclear energy levels and isomer shift.   | 61 |
| Fig.(3.14)  | Isomer shift and Quadrupole splitting.  | 62 |
| Fig.(3.15)  | The magnetic hyperfine splitting, combined magnetic and quadrupole interaction.   | 62 |
| Fig.(3.16)  | Mössbauer effect spectrometer   | 66 |
| Fig.( 3.17) | The wave forms relative to the incoming bistable signal; a)- The high square waveform created by $BOR$ +generator integrated by the $6\ Hz$ generator b)- The velocity waveform. c)- The drive waveform | 67 |
| Fig.(3.18)  | a) $\gamma$ -ray spectrum of the used $^{57}\text{Co}$ source in the PHA mode of PCA-II analyzer .  | 69 |
| Fig.(3.19)  | Measured ME spectra for: a) Metallic iron. b) $\alpha$ -Fe $_2$ O $_3$ c)Stainless Steel  | 71 |
| Fig.(3.20)  | The polaron is aquasi-particale consists of an electron together with the accompanying self-consistent polarization field.  | 76 |
| Fig.(3.21)  | Frequency dependence of (a) total polarizability and (b) power loss   | 83 |
| Fig.(3.22)  | Geometrical representation of the complex permittivity and its components   | 83 |
| Fig.(3.23)  | Block diagram of the adaptive technique used for ac and dc electrical measurements  | 87 |