



# **OPTIMIZATION OF SLUDGE THICKENING**

A Thesis

Submitted to the Faculty of Engineering  
Ain Shams University for the Fulfillment  
of the Requirement of PhD. Degree  
in Civil Engineering

by

**Eng. FATMA MAHMOUD ABD EL-SHAFI**

B.Sc. in Civil Engineering, June 1999  
Faculty of Engineering, Ain Shams University  
M.Sc. in Civil Engineering, December 2004  
Faculty of Engineering, Ain Shams University

**Supervisors**

**Prof. Dr. MOHAMED EL HOSSIENY EL NADI.**

Professor of Sanitary & Environmental Engineering  
Faculty of Engineering,  
Ain Shams University, Cairo, EGYPT

**Dr. MOHAMED ALY AHMED FERGALA.**

Associate Professor of Sanitary & Environmental Engineering  
Faculty of Engineering,  
Ain Shams University, Cairo, EGYPT

2017



# **OPTIMIZATION OF SLUDGE THICKENING**

A Thesis For  
**The PhD Degree In Civil Engineering**  
( **SANITARY ENGINEERING** )

by

**FATMA MAHMOUD ABD EL-SHAFI**

B.Sc. in Civil Engineering, June 1999

Faculty of Engineering, Ain Shams University

M.Sc. in Civil Engineering, December 2004

Faculty of Engineering, Ain Shams University

## **THESIS APPROVAL**

### **EXAMINERS COMMITTEE**

### **SIGNATURE**

**Prof. Dr. Hamdy Ibrahim Aly**

Prof. of Sanitary Engineering  
Ain Shams University, Cairo, Egypt.

-----

**Prof. Dr. Emad Hamdy Hassan**

Prof. of Water Engineering  
American University In Cairo, Egypt.

-----

**Prof. Dr. Moh. El Hossieny El Nadi**

Prof. of Sanitary & Environmental Engineering  
Ain Shams University, Cairo, Egypt.

-----

**Dr. Moh. Aly Ahmed Fergala**

Associate Prof. of Sanitary & Environmental Engineering  
Ain Shams University, Cairo, Egypt.

-----

Date:- ---/--/2017

# **DEDICATION**

This work takes a period from my life. I wish to dedicate it to whom suffered to educate, prepare, build capacity and help my self to be as I am,

## **TO MY FATHER SOUL**

I wish to dedicate it also to whom ease my life and share in carrying the responsibility to help me

## **TO MY MOTHER**

At the last, I wish to dedicate this work.

## **TO MY BROTHER AND MY SISTER**

## STATEMENT

This dissertation is submitted to Ain Shams University, Faculty of Engineering for the degree of PhD. in Civil Engineering.

The work included in this thesis was carried out by the author in the department of Public Works, Faculty of Engineering, Ain Shams University, from January 2012 to June 2017.

No part of the thesis has been submitted for a degree or a qualification at any other University or Institution.

Date:-            ---/--/2017

Signature:-      -----

Name:- *FATMA MAHMOUD ABD EL-SHAFI*

## ***ACKNOWLEDGMENT***

*The author wish deeply to express his gratitude to **Dr. Mohamed El Hossieny Abdel Rahman El Nadi**, Professor of Sanitary & Environmental Engineering, Faculty of Engineering, Ain Shams University, for patient guidance, helpful suggestions, great supporting, cooperation and help in thesis and laboratory work.*

*Also, great thanks to **Dr. Mohamed A. A. Fergala**, Associate Professor of Sanitary Engineering, Faculty of Engineering, Ain Shams University, for his help, encourage and cooperation during the preparation of this study*

*The author wish to the staff and personnel of Zenein WWTP, and, also special thanks for Chemist Ahmed in The Central Hlioplice Laboratory for facilities, and cooperation during the preparation of this study*

*Also, sincere thanks to the staff and personnel of Sanitary Engineering Section, Faculty of Engineering, Ain Shams University, for facilities, encouragement and cooperation during the preparation of this study*

## **ABSTRACT**

**Name :- FATMA MAHMOUD ABD EL-SHAFi Emam**

**Title :- “ Optimization Of Sludge Thickening”**

**Faculty : Faculty of Engineering, Ain Shams University**

**Specialty : Civil Eng., Irrigation and Hydraulic Department**

**Summary :**

Gravity thickeners are most commonly used in wastewater treatment plants in Egypt. Gravity thickeners are designed so as sedimentation happens due to physical reactions only, but what actually happens is that due to other incomprehensible reactions the sedimentation efficiency is affected. These incomprehensible reactions are the subject of this thesis. This research contains: **Firstly**, Data collecting for available information on the parameters affecting the gravity thickener and the troubles affecting the performance of the gravity thickeners. In addition to visiting some wastewater treatment plants in Egypt for investigations and data collections. **Secondary**, the experimental works have two stages batch-scale lab experiments to determine the best mixture ratio between primary & secondary sludge for thickener and also to determine the retention time to give maximum thickening efficiency, field-scale pilot unit experiments to determine the simulation model for the thickener behavior. **Finally**, discussing both experimental works results and producing the simulation model and its verification. It was concluded from this research as the following:

1. Based on the bench-scale lab experiments the best mixed ratio between primary sludge (PS) and waste activated sludge (WAS) with the gravity thickener is found (40 % PS+ 60 % WAS).
2. From the bench-scale lab experiments, the big effect of biological action was presentable after 16 hrs.
3. The study proved that hydrolysis phase by anaerobic action can be happened from start settling by gravity thickener depends on the sludge characteristics and sludge age.
4. Based on field pilot experiments, the maximum efficiency of gravity thickener for primary sludge is highest than efficiency of mixed sludge (40%PS + 60% WAS) and then efficiency of waste activated sludge with retention time 16 hr.
5. The study model produced a simulation model for the gravity thickener. It was found that the gravity thickener works by three equations depending on retention times and sludge types, thickening efficiency .

**Supervisors:**

**Prof. Dr. MOHAMED EL HOSSIENY EL NADI,**

**Dr. MOHAMED ALY FERGALA**

**KEYWORDS**

***Wastewater Treatment, Sludge Treatment, Sludge thickening.***

## TABLE OF CONTENTS

<b>TITLE</b>	<b>Page</b>
COVER	i
THESIS APPROVAL	ii
DEDICATION	iii
STATEMENT	iv
ACKNOWLEDGEMENT	v
ABSTRACT	vi
TABLE OF CONTENTS	vii
LIST OF FIGURES	xi
LIST OF TABLES	xv
<b><u>CHAPTER (I) INTRODUCTION</u></b>	<b>1-3</b>
1.1. GENERAL	1
1.2. STUDY OBJECTIVE	2
1.3. SCOPE OF WORK	2
1.3.1. THEORETICAL PART	2
1.3.1.1. BEFORE EXPERIMENTAL WORKS	2
1.3.1.2. AFTER EXPERIMENTAL WORKS	2
1.3.2. EXPERIMENTAL PART	3
1.3.2.1. LABORATORY EXPERIMENTAL BY USING BATCH SCALE	3
1.3.2.2. FIELD EXPERIMENTAL BY USING PILOT UNITS	3
1.4. THESIS ORGANIZATION	3
<b><u>CHAPTER (II) LITERATURE REVIEW</u></b>	<b>4-35</b>
2.1. INTRODUCTION	4
2.2. SOURCES & CHARACTERISTICS OF SLUDGE	4
2.2.1. PRIMARY SLUDGE	5
2.2.2. BIOLOGICAL SLUDGE	9
2.2.3. MIXED SLUDGE	13
2.3. SLUDGE TREATMENT	14
2.3.1. THICKENING (CONCENTRATION)	14
2.3.1.1. THICKENING DEFINITION	14
2.3.1.2. HOW A CONTINUOUS THICKENER WORKS	17
2.3.1.3. THICKENER OPERATIONAL	18

	DYNAMIC	
2.3.1.4.	APPLICABILITY.	19
2.3.1.5.	ADVANTAGE AND DISADVANTAGE OF GRAVITY THICKENER	19
2.3.1.6.	DESIGN CRITERIA	20
2.3.1.6.1.	MINIMUM SURFACE AREA	20
2.3.1.6.2.	HYDRAULIC LOADING RATE	21
2.3.1.6.3.	THICKENER DEPTH	21
2.3.1.6.4.	DRIVE TORQUE REQUIREMENTS	22
2.3.1.6.5.	FLOOR SLOPE	23
2.3.1.6.6.	RETENTION TIME	23
2.3.1.6.7.	OTHER CONSIDRATIONS	23
2.3.1.7.	FACTORS AFFECTING GRAVITY THICKENING PERFORMANCE	25
2.3.1.8.	TROUBLESHOOTING GUIDE FOR GRAVITY THICKENERS	26
2.4.	PROBLEMS RELATED TO DESIGN & OPERATION OF THE THICKENER IN EGYPT	30
<b>CHAPTER (III) MATERIAL AND METHODS</b>		<b>36-51</b>
3.1.	THE EXPERIMENTAL WORK PLAN	36
3.2.	LABORATORY EXPERIMENTS	37
3.2.1.	LABORATORY APPARATUS	37
3.2.2.	SAMPLING	39
3.2.3.	EXPERUMENTAL TECHNIQUE	39
3.2.3.1.	SCHEDULE OF OPERATION	39
3.2.3.2.	MEASURED PARAMETERS	40
3.3.	FIELD EXPERIMENTS	41
3.3.1.	SAMPLING	41
3.3.2.	PILOT PLANT COMPONENTS & ERECTION	42
3.3.2.1	PILOT PLANT COMPONENTS	42
3.3.3.	EXPERUMENTAL TECHNIQUE	44
3.3.3.1.	OPERATION SYSTEM	44
3.3.3.2.	THE MEASURED PARAMETERS	45
3.4.	ANALYTICAL MEASUREMENTS	45
3.4.1.	TOTAL SUSPENDED SOLIDS, VOLATILE MATTER	46
3.4.1.1.	APPARATUS	46
3.4.1.2.	PROCEDURE	46
3.4.2.	CHEMICAL OXYGEN DEMAND	49

3.4.3.	BIOCHEMICAL OXYGEN DEMAND	50
<b><u>CHAPTER (IV) RESULTS</u></b>		<b>52-82</b>
4.1.	GENERAL	52
4.1.1.	LAB EXPERIMENTS	52
4.1.2.	FIELD EXPERIMENTS	52
4.2.	LAB EXPERIMENTS	52
4.2.1.	EXPERIMENTS WITH SLUDGE FROM EL- BERKAH WWTP	53
4.2.2.	EXPERIMENTS WITH SLUDGE FROM ZENEIN WWTP	61
4.2.3.	EXPERIMENTS WITH SLUDGE FROM EL-GABAL AL-ASFAR (CONTRACT (16)) WWTP	69
4.3.	FIELD EXPERIMENTS	77
4.3.1.	EXPERIMENTS WITH DIFFERENT RETENTION TIME FOR DIFFERENT SLUDGE	77
4.3.1.1.	RELATION BETWEEN TSS & DIFFERENT RETENTION TIME FOR DIFFERERNT SLUDGE	77
<b><u>CHAPTER (V) MODELING</u></b>		<b>83-112</b>
5.1.	GENERAL	83
5.2.	PRODUCING MODEL	84
5.2.1.	FOR PRIMARY SLUDGE	88
5.2.2.	FOR WASTE ACTIVATED SLUDGE	90
5.2.3.	FOR MIXED SLUDGE (40%PS+60%WAS)	93
5.3.	MODEL MODIFICATIONS	96
5.3.1.	FOR PRIMARY SLUDGE	97
5.3.2.	FOR WASTE ACTIVATED SLUDGE	100
5.3.3.	FOR MIXED SLUDGE (40%PS+60%WAS)	103
5.4.	MODEL CHECK	106
5.4.1.	FOR PRIMARY SLUDGE	107
5.4.2.	FOR WASTE ACTIVATED SLUDGE	109
5.4.3.	FOR MIXED SLUDGE (40%PS+60%WAS)	110

<b><u>CHAPTER (VI) DISCUSSION</u></b>	<b>114-122</b>
6.1. GENERAL	114
6.2. LAB RESULTS DISCUSSION	114
6.2.1. EXPERIMENTS WITH DIFFERENT SLUDGE FROM THREE DIFFERENT WASTE WATER TREATMENT PLANTS	114
6.2.1.1. EXPERIMENTS WITH SLUDGE FROM BOTH OF ELBERKAH WASTEWATER TREATMENT PLANT AND EL GABAL ASFAR CONTRACT (16) WASTE WATER TREATMENT PLANT	115
6.2.1.2. EXPERIMENTS WITH SLUDGE FROM ZENEIN FOR DIFFERENT WASTE WATER TREATMENT PLANT	117
6.3. FIELD RESULTS DISCUSSION	120
6.4. MODEL RESULTS DISCUSSION	121
<b><u>CHAPTER (VII) CONCLUSION</u></b>	<b>124-128</b>
7.1. GENERAL	125
7.2. CONCLUSION	125
7.3. RECOMMENDATION	128
7.4. FURTHER WORKS	128
<b><u>REFERENCES</u></b>	<b>130-132</b>
<b><u>ARABIC SUMMARY</u></b>	

## LIST OF FIGURES

<b>FIGURES</b>	<b>Page</b>
<b><u>CHAPTER (II) LITERATURE REVIEW</u></b>	
Relation Between Overflow Rate And Percent Removal of BOD & Suspended Solids.	8
Fig. (2/1)	
Thickening and Sludge Volume Change.	14
Fig. (2/2)	
Cross Section of The Circular Gravity Thickener.	16
Fig. (2/3)	
Settling Regimes Depend Up on Closeness of Particles To Each Other.	17
Fig. (2/4)	
The Volume Dynamics & Solid Dynamics At Thickener.	18
Fig. (2/5)	
Show the separate steps in El- Gabal Al. Asfar WWTP Contract (19) .	31
Fig. (2/6)	
Show the layout site of El- Gabal Al. Asfar WWTP	32
Fig. (2/7)	
Show the sludge line in El- Gabal Al. Asfar WWTP	32
Fig. (2/8)	
Sludge Thickeners Status	35
Fig. (2/9)	
Sludge Thickeners Status	35
Fig. (2/10)	
<b><u>CHAPTER (III) MATERIAL AND METHODS</u></b>	
The Lab Batch Thickening System.	38
Fig. (3/1)	
The Lab Batch Component System .	38
Fig. (3/2)	
Location of Zenein WWTP.	41
Fig. (3/3)	
Zenein WWTP Components.	42
Fig. (3/4)	
Photo 1 Of The Used Pilot Plant In Zanein WWTP.	43
Fig. (3/5)	
Photo 2 Of The Used Pilot Plant In Zanein WWTP.	43
Fig. (3/6)	
Plan of The Used Pilot Plant In Zanein WWTP Component.	44
Fig. (3/7)	
Muffle Furnace And Drying Oven In Lab.	47
Fig. (3/8)	
The sensitive Balance In Lab.	48
Fig. (3/9)	
Main Components Of Sludge Solids.	48
Fig. (3/10)	
Equipment for COD Determination In Lab.	49
Fig. (3/11)	
Equipment for BOD <sub>5</sub> Determination In Lab.	51
Fig. (3/12)	

## **CHAPTER (IV) RESULTS**

	Relation Between BOD <sub>5</sub> & Time For	57
Fig. (4/1)	Primary Sludge ,Waste activated sludge & mixed sludge From El- Berkah WWTP .	
	Relation Between COD & Time For	58
Fig. (4/2)	Primary Sludge ,Waste activated sludge & mixed sludge From El- Berkah WWTP .	
	Relation Between TSS & Time For	59
Fig. (4/3)	Primary Sludge ,Waste activated sludge & mixed sludge From El- Berkah WWTP .	
	Relation Between VSS & Time For	60
Fig. (4/4)	Primary Sludge ,Waste activated sludge & mixed sludge From El- Berkah WWTP .	
	Relation Between BOD <sub>5</sub> & Time For	65
Fig. (4/5)	Primary Sludge ,Waste activated sludge & mixed sludge From Zenein WWTP .	
	Relation Between COD & Time For	66
Fig. (4/6)	Primary Sludge ,Waste activated sludge & mixed sludge From Zenein WWTP .	
	Relation Between TSS & Time For	67
Fig. (4/7)	Primary Sludge ,Waste activated sludge & mixed sludge From Zenein WWTP .	
	Relation Between VSS & Time For	68
Fig. (4/8)	Primary Sludge ,Waste activated sludge & mixed sludge From Zenein WWTP .	
	Relation Between BOD <sub>5</sub> & Time For	73
Fig. (4/9)	Primary Sludge ,Waste activated sludge & mixed sludge From El-Gabal Al.Asafar (contract (16)) WWTP.	
	Relation Between COD & Time For	74
Fig. (4/10)	Primary Sludge ,Waste activated sludge & mixed sludge From El-Gabal Al.Asafar (contract (16)) WWTP.	
	Relation Between TSS & Time For	75
Fig. (4/11)	Primary Sludge ,Waste activated sludge & mixed sludge From El-Gabal Al.Asafar (contract (16)) WWTP.	
Fig. (4/12)	Relation Between VSS & Time For	76

	Primary Sludge ,Waste activated sludge & mixed sludge From El-Gabal Al.Asafar (contract (16)) WWTP.	
Fig (4/13)	Relation Between Different TSS at different retention time for Primary sludge.	77
Fig (4/14)	Relation Between Different TSS at different retention time for Waste Activated sludge .	78
Fig (4/15)	Relation Between Different TSS at different retention time for Mixed sludge (40% ps + 60 % was) .	79
Fig (4/16)	Relation Between TSS thickened and Efficiency at different retention time for different sludge.	80
 <b><u>CHAPTER (V) MODELING</u></b>		
Fig. (5/1)	Mass balance on the Solids in the gravity thickener.	85
Fig. (5/2)	Flow diagram for producing model of thickening.	86
Fig. (5/3)	relation between efficiency for primary sludge and retention time during field experimental time.	88
Fig (5/4)	relation between efficiency for waste activated sludge and retention time during field experimental time.	91
Fig (5/5)	relation between efficiency for Mixed sludge (40 % ps + 60 % was) and retention time during field experimental time.	94
Fig (5/6)	relation between efficiency for primary sludge and divided retention time.	98
Fig (5/7)	Shows relation between efficiency for waste activated sludge and divided retention time.	101
Fig (5/8)	relation between efficiency for Mixed sludge (40%ps+60%was) and divided retention time.	104

## LIST OF TABLES

<b>TABLES</b>	<b>Page</b>
<b><u>CHAPTER (II) LITERATURE REVIEW</u></b>	
Table (2/1) Primary Sludge Characteristics.	6
Table (2/2) Activated Sludge Characteristics.	12
Table (2/3) Thickening Methods In Sludge Processing.	15
Table (2/4) Advantages and Disadvantages of gravity thickener.	19
Table (2/5) Design Criteria For Gravity Thickeners.	20
Table (2/6) Typical uniform load (W) values.	23
Table (2/7) Factors Affecting Gravity Thickening Performance.	25
Table (2/8) Solids Overflow in Peripheral Launder.	26
Table (2/9) Solids Overflow in Peripheral Launder.	27
Table (2/10) Rapidly Rising Bed Level.	27
Table (2/11) Thickener Underflow Density Too Low.	28
Table (2/12) Thickener Underflow Density Too High.	29
Table (2/13) Summarizes the technical data available for the existing units.	34
<b><u>CHAPTER (III) MATERIALS AND METHODS</u></b>	
Table (3/1) Schedule Of Experimental Work Of The Study.	37
<b><u>CHAPTER (IV) RESULTS</u></b>	
Table (4/1) The BOD <sub>5</sub> Characteristics of Different Sludge From El-Berkah WWTP .	53
Table (4/2) The COD Characteristics of Different Sludge From El-Berkah WWTP .	54
Table (4/3) TSS Characteristics of Different Sludge From El-Berkah WWTP .	55
Table (4/4) VSS Characteristics of Different Sludge From El-Berkah WWTP .	56
Table (4/5) The BOD <sub>5</sub> Characteristics of Different Sludge From Zenein WWTP .	61
Table (4/6) The COD Characteristics of Different	62

	Sludge From Zenein WWTP .	
Table (4/7)	TSS Characteristics of Different Sludge From Zenein WWTP .	63
Table (4/8)	VSS Characteristics of Different Sludge From Zenein WWTP .	64
Table (4/9)	The BOD <sub>5</sub> Characteristics of Different Sludge From El-Gabal Al-Asfar (contract (16)) WWTP.	69
Table (4/10)	The COD Characteristics of Different Sludge From El-Gabal Al-Asfar (contract (16)) WWTP .	70
Table (4/11)	TSS Characteristics of Different Sludge From El-Gabal Al-Asfar (contract (16)) WWTP .	71
Table (4/12)	VSS Characteristics of Different Sludge From El-Gabal Al-Asfar (contract (16)) WWTP .	72
Table (4/13)	TSS at different retention time for Primary sludge .	80
Table (4/14)	TSS at different retention time for Waste Activated sludge.	81
Table (4/15)	TSS at different retention time for Mixed sludge (40 % Ps + 60 % Was).	81
Table (4/16)	TSS thickened & Efficiency results for different sludge at different retention time.	82

#### **CHAPTER (V) MODELING**

Table (5/1)	$E_{\text{Measured}}$ % and $E_{\text{Calculated}}$ % for Primary sludge .	89
Table (5/2)	$E_{\text{Measured}}$ % and $E_{\text{Calculated}}$ % for Waste Activated sludge .	92
Table (5/3)	$E_{\text{Measured}}$ % and $E_{\text{Calculated}}$ % for mixed sludge .	95
Table (5/4)	$E_{\text{Measured}}$ % and $E_{\text{Calculated}}$ % for Primary sludge .	99
Table (5/5)	$E_{\text{Measured}}$ % and $E_{\text{Calculated}}$ % for Waste Activated sludge.	102
Table (5/6)	$E_{\text{Measured}}$ % and $E_{\text{Calculated}}$ % for mixing sludge .	105
Table (5/7)	TSS thickened measured at different retention time for Primary sludge .	107