



# BEHAVIOR OF COLD-FORMED STEEL IN MOMENT RESISTING FRAMES

By

Emad Mohammed Shafik Hassan

A Thesis Submitted to the  
Faculty of Engineering, Cairo University  
In Partial Fulfillment of the  
Requirement for the Degree of  
**MASTER OF SCIENCE**  
In  
STRUCTURAL ENGINEERING

FACULTY OF ENGINEERING, CAIRO UNIVERSITY  
GIZA, EGYPT  
**2015**

BEHAVIOR OF COLD-FORMED STEEL IN MOMENT  
RESISTING FRAMES

By  
Emad Mohammed Shafik Hassan

A Thesis Submitted to the  
Faculty of Engineering at Cairo University  
in Partial Fulfillment of the  
Requirements for the Degree of  
**MASTER OF SCIENCE**  
In  
STRUCTURAL ENGINEERING

Under the Supervision of

Prof. Dr. Sherif A. Mourad

Assoc. Prof. Dr. Mohamed Hassanien

.....  
Professor of Steel Structure and Bridges  
Structural Department  
Faculty of Engineering, Cairo University

.....  
Associate Professor  
Structural Department  
Faculty of Engineering, Cairo University

FACULTY OF ENGINEERING, CAIRO UNIVERSITY  
GIZA, EGYPT  
**2015**

# BEHAVIOR OF COLD-FORMED STEEL IN MOMENT RESISTING FRAMES

By

Emad Mohammed Shafik Hassan

A Thesis Submitted to the  
Faculty of Engineering at Cairo University  
in Partial Fulfillment of the  
Requirements for the Degree of  
**MASTER OF SCIENCE**  
in  
STRUCTURAL ENGINEERING

Approved by the Examining Committee:

**Prof. Dr. Sherif A. Mourad**, (Thesis main advisor)

**Assoc. Prof. Dr. Mohamed Hassanien Serror**, (Member)

**Prof. Dr. Metwally Abo-Hamad**, (Internal examiner)

**Prof. Dr. Abdel Rahim K. Dessuoki**, (External examiner)  
Prof. of structural Engineering, Ain Shams University

FACULTY OF ENGINEERING, CAIRO UNIVERSITY  
GIZA, EGYPT  
**2015**

**Engineer's Name:** Emad Mohamed Shafik Hassan  
**Date of Birth:** 01/06/1989  
**Nationality:** Egyptian  
**E-mail:** EngEmadShafik@yahoo.com  
**Phone:** 01140504740  
**Address:** 2 Mahmoud Mohran st, El-Basateen, Cairo  
**Registration Date:** 01/10/2012  
**Awarding Date:** / /  
**Degree:** Master of Science  
**Department:** Structure Engineering



**Supervisors:**

Prof. Sherif Mourad  
Assoc. Prof. Mohamed Hassainen

**Examiners:**

|                                |                       |
|--------------------------------|-----------------------|
| Prof. Sherif A. Mourad         | (Thesis main advisor) |
| Assoc. Prof. Mohamed Hassainen | (Member)              |
| Prof. Metwally Abo-Hamad       | (Internal examiner)   |
| Prof. Abdel Rehim K. Dessuoki  | (External examiner)   |

**Title of Thesis:**

BEHAVIOR OF COLD-FORMED STEEL IN MOMENT RESISTING FRAMES

**Key Words:**

Cold-formed steel; Moment frame; Cyclic behavior; Monotonic behavior.

**Summary:**

The thesis presents an analytical and experimental investigation of the cold-formed steel in moment resisting frames. Three dimensional non-linear finite element analyses have been performed for cold-formed steel beam-to-column connections under both monotonic and cyclic loading. Furthermore, experimental investigation has been conducted for full-scale models to test the real behavior of the connection in question under both monotonic and cyclic loading conditions. Several parameters have been examined: profiles of cold-formed C-sections, profile slenderness, vertical stiffener configurations, and horizontal stiffener configurations. The energy dissipation through both element and connection hysteretic behaviors has been also reported analytically and experimentally.

## Acknowledgments

The author is honored to obtain his M.Sc. degree from Cairo University under distinguished supervisors. He is deeply indebted to **Prof. Sherif Mourad** for his support, guidance, encouragement and valuable discussion. He also grateful for **Assoc. Prof. Mohamed Hassaïen** for his encouragement, guidance, valuable discussion, review this work, and his great effort to accomplish the thesis objectives.

The author would like to thanks **Prof. Hadadd Said** and Assoc. **Prof. Yehia**, directors of the concrete laboratory, Housing & Building National Research Center for their effort for allowing me to utilize the laboratory facilities. In addition, the author thanks **Prof. Hussam Hodhod** for performing the tensile test for steel specimens.

The financial fund for the experimental work was mainly provided from Cairo University with the support of **Prof. Sherif Mourad** and **Assoc. Prof. Mohamed Hassainen**. While the other part of the financial support was provided from Civil Engineering Center, Faculty of Engineering, Cairo University and its director **Prof. Hatem Mostafa**.

Finally, the author would like to thank his mother, father and wife for their continuous support. The author would not have achieved this work without their help.

# Table of Contents

|  |       |
|--|-------|
| Acknowledgments .....                            | i     |
| List of Tables .....                             | v     |
| List of Figures.....                             | vi    |
| Abstract.....                                    | xviii |
| CHAPTER 1: Introduction.....                     | 1     |
| 1.1 General .....                                | 1     |
| 1.2 Problem statement.....                       | 1     |
| 1.3 Objective of the research.....               | 1     |
| 1.4 Scope of the research .....                  | 2     |
| 1.5 Organization of the thesis .....             | 2     |
| CHAPTER 2: LITERATURE REVIEW .....               | 4     |
| 2.1 General.....                                 | 4     |
| 2.2 Design Codes .....                           | 4     |
| 2.2.1 Cold-formed steel.....                     | 4     |
| 2.2.2 Beam-to-Column moment connection .....     | 8     |
| 2.2.3 Cyclic Loading.....                        | 10    |
| 2.2.4 Tensile loading test .....                 | 11    |
| 2.3 Research Works .....                         | 12    |
| 2.3.1 Cold-formed steel.....                     | 12    |
| 2.3.2 Cold formed steel connections.....         | 18    |
| CHAPTER 3: Numerical Model and Verification..... | 21    |
| 3.1 General .....                                | 21    |
| 3.2 Numerical model.....                         | 21    |
| 3.3 Modeling Procedure.....                      | 21    |
| 3.3.1 Finite Element Modeling.....               | 21    |
| 3.3.2 Material .....                             | 23    |
| 3.3.3 Model Geometry .....                       | 24    |
| 3.3.4 Loading.....                               | 30    |
| 3.3.5 Evaluation of parameters.....              | 31    |
| 3.4 Numerical model verification .....           | 33    |

|  |     |
|--|-----|
| CHAPTER 4: Experimental model and test setup .....           | 35  |
| 4.1 General .....  | 35  |
| 4.2 Experimental model .....                                 | 35  |
| 4.3 Test specimens. ....                                     | 36  |
| 4.3.1 Monotonic loading specimens.....                       | 37  |
| 4.3.2 Cyclic loading specimens.....                          | 38  |
| 4.4 Construction of specimens .....                          | 39  |
| 4.5 Testing setup .....                                      | 41  |
| 4.6 Instrumentation .....                                    | 46  |
| 4.6.1 Strain gauge (SG).....                                 | 46  |
| 4.6.2 Linear variable displacement transducers (LVDTs) ..... | 48  |
| 4.6.3 Load cell.....   | 50  |
| 4.6.4 Data acquisition system.....                           | 50  |
| 4.7 Loading procedures.....                                  | 52  |
| 4.8 Material prosperities .....                              | 54  |
| 4.9 Processing of test results .....                         | 56  |
| CHAPTER 5: Results and Discussion .....                      | 58  |
| 5.1 General .....  | 58  |
| 5.2 Analytical results and discussion .....                  | 58  |
| 5.2.1 Profile Slenderness .....                              | 58  |
| 5.2.2 Effect of out of plane stiffeners.....                 | 82  |
| 5.2.3 Hysteretic behavior .....                              | 106 |
| 5.3 Experimental result and discussion.....                  | 169 |
| 5.3.1 General .....  | 169 |
| 5.3.2 Monotonic loading test.....                            | 169 |
| 5.3.1 Cyclic loading test.....                               | 211 |
| 5.3.1 Comparison .....                                       | 221 |
| CHAPTER 6: Summary, Conclusions and Recommendations .....    | 223 |
| 6.1 Summary .....  | 223 |
| 6.2 Conclusion .....   | 223 |
| 6.3 Recommendation for future work.....                      | 224 |

|  |     |
|--|-----|
| References .....   | 225 |
| Appendix A: Complete set of numerical analysis output..... | 228 |
| Appendix B: Cyclic Loading Code for ANSYS .....            | 243 |
| Appendix C: Work Shop Drawings.....                        | 253 |

## **List of Tables**

|   |    |
|---|----|
| Table 2-1: Maximum allowable $b/t$ and $C/t$ ratio for compression cold -formed elements.[2]. | 5  |
| Table 2-2: Maximum allowable $d_w/t_w$ ratio for flexural cold -formed elements.[2].          | 5  |
| Table 3-2: Profile parameters for adopted cold-formed beams                                   | 25 |
| Table 3-1: Through plate Profile parameters for adopted cold-formed beams                     | 26 |
| Table 3-3: Profile parameters for stiffened cold-formed beams                                 | 29 |
| Table 4-1: Monotonic loading test specimens   | 38 |
| Table 4-2: Cyclic loading test specimens  | 39 |
| Table 4-3: Mechanical proprieties of steel used   | 54 |

## List of Figures

|   |    |
|---|----|
| Figure 2-1: Definition of b, C and dw. [2].....   | 5  |
| Figure 2-2: CFS channel built up section connectors as per ECP 205 .....  | 6  |
| Figure 2-3: Classification of joint in Euro code-3 part 1-8 [7].....  | 9  |
| Figure 2-4: Cyclic loading according to AISC seismic provision [6] .....  | 11 |
| Figure 2-5: Tensile test specimen dimensions as per ASTM A-370 [9].....   | 11 |
| Figure 3-1: ANSYS 11.0 shell element "shell181" representations [1].....  | 22 |
| Figure 3-2: ANSYS 11.0 rigid beam element MPC184 representations [1] .....  | 22 |
| Figure 3-3: Finite element model and boundary conditions .....  | 23 |
| Figure 3-4: Stress strain curve for employed material.....  | 24 |
| Figure 3-5: Cold-formed steel beam with different profile shapes.....   | 25 |
| Figure 3-6: Through plate dimensions.....   | 26 |
| Figure 3-7: Out of plane stiffeners configuration: (a) CONFIG-0, (b) CONFIG-1, (c)<br>CONFIG-2, (d) CONFIG-3 and (e) COFIG-4.....     | 28 |
| Figure 3-8: Monotonic load substeps.....  | 30 |
| Figure 3-9: Cyclic loading as per AISC seismic provision [6].....   | 31 |
| Figure 3-10: Sketch for bending moment diagram in beam and nominal dimensions .....   | 32 |
| Figure 3-11: Calculation of rotation angle of the beam.....   | 33 |
| Figure 3-12: Finite element model as per Alireza's model for cold-formed steel lipped C-<br>section[18].....                          | 33 |
| Figure 3-13: Compression of nominal moment (M/Mp) against rotation ( $\theta$ ) curve with<br>Alireza [18].....                       | 34 |
| Figure 4-1: General view of specimens .....   | 36 |
| Figure 4-2: Cold-formed steel beam components.....  | 37 |
| Figure 4-3: Specimens assembly using torque wrench.....   | 40 |
| Figure 4-4: The supporting elements for test: (a) supporting frame (b) supporting column ...  | 40 |
| Figure 4-5: Hydraulic jack temporary supports .....   | 41 |
| Figure 4-6: Main dimensions of tested frame .....   | 42 |
| Figure 4-7: The fixation of the supporting column with floor.....   | 43 |
| Figure 4-8: The lateral supporting system and the foam material between the supporting<br>system and the cold-formed steel beam ..... | 44 |
| Figure 4-9: The lateral supporting system .....   | 45 |
| Figure 4-10: The supporting frame view .....  | 46 |
| Figure 4-11: The general view of a stain gauges used in test.....   | 47 |
| Figure 4-12: Typical strain gauges instrumentation in the test specimens .....  | 48 |
| Figure 4-13: General view of LVDT before using .....  | 49 |
| Figure 4-14: Typical LVDT instrumentation in the test specimens .....   | 50 |
| Figure 4-15: Data acquisition system .....  | 51 |
| Figure 4-16: Computer used to monitor the test.....   | 51 |
| Figure 4-17: General view of all instrumentation arrangement.....   | 52 |
| Figure 4-18: Cyclic loading program used in tests .....   | 53 |

|   |    |
|---|----|
| Figure 4-19: Lab view program .....   | 53 |
| Figure 4-20: Tensile test machine.....  | 55 |
| Figure 4-21: Steel coupons after test and failure shape .....   | 55 |
| Figure 4-22: Calculation of energy dissipation coefficient.....   | 57 |
| Figure 5-1: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 150x60x15/t.....                               | 59 |
| Figure 5-2: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 200x85x20/t.....                               | 60 |
| Figure 5-3: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 300x100x20/t.....                              | 60 |
| Figure 5-4: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 400x100x25/t.....                              | 61 |
| Figure 5-5: Normalized moment (M/Mp) against H/t ratio for C-Section .....  | 62 |
| Figure 5-6: Normalized moment (M/Mp) against B/t ratio for C-Section.....   | 63 |
| Figure 5-7: Initial stiffness against plastic capacity (Mp) for C-Section and comparison with EC3 .....                 | 64 |
| Figure 5-8: ductility coefficient ( $\mu$ ) against the plastic moment (Mp) of C-section.....                           | 65 |
| Figure 5-9: ductility coefficient against the slenderness ratio (H/t) of the web of C-section..                         | 65 |
| Figure 5-10: ductility coefficient against the slenderness ratio (B/t) of the flanges of C-section .....                | 66 |
| Figure 5-11: Lipped C-Section with dimensions 400x100x25/2 von misses stress distribution .....                         | 67 |
| Figure 5-12: Through plate von misses stress distribution .....   | 67 |
| Figure 5-13: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 150x30x20/t.....                         | 68 |
| Figure 5-14: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 200x50x25/t.....                         | 69 |
| Figure 5-15: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 300x50x25/t.....                         | 69 |
| Figure 5-16: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 400x50x25/t.....                         | 70 |
| Figure 5-17: Normalized moment (M/Mp) against H/t ratio for Broken-Section .....  | 71 |
| Figure 5-18: Initial stiffness against plastic capacity (Mp) for Broken-Section and comparison with EC3 .....           | 71 |
| Figure 5-19: ductility coefficient ( $\mu$ ) against the plastic moment (Mp) of Broken-section ....                     | 72 |
| Figure 5-20: ductility coefficient ( $\mu$ ) against the slenderness ratio (H/t) of the web of Broken-section .....     | 73 |
| Figure 5-21: ductility coefficient ( $\mu$ ) against the slenderness ratio (B/t) of the flanges of Broken-section ..... | 73 |
| Figure 5-22: Von misses stress distribution for Broken-Section with dimensions 400x50x25/2 .....                        | 74 |
| Figure 5-23: Von misses stress distribution for through plate.....  | 75 |
| Figure 5-24: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 150x35/t.....                            | 76 |
| Figure 5-25: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/t.....                            | 76 |
| Figure 5-26: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/t.....                            | 77 |
| Figure 5-27: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 400x60/t.....                            | 77 |
| Figure 5-28: Normalized moment (M/Mp) against H/t ratio for Curved-Section .....  | 78 |
| Figure 5-29: Initial stiffness against plastic capacity (Mp) for Curved-Section and comparison with EC3 .....           | 79 |
| Figure 5-30: Von misses stress distribution for Curved-Section with dimensions 400x60/....                              | 80 |

|   |    |
|---|----|
| Figure 5-31: Von misses stress distribution for through plate.....  | 80 |
| Figure 5-32: Comparison between different CFS beam section according to the maximum nominal moment (Max. $M/M_p$ ) against the plastic moment ( $M_p$ ) .....             | 81 |
| Figure 5-33: Comparison between different CFS beam section according to the maximum nominal moment (Max. $M/M_p$ ) against the web slenderness ratio ( $H/t$ ).....       | 82 |
| Figure 5-34: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 200x85x20/1 without stiffeners and with different stiffeners configuration.....            | 84 |
| Figure 5-35: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 200x85x20/2 without stiffeners and with different stiffeners configuration.....            | 84 |
| Figure 5-36: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 200x85x20/3 without stiffeners and with different stiffeners configuration.....            | 85 |
| Figure 5-37: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 200x85x20/4 without stiffeners and with different stiffeners configuration.....            | 85 |
| Figure 5-38: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 300x100x20/1 without stiffeners and with different stiffeners configuration.....           | 86 |
| Figure 5-39: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 300x100x20/2 without stiffeners and with different stiffeners configuration.....           | 86 |
| Figure 5-40: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 300x100x20/3 without stiffeners and with different stiffeners configuration.....           | 87 |
| Figure 5-41: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 300x100x20/4 without stiffeners and with different stiffeners configuration.....           | 87 |
| Figure 5-42: Effect of $H/t$ ratio on the maximum normalized moment ( $M/M_p$ ) for: C-Section with different stiffeners configuration .....                              | 88 |
| Figure 5-43: Effect of $B/t$ ratio on the maximum normalized moment ( $M/M_p$ ) for: C-Section with different stiffeners configuration .....                              | 89 |
| Figure 5-44: Von misses stress distribution for lipped C-section with different stiffeners configuration; (a) CONFIG-1, (b) CONFIG-2, (c) CONFIG-3 and (d) CONFIG-4 ..... | 90 |
| Figure 5-45: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 200x50x25/1 without stiffeners and with different stiffeners configuration .....      | 91 |
| Figure 5-46: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 200x50x25/2 without stiffeners and with different stiffeners configuration .....      | 92 |
| Figure 5-47: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 200x50x25/3 without stiffeners and with different stiffeners configuration .....      | 92 |
| Figure 5-48: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 200x50x25/4 without stiffeners and with different stiffeners configuration .....      | 93 |
| Figure 5-49: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 300x50x25/1 without stiffeners and with different stiffeners configuration .....      | 93 |
| Figure 5-50: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 300x50x25/2 without stiffeners and with different stiffeners configuration .....      | 94 |
| Figure 5-51: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 300x50x25/3 without stiffeners and with different stiffeners configuration .....      | 94 |

|  |     |
|--|-----|
| Figure 5-52: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 300x50x25/4 without stiffeners and with different stiffeners configuration .....                  | 95  |
| Figure 5-53: Effect of H/t ratio on the maximum normalized moment (M/Mp) for: Broken-Section with different stiffeners configuration .....                                       | 96  |
| Figure 5-54: Von misses stress distribution for Broken-section with different stiffeners configuration; (a) CONFIG-1, (b) CONFIG-2, (c) CONFIG-3 and (d) CONFIG-4 .....          | 97  |
| Figure 5-55: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/1 without stiffeners and with different stiffeners configuration.....                      | 98  |
| Figure 5-56: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/2 without stiffeners and with different stiffeners configuration.....                      | 99  |
| Figure 5-57: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/3 without stiffeners and with different stiffeners configuration.....                      | 99  |
| Figure 5-58: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/4 without stiffeners and with different stiffeners configuration.....                      | 100 |
| Figure 5-59: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/1 without stiffeners and with different stiffeners configuration.....                      | 100 |
| Figure 5-60: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/2 without stiffeners and with different stiffeners configuration.....                      | 101 |
| Figure 5-61: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/3 without stiffeners and with different stiffeners configuration.....                      | 101 |
| Figure 5-62: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/4 without stiffeners and with different stiffeners configuration.....                      | 102 |
| Figure 5-63: Effect of H/t ratio on the maximum normalized moment (M/Mp) for: Curved-Section with different stiffeners configuration .....                                       | 103 |
| Figure 5-64: Von misses stress distribution for Curved-section with different stiffeners configuration; (a) CONFIG-1, (b) CONFIG-2, (c) CONFIG-3 and (d) CONFIG-4 .....          | 104 |
| Figure 5-65: Comparison between different CFS beam section with stiffeners CONFIG-4 according to the maximum nominal moment (Max. M/Mp) against the plastic moment (Mp) .....    | 105 |
| Figure 5-66: Comparison between different CFS beam section with stiffeners CONFIG-4 according to the maximum nominal moment (Max. M/Mp) against web slenderness ratio (H/t)..... | 106 |
| Figure 5-67: Normalized moment (M/Mp) against $\Theta$ for: C-Section 200x85x20/2 under cyclic load .....  | 107 |
| Figure 5-68: Normalized moment (M/Mp) against $\Theta$ for: C-Section 200x85x20/3 under cyclic load .....  | 108 |
| Figure 5-69: Normalized moment (M/Mp) against $\Theta$ for: C-Section 300x100x20/2 under cyclic load .....   | 108 |
| Figure 5-70: Normalized moment (M/Mp) against $\Theta$ for: C-Section 300x100x20/3 under cyclic load .....   | 109 |
| Figure 5-71: Effect of H/t ratio on the energy dissipation capacity for C-section with depths 200 and 300mm.....   | 110 |

|   |     |
|---|-----|
| Figure 5-72: Effect of plastic moment ( $M_p$ ) on the energy dissipation capacity for C-section with depths 200 and 300mm .....  | 110 |
| Figure 5-73: M Normalized moment ( $M/M_p$ ) against $\Theta$ for: Broken-Section 200x50x25/2 under cyclic load.....  | 111 |
| Figure 5-74: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Broken-Section 200x50x25/3 under cyclic load .....   | 112 |
| Figure 5-75: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Broken-Section 300x50x25/2 under cyclic load .....   | 112 |
| Figure 5-76: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Broken-Section 300x50x25/3 under cyclic load .....   | 113 |
| Figure 5-77: Effect of H/t ratio on the energy dissipation capacity for Broken-section with depths 200 and 300mm .....  | 114 |
| Figure 5-78: Effect of plastic moment ( $M_p$ ) on the energy dissipation capacity for Broken-section with depths 200 and 300mm.....                                    | 114 |
| Figure 5-79: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Curved-Section 200x40/2 under cyclic load .....  | 115 |
| Figure 5-80: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Curved-Section 200x40/3 under cyclic load .....  | 116 |
| Figure 5-81: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Curved-Section 300x50/2 under cyclic load .....  | 116 |
| Figure 5-82: Normalized moment ( $M/M_p$ ) against $\Theta$ for: Curved-Section 300x50/3 under cyclic load .....  | 117 |
| Figure 5-83: Effect of H/t ratio on the energy dissipation capacity for Curved-section with depths 200 and 300mm .....  | 118 |
| Figure 5-84: Effect of plastic moment ( $M_p$ ) on the energy dissipation capacity for Curved-section with depths 200 and 300mm.....                                    | 118 |
| Figure 5-85: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 200x85x20/2 with stiffeners configuration CONFIG-1 under cyclic load .....               | 119 |
| Figure 5-86: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 200x85x20/3 with stiffeners configuration CONFIG-1 under cyclic load .....               | 120 |
| Figure 5-87: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 300x100x20/2 with stiffeners configuration CONFIG-1 under cyclic load .....              | 120 |
| Figure 5-88: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: C-Section 300x100x20/3 with stiffeners configuration CONFIG-1 under cyclic load .....              | 121 |
| Figure 5-89: Effect of H/t ratio on the energy dissipation capacity for C-section with stiffeners configuration CONFIG-1 with depths 200 and 300mm .....                | 122 |
| Figure 5-90: Effect of plastic moment ( $M_p$ ) on the energy dissipation capacity for C-section with stiffeners configuration CONFIG-1 with depths 200 and 300mm ..... | 122 |
| Figure 5-91: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 200x50x25/2 with stiffeners configuration CONFIG-1 under cyclic load .....          | 123 |
| Figure 5-92: Normalized moment ( $M/M_p$ ) against ( $\Theta$ ) for: Broken-Section 200x50x25/3 with stiffeners configuration CONFIG-1 under cyclic load .....          | 124 |

|   |     |
|---|-----|
| Figure 5-93: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 300x50x25/2 with stiffeners configuration CONFIG-1 under cyclic load .....               | 124 |
| Figure 5-94: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 300x50x25/3 with stiffeners configuration CONFIG-1 under cyclic load .....               | 125 |
| Figure 5-95: Effect of H/t ratio on the energy dissipation capacity for Broken-section with stiffeners configuration CONFIG-1 with depths 200 and 300mm .....           | 126 |
| Figure 5-96: Effect of plastic moment (Mp) on the energy dissipation capacity for Broken-section with stiffeners configuration CONFIG-1 with depths 200 and 300mm.....  | 126 |
| Figure 5-97: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/2 with stiffeners configuration CONFIG-1 under cyclic load .....                  | 127 |
| Figure 5-98: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 200x40/3 with stiffeners configuration CONFIG-1 under cyclic load .....                  | 128 |
| Figure 5-99: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/2 with stiffeners configuration CONFIG-1 under cyclic load .....                  | 128 |
| Figure 5-100: Normalized moment (M/Mp) against ( $\Theta$ ) for: Curved-Section 300x50/3 with stiffeners configuration CONFIG-1 under cyclic load .....                 | 129 |
| Figure 5-101: Effect of H/t ratio on the energy dissipation capacity for Curved-section with stiffeners configuration CONFIG-1 with depths 200 and 300mm .....          | 130 |
| Figure 5-102: Effect of plastic moment (Mp) on the energy dissipation capacity for Curved-section with stiffeners configuration CONFIG-1 with depths 200 and 300mm..... | 130 |
| Figure 5-103: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 200x85x20/2 with stiffeners configuration CONFIG-2 under cyclic load .....                   | 131 |
| Figure 5-104: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 200x85x20/3 with stiffeners configuration CONFIG-2 under cyclic load .....                   | 132 |
| Figure 5-105: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 300x100x20/2 with stiffeners configuration CONFIG-2 under cyclic load .....                  | 132 |
| Figure 5-106: Normalized moment (M/Mp) against ( $\Theta$ ) for: C-Section 300x100x20/3 with stiffeners configuration CONFIG-2 under cyclic load .....                  | 133 |
| Figure 5-107: Effect of H/t ratio on the energy dissipation capacity for C-section with stiffeners configuration CONFIG-2 with depths 200 and 300mm .....               | 134 |
| Figure 5-108: Effect of plastic moment (Mp) on the energy dissipation capacity for C-section with stiffeners configuration CONFIG-2 with depths 200 and 300mm .....     | 134 |
| Figure 5-109: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 200x50x25/2 with stiffeners configuration CONFIG-2 under cyclic load .....              | 135 |
| Figure 5-110: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 200x50x25/3 with stiffeners configuration CONFIG-2 under cyclic load .....              | 136 |
| Figure 5-111: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 300x50x25/2 with stiffeners configuration CONFIG-2 under cyclic load .....              | 136 |
| Figure 5-112: Normalized moment (M/Mp) against ( $\Theta$ ) for: Broken-Section 300x50x25/3 with stiffeners configuration CONFIG-2 under cyclic load .....              | 137 |
| Figure 5-113: Effect of H/t ratio on the energy dissipation capacity for Broken-section with stiffeners configuration CONFIG-2 with depths 200 and 300mm .....          | 138 |