



Cairo University

FLOW ASSURANCE STUDY FOR A GATHERING PIPES SYSTEM OF AN EGYPTIAN GAS-CONDENSATE FIELD

By

Emad El-Din Mahmoud Rabeea

A Thesis Submitted to the
Faculty of Engineering at Cairo University
in Partial Fulfillment of the
Requirements for the Degree of
MASTER OF SCIENCE
in
Petroleum Engineering

FACULTY OF ENGINEERING, CAIRO UNIVERSITY
GIZA, EGYPT
2018

FLOW ASSURANCE STUDY FOR A GATHERING PIPES SYSTEM OF AN EGYPTIAN GAS-CONDENSATE FIELD

By
Emad El-Din Mahmoud Rabeea

A Thesis Submitted to the
Faculty of Engineering at Cairo University
in Partial Fulfillment of the
Requirements for the Degree of
MASTER OF SCIENCE
in
Petroleum Engineering

Under the Supervision of

Prof. Dr. Abdel Waly Abdalla Abdel Waly

Professor of Gas Production Engineering
Mining, Petroleum and Metallurgy Engineering
Faculty of Engineering, Cairo University

FACULTY OF ENGINEERING, CAIRO UNIVERSITY
GIZA, EGYPT
2018

FLOW ASSURANCE STUDY FOR A GATHERING PIPES SYSTEM OF AN EGYPTIAN GAS-CONDENSATE FIELD

By
Emad El-Din Mahmoud Rabeea

A Thesis Submitted to the
Faculty of Engineering at Cairo University
in Partial Fulfillment of the
Requirements for the Degree of
MASTER OF SCIENCE
in
Petroleum Engineering

Approved by the
Examining Committee

Prof. Dr. Abdel Waly Abdalla Abdel Waly (Thesis Main Advisor)

Prof. Dr. Mohamed Khairy Ali Ahmed (Internal Examiner)

Eng. Taher Abdel Rehem Ali (External Examiner)
Chairman of Board of Petrosilah Company

Engineer's Name: Emad El-Din Mahmoud Rabeea

Date of Birth: 20 / 07 / 1986

Nationality: Egyptian

E-mail: emad.rabeea@gmail.com

Phone: 00201066566588

Address: Mehalla, Gharbya

Registration Date: 1 / 3 / 2015

Awarding Date: / / 2018

Degree: Master of Science

Department: Mining, Petroleum and Metallurgy Engineering

Supervisors: Prof. Dr. Abdel Waly Abdalla Abdel Waly

Examiners:

Prof. Dr. Abdel Waly A Abdel Waly	(Thesis Main advisor)
Prof. Dr. Mohamed Khairy Ali Ahmed	(Internal examiner)
Eng. Taher Abdel Rehem Ali	(External examiner)
Chairman of Board of Petrosilah Company	

Title of Thesis:

FLOW ASSURANCE STUDY FOR A GATHERING PIPES SYSTEM OF AN EGYPTIAN GAS-CONDENSATE FIELD

Key Words:

Flow assurance; Pipes; Condensate; Gas; Multiphase flow

Summary:

Flow assurance refers to ensuring successful and economical flow of hydrocarbon from reservoir to the point of sale. In this study, a gas-condensate field gathering system is considered for a flow assurance study to determine its integrity and reliability towards current, future conditions and at maximum capacity. A transient flow study is performed assuming two scenarios; the time needed to reach the maximum allowable working pressure and performing pigging to the trunk lines. The study showed the importance of flow assurance for management decision and engineering design.



Acknowledgments

I would like to express my deep gratitude to Professor Dr. Abdel Waly, my research supervisors, for their patient guidance, encouragement and useful critiques of this research work. I would also like to thank WASCO managers, for their advice and assistance in keeping my progress on schedule. My grateful thanks are also extended to my colleagues for his help in collecting the required data and providing me with the software used in my thesis. Finally, I wish to thank my parents and my wife for their support and encouragement throughout my study.

Dedication

To my Advisor, Prof. Dr. Abdel Waly, without your advice, support and encouragement, this work wouldn't be possible. Thank you.

To my parents, this day wouldn't be possible without your full support and help. This day is the crown jewel of your journey. Thank you.

To my wife, you have stood by me through this journey and here we are. This glories day is your prize. Thank you.

To my colleagues, this work wouldn't be possible without your help with data, material and advice. Thank you

To my son, this is my legacy to you. Be proud of it, learn from it and improve it.

Table of Contents

ACKNOWLEDGMENTS.....	I
DEDICATION	II
TABLE OF CONTENTS.....	III
LIST OF TABLES.....	V
LIST OF FIGURES.....	VI
NOMENCLATURE	VIII
ABSTRACT	IX
CHAPTER 1 : INTRODUCTION	1
CHAPTER 2 : OBJECTIVE.....	3
CHAPTER 3 : PROBLEM STATEMENT.....	4
CHAPTER 4 : LITERATURE REVIEW	6
4.1. INTRODUCTION	6
4.2. PRESSURE DROP.....	6
4.2.1. Single Phase Flow.....	7
4.3. MULTIPHASE FLOW.....	12
4.3.1. Vertical multiphase flow correlations	14
4.3.2. Horizontal multiphase flow correlations.....	16
4.3.3. Inclined Multiphase flow	16
4.4. GATHERING SYSTEMS	18
4.5. TRANSIENT FLOW	22
4.5.1. Equation of State.....	22
4.5.2. The equation of continuity	23
4.5.3. The equation of motion	23
4.6. NUMERICAL SOLUTIONS	24
4.7. FLOW REGIMES	25
4.8. LIQUID HOLD-UP	26
4.9. SLUG FLOW.....	27
4.9.1. Hydrodynamic Slugging	29
4.9.2. Pigging.....	29
4.9.3. Ramp-Up.....	29
4.10. HYDRATE FORMATION	31
4.11. EROSION	33
CHAPTER 5 : METHODOLOGY	34
CHAPTER 6 : PROCEDURES.....	35

6.1.	INTRODUCTION	35
6.2.	COLLECTING DATA.....	37
6.3.	ASSUMPTIONS	37
6.4.	DATA	38
6.4.1.	Flow data.....	38
6.4.2.	Nodal-1 wells.....	38
6.4.3.	Nodal-3 wells.....	39
6.4.4.	Flow Line Data	39
6.5.	BUILDING THE MATHEMATICAL MODEL	41
CHAPTER 7 : RESULTS AND DISCUSSION.....		42
7.1.	DATA MATCHING.....	42
7.1.1.	Production figures matching.....	42
7.1.2.	Flow Line Pressure matching.....	42
7.2.	CURRENT SITUATION STEADY-STATE SIMULATION RESULTS.....	43
7.2.1.	Pressure Profile	43
7.2.2.	Flow regimes.....	46
7.2.3.	Liquid Holdup.....	47
7.2.4.	Slug flow.....	49
7.2.5.	Erosion Velocity Ratio (EVR)	51
7.2.6.	Hydrate formation.....	52
7.2.7.	Summary of current network	54
7.3.	NETWORK MAXIMUM CAPACITY	58
7.4.	TRANSIENT FLOW SCENARIOS	71
7.4.1.	ESD scenario.....	71
7.4.2.	Pigging operation.....	72
CHAPTER 8 : CONCLUSIONS AND RECOMMENDATIONS		90
8.1.	CONCLUSIONS	90
8.2.	RECOMMENDATIONS	90
REFERENCES		92

List of Tables

Table 4.1: Multiphase vertical flow correlations history. (Brown and Beggs ⁽⁶⁾).	14
Table 4.2: Multiphase horizontal flow correlation history. [After Brown and Beggs ⁽⁶⁾].	17
Table 6.1: Flow data of the producing wells and nodals used in the model.	38
Table 6.2: Nodal-1 wells and its flowing data.	39
Table 6.3: Nodal-3 wells and its flowing data.	39
Table 6.4: The data of the network's pipelines.	39
Table 7.1: Data matching for production data.	42
Table 7.2: Data matching for flow line pressure.	43
Table 7.3: The calculated pressure drop across each branch in the system.	44
Table 7.4: Flow regime of each pipeline in the system calculated by the model.	46
Table 7.5: Liquid holdup data from the model for each flow line.	47
Table 7.6: Maximum surge volume expected from each pipeline.	49
Table 7.7: Erosion Velocity Ration (EVR) of the pipelines in the network.	51
Table 7.8: Hydrate difference temperature for each pipeline.	52
Table 7.9: Summery of the simulation results for the current flowing condition.	55
Table 7.10: The SIWHP of WASCO fields' wells.	59
Table 7.11: The maximum capacity of the network, considering each field individually.	63
Table 7.12: The maximum capacity of the network, considering the whole network.	63
Table 7.13: Summery of the simulation results of the network, during maximum production rates.	65
Table 7.14: The maximum capacity of the network, considering the whole network capacity and integrity.	67
Table 7.15: Summery of the simulation results of the network, during maximum production rates.	69
Table 7.16: Summery of pigging operation of the main trunk line of the network.	80

List of Figures

Figure 4.1: Gas flow in an inclined section. [After Kumar ⁽²⁾].	9
Figure 4.2: Overall production system including all flow categories. [After Brown and Beggs ⁽⁶⁾].	13
Figure 4.3: (a) Axial gathering systems and (b) radial gathering systems.	18
Figure 4.4: (a) Well-Center gathering system and (b) Trunk-line gathering system. [After Kumar ⁽²⁾].	18
Figure 4.5: Loopless pipeline system. [After Kumar ⁽²⁾].	21
Figure 4.6: Looped systems: (a) single loop, (b) multiple loop. [After Kumar ⁽²⁾].	22
Figure 4.7: Flow regime of two-phase flow in horizontal pipe. [After Brennen ⁽³⁹⁾].	25
Figure 4.8: Flow regime of two-phase flow in vertical pipe. [After Brennen ⁽³⁹⁾].	26
Figure 4.9: Pigging Operation illustration.	29
Figure 4.10: Ramp-up illustration.	30
Figure 4.11: Hydrate structure I, II and H. [After Watt ⁽⁶³⁾].	31
Figure 4.12: Hydrate curve. [After PIPESIM Manual ⁽⁶⁰⁾].	32
Figure 6.1: WASCO fields pipeline gathering system.	36
Figure 7.1: Pressure profile calculated from the model across truck lines in the system for the current situation	45
Figure 7.2: Liquid holdup, % Vs. gas velocity, ft/s.	49
Figure 7.3: The effect of different flow rates in EL-Wastani field on truck line pressure.	60
Figure 7.4: The effect of different flow rates in Bassant field on truck line pressure.	60
Figure 7.5: The effect of different flow rates in Balsam field on truck line pressure.	61
Figure 7.6: The effect of different flow rates in Faraskur field on truck line pressure.	61
Figure 7.7: The effect of different flow rates in SAEN field on truck line pressure.	62
Figure 7.8: The effect of different flow rates in Salma field on truck line pressure.	62
Figure 7.9: Pressure profile of the main trunk lines of the network, along with the current condition profile.	64
Figure 7.10: A comparison between production rates for each simulation case.	68
Figure 7.11: Pressure profile of the main trunk lines of the network for maximum flow rate, along with the current condition profile	68
Figure 7.12: Central Processing Facility pressure with time.	71
Figure 7.13: Pigging operation for TL_1.	72
Figure 7.14: Pigging operation for TL_2.	73
Figure 7.15: Pigging operation for TL_3.	73
Figure 7.16: Pigging operation for TL_4.	74
Figure 7.17: Pigging operation for TL_5.	74
Figure 7.18: Pigging operation for TL_6.	75
Figure 7.19: Pigging operation for TL_7.	75
Figure 7.20: Pigging operation for TL_8.	76
Figure 7.21: Pigging operation for TL_9.	76
Figure 7.22: Pigging operation for TL_10.	77
Figure 7.23: Pigging operation for TL_11.	77
Figure 7.24: Pigging operation for TL_12.	78
Figure 7.25: Pigging operation for TL_13.	78

Figure 7.26: Pigging operation for TL_14.	79
Figure 7.27: Pigging operation for TL_15.	79
Figure 7.28: Pigging operation for TL_16.	80
Figure 7.29: Effect of pigging operation for TL_1 on source node pressure.	81
Figure 7.30: Effect of pigging operation for TL_2 on source node pressure.	82
Figure 7.31: Effect of pigging operation for TL_3 on source node pressure.	82
Figure 7.32: Effect of pigging operation for TL_4 on source node pressure.	83
Figure 7.33: Effect of pigging operation for TL_5 on source node pressure.	83
Figure 7.34: Effect of pigging operation for TL_6 on source node pressure.	84
Figure 7.35: Effect of pigging operation for TL_7 on source node pressure.	84
Figure 7.36: Effect of pigging operation for TL_8 on source node pressure.	85
Figure 7.37: Effect of pigging operation for TL_9 on source node pressure.	85
Figure 7.38: Effect of pigging operation for TL_10 on source node pressure.	86
Figure 7.39: Effect of pigging operation for TL_11 on source node pressure.	86
Figure 7.40: Effect of pigging operation for TL_12 on source node pressure.	87
Figure 7.41: Effect of pigging operation for TL_13 on source node pressure.	87
Figure 7.42: Effect of pigging operation for TL_14 on source node pressure.	88
Figure 7.43: Effect of pigging operation for TL_15 on source node pressure.	88
Figure 7.44: Effect of pigging operation for TL_16 on source node pressure.	89

Nomenclature

AGA	:American Gas Association
API	:American Petroleum Institute
CGR	:Condensate/gas ratio
CPF	:Central Processing Facility
Dab-x	: Dabayaa well number x
ESD	: Emergency Shut down
EVR	: Erosion Velocity Ratio
EWE-2	: El-Wastani East-2 well
EW-x	: El-Wastani number x well
Far-3	: Faraskur-3 well
FL	: Flow Line
FLP	: Flow Line Pressure
FLT	: Flow Line Temperature
GPS	: Global Positioning System
ID	: Internal diameter
MAWP	: Maximum Allowable Working Pressure
MFD	: Manifold
Mscfd	: Thousand standard cubic feet per day
MMscfd	: Million standard cubic feet per day
NA	: Not available
NCE	: Node connecting element
psia	: Absolute pound per square inch
psig	: Gauge pound per square inch
Qc	: Condensate flow rate
Qg	: Gas flow rate
Qw	: Water flow rate
S-Far-x	: South Faraskur well number x
SAEN	: South Abu EL-Naga Field
SAEN-x	: South Abu El-Naga well number x
SIWHP	: Shut-In Well Head Pressure
STB/D	: Stock tank barrel per day
TL	: Trunk Line
VR	: Valve Room
WASCO	: El-Wastani Petroleum Company
WC	: Water Cut

Abstract

Flow assurance is a newly concept introduced to industry in the 90th decade. Flow assurance refers to ensuring successful and economical flow of hydrocarbon stream from reservoir to the point of sale. Flow assurance is extremely diverse, encompassing many discrete and specialized subjects and bridging across the full series of engineering disciplines.

There are several obstacles to the flow from the reservoir till the end user. The most common obstacles are pressure drop, liquid holdup, erosion and hydrate formation. There are several correlations were developed in literatures to predict those obstacles. Those correlations can be time-dependent, thus called transient flow correlations. There are several commercial simulation software equipped with these correlations and save time and energy for solving this equations by hand.

In this study, WASCO gas-condensate field gathering system is considered for a flow assurance study to determine its integrity and reliability towards current and future conditions. The commercial, multiphase, transient flow software OLGA is used in this study. Data from the fields are collected, sorted and filtered to match the required input format of the software. After building the mathematical model, data matching is done to verify the model.

The current condition of the network is studied for steady-state flow assurance aspects as pressure drop, liquid holdup, flow regime, erosion and hydrate formation. It was found that the network is suitable for the current production rates. The maximum capacity of the network is then calculated and the flow assurance study for the new flow rates is repeated.

A transient flow study is performed assuming two scenarios. The first scenario is to calculate the time needed for the network to reach the maximum allowable working pressure, if an emergency shutdown occurred in the downstream processing facility. The second scenario is performing pigging operation to the main trunk lines and studying its effect on the pressure drop.

The study clearly showed the importance of flow assurance study for management decision and engineering design. The effect of liquid holdup on pressure drop is clarified and regular pigging operation is recommended to overcome the high pressure drop. The effect of gas velocity on liquid holdup is stated. The erosion velocity ratio also limited the maximum capacity of the network and the study recommended looping the main trunk line to increase its capacity.

Chapter 1

Introduction

The increasing demand of energy sources, along with fluctuation of oil and gas prices make it inevitable to review the current technologies of production, transportation and storage of oil and gas. New technologies have been introduced in exploration and development of oil or gas well to be able to produce economically. These technologies show great success in drilling and producing oil and gas wells economically and efficiently. However, one major obstacle aroused recently especially as we dig deeper under water and underground. This obstacle is how to deliver the valuable hydrocarbon from the reservoir economically to the end user. This concern made the manufacturer and scientists to come up with a new term in oil and gas industry; flow assurance .

Flow assurance refers to ensuring successful and economical flow of hydrocarbon stream from reservoir to the point of sale. By definition, Flow assurance focuses on the whole engineering and production life cycle from the reservoir through refining, to ensure with high confidence that the reservoir fluids can be moved from the reservoir to the refinery smoothly and without interruption.

Flow assurance is extremely diverse, encompassing many discrete and specialized subjects and bridging across the full series of engineering disciplines. The financial loss from production interruption or asset damage due to flow assurance mishap can be astronomical .

According to API ⁽¹⁾, Flow assurance is a term commonly used to cover a wide range of flow-related issues. These issues typically include:

1. Hydrate formation‘
2. Wax formation‘
3. Asphaltene formation‘
4. Emulsions‘
5. Foaming‘
6. Scale formation‘
7. Sand production‘
8. Slugging‘
9. Materials-related issues .

The flow assurance study should cover the entire system, from the perforations through to and including the processing facilities on the host/drilling rig, as well as considering the complete life-cycle of the development, including:

1. Installation activities‘
2. Commissioning activities‘

3. Routine operation‘
4. Intervention and maintenance activities‘
5. Abandonment activities.

In this thesis, the main focus will be on the flow assurance regarding the hydrocarbon transport from gas-condensate wells to the processing facility through a pipeline gathering system.