

بسم الله الرحمن الرحيم

 $\infty\infty\infty$

تم رفع هذه الرسالة بواسطة / سلوي محمود عقل

بقسم التوثيق الإلكتروني بمركز الشبكات وتكنولوجيا المعلومات دون أدنى مسئولية عن محتوى هذه الرسالة.

ملاحظات: لا يوجد

AIN SHAMS UNIVERSITY

Since 1992



Effect of Variation of Layers Thicknesses on Shade Production in Two Layering Techniques.

Thesis submitted to the Faculty of Dentistry, Ain Shams
University in partial fulfillment of the requirements of
PhD degree in Operative Dentistry.

By

Nermeen Mohamed Reda Diab

B.D.S., Ain Shams University (2009)

M.S.C., Ain Shams University (2015)

Ain Shams University

2022

Supervisors

Dr. Khaled Aly Nour

Assistant professor, Department of Operative Dentistry Faculty of Dentistry, Ain Shams University

Dr. Mohammed Nasser Mohammed Anwar

Lecturer, Department of Operative Dentistry Faculty of Dentistry, Ain Shams University

Ain Shams University 2022

I'd like to express my gratitude to my supervisors,

- -Dr.khaled Aly Nour, Assistant professor of operative dentistry, Ain Shams university.
- -Dr.Mohamed Nasser, Lecturer of operative dentistry, Ain Shams university.

I'd like also to thank these 4 colleagues of mine, for their endless help and support during the course of this thesis,

- -Rana Abdel Reheem, lecturer of operative dentistry, Ain shams university.
- -Maha Salah, assistant lecturer of operative dentistry, Ain Shams university.
- -Amr Eldeeb, assistant lecturer of operative dentistry, Ain Shams university & my research partner.
- -Dina Gamal, teaching assistant of operative dentistry, Ain Shams university.

I'd like to dedicate this thesis to:

- -My mom, my number one supporter, my backbone, I wouldn't have done it without you!
- -Dr. Salma Elashry "God bless her soul" ... my second mom, who'd have been thrilled watching me defend my thesis this day.
- -Mr. Ahmed Shams ... my chemistry teacher 20 years ago, you are my forever idol and the reason I love teaching, I hope one day I reach your level of perfection as a teacher.
- -Hany Ali Galal, my late beloved uncle "God bless his soul" I knew how to enjoy life because of you.

Table of Contents

| List of tables | ii |
|-------------------------|-----|
| List of figures | iv |
| Introduction | 1 |
| Review of literature | 4 |
| Aim of the study | 33 |
| Materials and Methods | 34 |
| Results | 67 |
| Discussion | 121 |
| Summary and Conclusions | 132 |
| References | 135 |
| Arabic Summary | 1 |

List of Tables

| Table 4-1: materials used, their compositions and lot numbers |
|--|
| Table 4-2 : Variables investigated |
| Table 4-3: Interaction between experimental variables: |
| Table 5-1 Effect of different variables and their interactions on color change (ΔE) |
| (2000) (spectrophotometer) |
| Table 5-2 :Effect of different variables and their interactions on color change (ΔE) |
| (2000) (cross polarized photography) |
| Table 5-3: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (spectrophotometer) for different shade combinations |
| Table 5-4: : Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (cross polarized photography) for different shade combinations 70 |
| Table 5-5: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (spectrophotometer) for different shade combinations |
| Table 5-6: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (cross polarized photography) for different shade combinations 73 |
| Table 5-7: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (spectrophotometer) for different enamel thicknesses |
| Table 5-8: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (cross polarized photography) for different enamel thicknesses 76 |
| Table 5-9: Frequency and percentage values of color difference acceptability for |
| different enamel thicknesses |
| Table 5-10: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (spectrophotometer) for different enamel thicknesses within other |
| variables83 |
| Table 5-11: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (cross polarized photography) for different enamel thicknesses within |
| other variables |
| Table 5-12: Frequency and percentage values of color difference acceptability for |
| different enamel thicknesses within other variables91 |
| Table 5-13: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (spectrophotometer) for different shade combinations96 |
| Table 5-14: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (cross polarized photography) for different shade combinations 98 |
| Table 5-15: Frequency and percentage values of color difference acceptability for |
| different shade combinations |
| Table 5-16: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
| (spectrophotometer) for different shade combinations within other |
| variables |

| Table 5-17: Mean and standard deviation (SD) values of color change (ΔE) (2000) |
|---|
| (cross polarized photography) for different shade combinations within |
| other variables |
| Table 5-18: Frequency and percentage values of color difference acceptability for |
| different shade combinations within other variables111 |
| Table 5-19: Inter-device agreement |
| Table 5-20: Frequency and percentage values of color difference acceptability for |
| different genders |
| Table 5-21: Frequency and percentage values of color difference acceptability for |
| different professions |

List of Figures:

| Figure 2-1: A diagram showing the human visible light spectrum (8). | 4 |
|---|--------|
| Figure 2-2: A diagram showing the spectral sensitivities of the L-, M-, and S | |
| classes (10) | 5 |
| Figure 2-3: A diagram showing the CIELab color space (17). | |
| Figure 2-4A diagram showing inclusion (a) and exclusion (b) of specular refle | ection |
| (62). | 19 |
| Figure 2-5): A diagram showing the layering concepts 1 (a) and 2 (b) (2) | 29 |
| Figure 4-1: Enamel shades used. | 36 |
| Figure 4-2: body shades used | 36 |
| Figure 4-3:dentin shades used | 36 |
| Figure 4-4: A photograph showing the circular split copper mold with a central | l hole |
| of 10 mm diameter and a thickness of 3 mm (M-3) | 42 |
| Figure 4-5: A photograph showing packing of the dentin shade into M-3. (a) A c | lentin |
| shade packed in M-3 in one increment slightly overfilling the mol | d. (b) |
| The increment covered with an acetate paper and pressed firmly v | vith a |
| glass slide to extrude any excess material/ | 42 |
| Figure 4-6: A photograph showing verification of the required thickness of a continuous | lentin |
| shade disc using a digital caliper | 43 |
| Figure 4-7: A photograph showing the specially constructed device composed | d of a |
| cylindrical mold with an internal diameter of 10 mm and length of | 4 cm |
| with a central piston of the same dimensions snugly fit into the int | ternal |
| chamber of the mold.with an internal diameter of 10 mm | 43 |
| Figure 4-8: A photograph showing packing of the enamel shade layer on top of | of the |
| dentin shade disc. (a) The cured dentin shade disc inserted int | o the |
| preadjusted specially constructed device. (b) The enamel shade pa | acked |
| over the dentin shade disc slightly overfilling the mold. (c) The incre | ement |
| covered with an acetate paper and pressed firmly with a glass sli | de to |
| extrude any excess material. (d) Light curing of the enamel | shade |
| increment | 44 |
| Figure 4-9: A photograph showing verification of the required thickness | of an |
| enamel/dentin shade disc using a digital calliper. | 44 |
| Figure 4-10: A photograph showing the circular split copper with a central ho | ole of |
| 10 mm diameter and a thickness of 2 mm (M-2). | 47 |
| Figure 4-11 A photograph showing packing of the dentin shade into M-2. (a) A c | lentin |
| shade packed in M-2 in one increment slightly overfilling the mol | d. (b) |
| The increment covered with an acetate paper and pressed firmly v | vith a |
| glass slide to extrude any excess material. (c) Light curing of the c | lentin |
| shade increment. | 47 |

| Figure 4-12 | 2: A photograph showing packing of the body shade layer on top of the |
|-------------|--|
| | dentin shade disc. (a) The cured dentin shade disc inserted into M-3. (b) |
| | The body shade packed over the dentin shade disc slightly overfilling the |
| | mold. (c) The increment covered with an acetate paper and pressed firmly |
| | with a glass slide to extrude any excess material. (d) Light curing of the |
| T | body shade increment |
| Figure 4-13 | : A photograph showing packing of the enamel shade layer on top of the |
| | body/dentin shade disc. (a) The cured body/dentin shade disc inserted |
| | into the pre-adjusted specially constructed device. (b) The enamel shade |
| | packed over the body shade side slightly overfilling the mold. (c) The |
| | increment covered with an acetate paper and pressed firmly with a glass |
| | slide to extrude any excess material. (d) Light curing of the enamel shade |
| | increment |
| Figure 4-14 | 4: A photograph showing calibration of the VITA Easyshade® V by |
| | placing its probe tip on the calibration port aperture before each color measurement |
| Figure 4-15 | 5 : A photograph showing the VITA Easyshade® V spectrophotometer |
| U | during color measurement of a finalized resin composite disc |
| Figure 4-16 | 5 :A photograph showing the VITA Easyshade® V spectrophotometer |
| U | during color measurement of a reference VITA classical shade tab. (a) |
| | The reference VITA classical shade tab fitted in the custom-made |
| | positioning clear silicone mold. (b) The VITA Easyshade® V |
| | spectrophotometer probe tip fitted in the custom-made positioning clear |
| | silicone mold |
| Figure 4-17 | 7 :A photograph showing a full frame digital single-lens reflex camera |
| 6 | (Canon EOS 6D Mark II) with mounted Canon EF 100 mm f/2.8 L IS |
| | USM Macro Lens and an external ring flash (Meike MK-14EXT Macro |
| | Ring Lite) attached to a cross-polarizing filter (polar_eyes, Emulation, |
| | Frankfurt, Germany) |
| Figure 4-18 | B: A photograph showing the cross-polarized photography assembly |
| 118010 11 | attached to a tripod (055PRO3 kit, Manfrotto, Italy) adjusted to allow the |
| | optical axis of the camera to be perpendicular to the horizontal plane and |
| | fixed to 19 cm |
| Figure 4-19 | : A photograph showing the built-in water balance indicators of the tripod |
| Tiguic +-1) | (055PRO3 kit, Manfrotto, Italy) |
| Figure 4-20 | : A photograph showing a resin composite disc placed over a black matt |
| 115010 1 20 | background next to its reference VITA classical shade tab with the gray |
| | reference card (white_balance, Emulation, $L*79 + a*0 + b*0$) placed |
| | directly below them with fully captured two lo |
| Figure 1-21 | calibration of the polarized photos by adobe photoshop |
| 11501C T-21 | .cuitoration of the polarized photos by adobe photoshop |