

شبكة المعلومات الجامعية التوثيق الإلكتروني والميكروفيلو

# بسم الله الرحمن الرحيم





HANAA ALY



شبكة المعلومات الجامعية التوثيق الإلكتروني والميكرونيله



شبكة المعلومات الجامعية التوثيق الالكتروني والميكروفيلم



HANAA ALY



شبكة المعلومات الجامعية التوثيق الإلكترونى والميكروفيلم

## جامعة عين شمس التوثيق الإلكتروني والميكروفيلم قسم

نقسم بالله العظيم أن المادة التي تم توثيقها وتسجيلها على هذه الأقراص المدمجة قد أعدت دون أية تغيرات



يجب أن

تحفظ هذه الأقراص المدمجة بعيدا عن الغبار



HANAA ALY





# Use of Continuous-Flow Sequencing Batch Biofilm Reactor (CSBBR) for Improving the Treatment Process in the Wastewater Treatment Plants

By

#### **Ahmed Abdelhalim Sallam**

A Thesis Submitted to the
Faculty of Engineering at Cairo University
in Partial Fulfillment of the
Requirements for the Degree of
MASTER OF SCIENCE
in
Civil Engineering-Public Works

FACULTY OF ENGINEERING, CAIRO UNIVERSITY GIZA, EGYPT 2020

## Use of Continuous-Flow Sequencing Batch Biofilm Reactor (CSBBR) for Improving the Treatment Process in the Wastewater Treatment Plants

## By **Ahmed Abdelhalim Sallam**

A Thesis Submitted to the Faculty of Engineering at Cairo University in Partial Fulfillment of the Requirements for the Degree of **MASTER OF SCIENCE** 

in

**Civil Engineering-Public Works** 

Under the Supervision of

#### Prof. Dr. Hisham Sayed Abdel Halim

Dr. Abdelsalam Ahmed Elawwad

Professor of Sanitary and Environmental
Engineering
Public Works Department
Faculty of Engineering ,Cairo University

Associate Professor of Sanitary and Environmental Engineering Public Works Department Faculty of Engineering ,Cairo University

FACULTY OF ENGINEERING, CAIRO UNIVERSITY GIZA, EGYPT 2020

## USE OF CONTINUOUS-FLOW SEQUENCING BATCH BIOFILM REACTOR (CSBBR) FOR IMPROVING THE TREATMENT PROCESS IN THE WASTEWATER TREATMENT PLANTS

By

#### **Ahmed Abdelhalim Sallam**

A Thesis Submitted to the Faculty of Engineering at Cairo University in Partial Fulfillment of the Requirements for the Degree of

MASTER OF SCIENCE

in

**Civil Engineering-Public Works** 

Examining Committee	
Prof. Dr. Hisham Sayed Abdel Halim	Thesis Main Advisor
Dr. Abdelsalam Ahmed Elawwad	Advisor
Dr. Mona Mohammed Galal El-Din	Internal Examiner
Prof. Dr. Maha Mostafa El Shafei	External Examiner

- Professor of sanitary and environmental engineering, Housing and Building National Research Center

Approved by the

FACULTY OF ENGINEERING, CAIRO UNIVERSITY GIZA, EGYPT 2020 Engineer's Name: <u>Ahmed Abdelhallem Sallam Bekhet.</u>

**Date of Birth:** 31/12/1965 **Nationality:** Egyptian

**E-mail:** ahmdsallamsallam@gmail.com

 Phone:
 01223411972

 Registration Date:
 01/10/2012

 Awarding Date:
 / /2020

**Degree:** Master of Science

**Department:** Civil Engineering – Public Works.

**Supervisors:** 

Prof. Hisham Abdel Halim Dr. Abdelsalam Elawwad

**Examiners:** Prof. Dr. Hisham Sayed Abdel Halim Thesis Main Advisor

Dr. Abdelsalam Ahmed Elawwad Advisor

Dr. Mona Mohammed Galal El-Din Internal Examiner
Prof. Dr. Maha Mostafa El Shafei External Examiner
-Professor of sanitary and environmental engineering,

Housing and Building National Research Center

#### **Title of Thesis:**

Use of Continuous-Flow Sequencing Batch Biofilm Reactor (CSBBR) for Improving the Treatment Process in the Wastewater Treatment Plants

#### **Key Words:**

Wastewater treatment; CSBBR; Organic Removal; SBR with media; wastewater treatment.

**Summary:** In this research, a pilot plant was constructed and operated using the continuous-flow sequencing batch biofilm reactor (CSBBR) to study its performance towards wastewater treatment. The experimental work was conducted at Zenien WWTP through different 4 stages using two reactors (R1, R2): The first stage (start-up) carried out in 49 days, the second stage (Low organic load) carried out in 21 days, the third stage (Low organic with added media in R2) carried out in 70 days, and the fourth stage (medium organic load with added media in R2) carried out in 84 days, respectively. Thus, the pilot plant has been operated for 224 continuous days. The temperature was between (16.1 - 33 °C), and pH (6.00 - 7.84). The media used during the third & fourth stages is polyethylene HDPE Bio Pac Media with specific surface area of 600 m<sup>2</sup>/m<sup>3</sup> and have been occupied 30% of the reactor volume. The solid retention time (SRT) was adjusted to be 15 days for all stages, flow rate was (10 L/Hr.), and hydraulic retention time (HRT) was (6 hrs.) for all stages. The removal rates have improved after media addition, and the pilot plant has showed stability for the treatment process with load increases.



### **Disclaimer**

I hereby declare that this thesis is my own original work and that no part of it has been submitted for a degree qualification at any other university or institute.

I further declare that I have appropriately acknowledged all sources used and have

cited them in the references section.

Name: Ahmed Abdelhallem Sallam Bekhet Date: / /2020

Signature:

## Acknowledgments

I would like to thank the almighty Allah for the uncountable blessing and mercy that he has bestowed upon me. My sincerest appreciations go to my supervisors Prof. Hisham Sayed Abdel Halim, and Dr. Abdelsalam Elawwad. Thank you so much for your guidance, input throughout the research and thesis writing period. The last and the most important, my mother and my family. All is nothing without your support and pray. Thank you.

## **Table of Contents**

<u>LIST OF TABLES</u>	vi
<u>LIST OF FIGURES</u>	vii
NOMENCLATURE	xi
ABSTRACT	xii
CHAPTER 1: INTRODUCTION	1
1.1. Background.	1
1.2. Problem statement	2
Research objectives	2
CHAPTER 2: LITERATURE REVIEW	3
2.1. Introduction	3
2.2. Impact of regulations on wastewater engineering	3
2.3. Process of treatment.	4
2.3.1. Preliminary/Primary Treatment	6
2.3.2. Screening Influent Wastewater	6
2.3.3. Grit Removal.	7
2.3.4. Influent-Flow Equalization.	7
2.4. Advanced wastewater treatment.	8
2.5. Sequencing batch reactor (SBRs)	9
2.5.1. SBR Characteristics.	10
2.5.2. Basic Treatment Process.	10
2.5.2.1. Fill.	10
2.5.2.2. React	12
2.5.2.3. Settle	12
2.5.2.4. Decant	12
2.5.2.5. Idle	13
2.5.3. Continuous-Flow Systems.	13
2.6. Design guidelines.	13
2.6.1. Basin Design	13
2.7. Flow-Paced Batch Operation	14
2.8. Lessons from the Field	14
2.9. Blower Design	15

2.10. Variable Frequency Drives – VFDs	15
2.11. Decanting	16
2.12. Bottom Slope	16
2.13. Maintenance	16
2.14. Post Basin	16
2.15. Operational suggestions	17
2.15.1. Parameters to be monitored by the SCADA system	17
2.16. Cold-Climate Adjustments	18
2.17. Sampling	19
2.17.1. Proper Sampling Points	19
2.18. Parameters to Monitor.	19
2.18.1. Solids Retention Time – SRT	19
2.18.2. Sludge Wasting.	19
2.19. Alkalinity	20
CHAPTER 3: MATERIALS AND METHODS	21
3.1. Plan of Work	21
3.2. Description of Zenein WWTP	22
3.3. Pilot plant setup	24
3.4. The media	29
3.5. Chemicals used for increasing the organic load	30
3.6. Wastewater samples collection	31
3.6.1. Sampling program	32
3.7. Analytical methods	33
3.7.1. Chemical oxygen demand (COD)	33
3.7.2. Biological oxygen demand (BOD)	33
3.7.3. Total kjeldahl nitrogen (TKN)	33
3.7.4. Ammonium nitrogen	34
3.7.5. Nitrite nitrogen	34
3.7.6. Nitrate nitrogen	35
3.7.7. Total nitrogen.	35
3.7.8. Phosphorus	35
3.7.9. Total suspended solids (TSS)	36

3.7.10. Volatile suspended solids (VSS)	36
3.7.11. Alkalinity	36
3.7.12. Sludge volume index (SVI)	36
CHAPTER 4: RESULTS AND DISCUSSION	38
4.1. Introduction	38
4.2. Starting up period (Run I)	38
4.3. Second stage period (RUN II).	48
4.4. Third stage period (RUN III)	58
4.5. Fourth stage period (RUN IV)	68
4.6. Assessment of influent and effluent wastewater quality	78
4.6.1. BOD results.	78
4.6.2. COD results.	81
4.6.3. VSS results	84
4.6.4. TSS results.	87
4.6.5. MLSS & MLVSS results	90
4.6.6. NO <sub>2</sub> &NO <sub>3</sub> results.	92
4.6.7. NH <sub>4</sub> results.	94
4.6.8. pH value	96
4.6.9. Temperature measurements	97
4.6.10. DO measurements	97
4.7. Batch Reactors	98
4.7.1. Run 1. Carbon removal	98
4.7.2. Run 2. Denitrification.	100
4.7.3. Run 3. Nitrification.	103
CHAPTER 5: CONCLUSIONS AND RECOMEDATIONS	105
5.1. Conclusions	105
5.2. Recommendations.	107
REFERENCES	108
APPENDIXES	118

## LIST OF TABLES

Table 3.1 Plan of work and operating conditions	22
Table 3.2 Specification of the media	30
Table 3.3 Chemical added to increase organic load	31
Table 4.1 Operation condition of startup period	39
Table 4.2 Results summery of startup period	39
Table 4.3 Operation condition of second period	49
Table 4.4 Results summery of second period	49
Table 4.5 Operation condition of third period	58
Table 4.6 Results summery of third period	59
Table 4.7 Operation condition of fourth period	68
Table 4.8 Results summery of fourth period	69
Table 4.9 BOD concentrations and its removal efficiency % by R1 in all stages	79
Table 4.10 BOD concentrations and its removal efficiency % by R2 in all stages	81
Table 4.11 COD concentrations and its removal efficiency % by R1 in all stages	82
Table 4.12 COD concentrations and its removal efficiency % by R2 in all stages	84
Table 4.13 VSS concentrations and its removal efficiency % by R1 in all stages	86
Table 4.14 VSS concentrations and its removal efficiency % by R2 in all stages	87
Table 4.15 TSS concentrations and its removal efficiency % by R1 in all stages	89
Table 4.16 TSS concentrations and its removal efficiency % by R2 in all stages	90
Table 4.17 pH values for R1, R2	96
Table 4.18 Atmospheric temperature values on-site	97
Table 4.19 DO values of the R1, R2.	98
Table 4.20 Chemicals added to the batches.	98

## LIST OF FIGURES

Figure 2.1 Schematic diagrams of a wastewater plant. (Azadi et al., 2015)	
Figure 2.2 Schematic diagrams of SBR wastewater plant	
Figure 3.1 General Layout of Zenein WWTP	
Figure 3.2 Schematic diagram of the pilot plant.	
Figure 3.3 Details of the reactor and components	
Figure 3.4 Air diffusers at the bottom of the reactors	
Figure 3.5 Feeding tank 500 L	
Figure 3.6 The reactors and decant pumps.	
Figure 3.7 Influent pipe of the reactors	
Figure 3.8 Pilot Plant after construction.	
Figure 3.9 Sample of media.	
Figure 3.10 The sampling bottles	
Figure 4.1 Influent and effluent BOD concentrations in R1 at start-up stage	
Figure 4.2 BOD removal percentage in R1 at start-up stage	
Figure 4.3 Influent and effluent COD concentrations in R1 at start-up stage	
Figure 4.4 COD removal percentage in R1 at start-up stage	
Figure 4.5 BOD & COD loads in R1 and R2 at start-up stage	
Figure 4.6 Influent and effluent of VSS concentration in R1 at start-up stage	
Figure 4.7 VSS removal percentage in R1 at start-up stage	
Figure 4.8 Influent and effluent of TSS concentration in R1 at start-up stage	
Figure 4.9 TSS removal percentage in R1 at start-up stage	
Figure 4.10 Influent and effluent of BOD concentration in R2 at start-up stage	
Figure 4.11 BOD removal percentage in R2 at start-up stage	
Figure 4.12 Influent and effluent of COD concentration in R2 at start-up stage	
Figure 4.13 COD removal percentage in R2 at start-up stage	
Figure 4.14 Influent and effluent of VSS concentration in R2 at start-up stage	
Figure 4.15 VSS removal percentage in R2 at start-up stage	
Figure 4.16 Influent and effluent of TSS concentration in R2 at start-up stage	
Figure 4.17 TSS removal percentage in R2 at start-up stage	
Figure 4.18 Influent and effluent of BOD concentration in R1 at second period	
stage	

Figure 4.19 BOD removal percentage in R1 at second period stage	50
Figure 4.20 Influent and effluent of COD concentration in R1 at second period	51
stage	<i>J</i> 1
Figure 4.21 COD removal percentage in R1 at second period stage	51
Figure 4.22 BOD & COD loads in R1 and R2 at second period stage	52
Figure 4.23 Influent and effluent of VSS concentration in R1 at second period	<i>50</i>
stage	52
Figure 4.24 VSS removal percentage in R1 at second period stage	53
Figure 4.25 Influent and effluent of TSS concentration in R1 at second period	53
stage	33
Figure 4.26 TSS removal percentage in R1 at second period stage	54
Figure 4.27 Influent and effluent of BOD concentration in R2 at second period	54
stage	54
Figure 4.28 BOD removal percentage in R2 at second period stage	55
Figure 4.29 Influent and effluent of COD concentration in R2 at second period	55
stage	3.
Figure 4.30 COD removal percentage in R2 at second period stage	56
Figure 4.31 Influent and effluent of VSS concentration in R2 at second period	56
stage	50
Figure 4.32 VSS removal percentage in R2 at second period stage	57
Figure 4.33 Influent and effluent of TSS concentration in R2 at second period	57
stage	31
Figure 4.34 TSS removal percentage in R2 at second period stage	58
Figure 4.35 Influent and effluent of BOD concentration in R1 at third period stage	59
Figure 4.36 BOD removal percentage in R1 at third period stage	60
Figure 4.37 Influent and effluent of COD concentration in R1 at third period stage	60
Figure 4.38 COD removal percentage in R1 at third period stage	61
Figure 4.39 BOD & COD loads in R1 and R2 at third period stage	61
Figure 4.40 Influent and effluent of VSS concentration in R1 at third period stage	62
Figure 4.41 VSS removal percentage in R1 at third period stage	62
Figure 4.42 Influent and effluent of TSS concentration in R1 at third period stage	63
Figure 4.43 TSS removal percentage in R1 at third period stage	63