



شبكة المعلومات الجامعية
التوثيق الإلكتروني والميكروفيلم

بسم الله الرحمن الرحيم



HANAA ALY



شبكة المعلومات الجامعية
التوثيق الإلكتروني والميكروفيلم



شبكة المعلومات الجامعية التوثيق الإلكتروني والميكروفيلم



HANAA ALY



شبكة المعلومات الجامعية
التوثيق الإلكتروني والميكروفيلم

جامعة عين شمس

التوثيق الإلكتروني والميكروفيلم

قسم

نقسم بالله العظيم أن المادة التي تم توثيقها وتسجيلها
علي هذه الأقراص المدمجة قد أعدت دون أية تغيرات



يجب أن

تحفظ هذه الأقراص المدمجة بعيدا عن الغبار



HANAA ALY



AIN SHAMS UNIVERSITY
FACULTY OF ENGINEERING
Design and Production Engineering

**Thermomechanical processing and deformation behavior of dual
phase steel**

A Thesis submitted in partial fulfillment of the requirements of the degree
of

Doctor of Philosophy In Mechanical Engineering
(Design and Production Engineering)

By

Hany Abd AL Rahman Khalifa

Master of Science In Mechanical Engineering
(Design and Production Engineering)
Faculty of Engineering, Ain Shams University, 2013

Supervised By

Prof. Dr. Mohamed Ahmed Taha

Prof. Dr. Taher Ahmed EL-Bitar

Dr. Gamal Mohamed Megahed

Cairo - (2021)



AIN SHAMS UNIVERSITY
FACULTY OF ENGINEERING
Design and Production Engineering

**Thermomechanical processing and deformation behavior of dual
phase steel**

By

Hany Abd Al-Rahman Khalifa

Master of Science in Mechanical Engineering
(Design and Production Engineering)
Faculty of Engineering, Ain Shams University, 2013

Examiners' Committee

Name and Affiliation

Signature

Prof. Dr. Mohamed Ahmed Taha

Design and Production Engineering Department,
Faculty of Engineering, Ain Shams University.

.....

Prof. Dr. Iman El Mahallawi

Department of Metallurgical Engineering
Faculty of Engineering, Cairo university

.....

Prof. Dr. Ahmed El Sabbagh

Design and Production Engineering Department,
Faculty of Engineering, Ain Shams University

.....

Date:

Statement

This thesis is submitted as a partial fulfillment of Doctor of Philosophy in Mechanical Engineering, Faculty of Engineering, Ain shams University.

The author carried out the work included in this thesis, and no part of it has been submitted for a degree or a qualification at any other scientific entity.

Signature

.....

Hany Abd Al-Rahman Khalifa

Date:

Acknowledgments

First and foremost, praises and thanks to the God, the Almighty, for blessings throughout my research work to complete the research successfully. This dissertation would not have been possible without the guidance and help of several persons who contributed and extended their valuable assistance in the preparation and completion of this study.

I would like to express my deep and sincere gratitude to my research supervisor, **Prof. Mohamed Ahmed Taha** for providing invaluable guidance throughout this research. His dynamism, vision, sincerity and motivation have deeply inspired me. He has taught me the methodology to carry out the research and to present the research works as clearly as possible. It was a great privilege and honor to work and study under his guidance. I am especially thankful and grateful to my thesis supervisors **Prof. Thaer Elbitar** for his technical support.

Unlimited thanks to **Dr. Gamal Megahed** for his constant help, guidance and the countless hours of attention he devoted throughout the work in this thesis. I am extremely grateful for what he has offered me during working under his management in EZZ steel plant. I would also like to thank him for his friendship, empathy, and great sense of humor.

I am extremely grateful to my mother for her love, prayers, caring and sacrifices for educating and preparing me for my future. I am very much thankful to my wife and my daughters for their love, understanding, prayers and continuing support to complete this research work.

Finally, my thanks go to special people who have supported me to complete the research work directly or indirectly, especially:

Professor Heinz Palkowski and Dr. Mohamed Soliman (Clausthal University of Technology) for their unlimited support in the technical issues as long as performing experiments by the facilities of the Technische Universität Clausthal.

Researcher Data

Name : Hany Abd Al Rahman Khalifa
Date of birth : 02/04/1975
Place of birth : Beheira governorate
Last academic degree : Master of Science
Field of specialization : Materials Engineering
University issued the degree : Ain Shams University
Date of issued degree : August, 2013
Current job : Rolling mill manager, EZZ steel,
Sokhna, Egypt.

Abstract

The current work developed two grades of direct hot rolled ultralow carbon dual phase steel, ferrite bainite dual phase “FBDP” and ferrite martensite dual phase “FMDP” steel with high ductility values. The alloy design and production route cope with a compact slab production CSP plant. Ultralow carbon alloys were determined within the pre-peritectic region from phase diagrams plotted by Thermo-Calc 2020. The chemical compositions of the alloys are 0.045% C, 0.28 Si%, 0.91% Mn, and different Cr weight contents of 0.59%, 1%, 1.56%, and 2%. These alloys were used to develop FBDP steel. Analogous to “FBDP” steel, the martensitic dual phase steel is developed using ultralow carbon alloy and the only difference is the addition of niobium. The chemical composition of FMDP steel is (0.045 Wt.% carbon, 0.04 Wt.% niobium, 0.59 Wt.% chromium, 0.9 Wt.% manganese, 0.28 wt.% silicon) . These alloys were melted and cast into blocks, and then a certain thermomechanical schedule was applied using the actual data obtained from the log files of a CSP plant. The cooling schedule was designed with the aid of CCT and TTT curves plotted by JMatPro. The designed thermomechanical processing scheduled was performed by two methods. In the first method physical simulator “Baher TTS 820” is used. This device allows to perform physical simulation of direct hot rolled dual phase low carbon steel by varying the metallurgical temperatures and deformation parameters of to simulate compact slab production plant CSP. The second method is the pilot scale rolling and salt bath heat treatment, this route is used to develop FBDP steel under specific conditions determined from the results of physical simulation of the thermomechanical processing. The niobium was added to the FMDP steel to enhance the ductility of the martensite DP steel, since the current work aims to get high ductility values of DP steel, while lower carbon content is enough to get high ductile FBDP steel. The micro alloying affects the hot deformation flow behavior of the steel and the final microstructure. Consequently rheological curve characteristics under different rolling conditions are predicted using data of compact slab production log files and the phenomenological hyperbolic sinusoidal Arrhenius mathematical model. The Practical values of high strain rates reaches to $100\text{ }S^{-1}$ along with the practical deformations temperatures of an industrial hot strip mill plant are used. Mean flow stress, non-recrystallization temperature and microstructure grain size are investigated. The results show that hot rolled FBDP steel contains a substantial amount of bainite from 10 to 28% and negligible martensite. The increase in Cr led to an increase in the bainite volume fraction and an increase in the yield strength and tensile strength, while the elongation decreased slightly. The strain hardening exponent (n-value) reached values ranging from 0.28 to 0.36, while a value of 0.18 was found in the

literature for martensitic DP steel. Stroke-force curves plotted from the Erichsen test achieved high Erichsen index values from 14 to 18mm. The results of FMDP steel shows that the increase of finishing rolling temperature from 780 °C to 840 °C or decreasing either of step cooling duration at ferrite bay from 7 to 4 seconds, enhances yield and tensile strengths, all due to more martensite volume fraction formation. The yield and tensile strengths also increase with decreasing coiling temperature from 330 °C to 180 °C, which is explained due to the increase of dislocation densities resulted from the sudden shape change during martensite formation at the lower coiling temperature in additional to the self-tempering of martensite formed at higher coiling temperatures which soften the dual phase steel. The numerical analysis of flow behavior shows that predicted values of mean flow stress and non-recrystallization temperature are in a good agreement with the values obtained from the straightforward method by mathematical integration of the flow curves predicted by (BährTTS820) thermomechanical simulator. Predicted grain size shows good agreement with industrial rolled specimen microstructure. Predicted flow curves show good agreement with those directly plotted from physical simulation data.

Keywords:

Dual phase steel, Thermomechanical processing, Hot Rolling, Isothermal holding, Physical simulation, bainite, martensite.

Table of Content

content	page
Acknowledgments	vi
Researcher Data	v
Abstract	vii
Table of Content	viii
List of Figures	xii
List of Tables	xvi
List of Abbreviations	xi
List of Symbols	xiii
chapter 1 : Introduction	
Chapter 2 : Literature Survey	17
2.1 Production of Dual Phase steel	18
2.1.1 Compact slab production CSP plants.	18
2.1.2 Principles of formation of DP microstructure by CSP plants	19
2.1.3 The role of alloying element in DP steels	20
2.1.4 The role of micro alloying in DP steel	22
2.1.5 Critical peritectic range	23
2.2 Thermomechanical rolling (TMR) of DP steel	24
2.2.1 Dynamic phenomenon at HR	25
2.3 Constitutive Modeling	26
2.3.1 Strain rate	26
2.3.2. Z- parameter	27
2.3.4 Mean flow stress	28
2.4 Martensite in DP steel	31

2.5 Bainite in DP steel	32
Chapter 3 : Problem definition and work plan	35
3.1 Aim and methodology	36
3.2 parameters controlling the development of DP steel	37
3.3 Summary of work plan	38
Chapter 4 : Experimental procedures and methods	40
4.1 Alloy design	41
4.2 Material preparation	42
4.3 Dilatation and Physical simulation of hot strip mill	42
4.3.1 Dilatation Experiments	42
4.3.2 physical simulation Experiments of TMCR	43
4.4 Pilot rolling and salt bath treatment	46
4.5 Microstructure Examinations	47
4.5.1 LOM	47
4.5.2 Scanning electron microscope (SEM)	48
4.5.3 Transmission Electron Microscopy (TEM)	48
4.6 Tensile Test	48
4.7 Erichsen Stretch Forming Test	49
Chapter 5: Results and Discussion	50
Results and discussion : Part 1 FB DP Steel	50
5.1 Thermodynamic - Kinetic Calculations and Alloy Design	51
5.2 Dilatation Test Results	57
5.2.1 Microstructure of dilatation test	58
5.3 Physical simulation of TMCR to produce FB DP steel	58
5.3.1 Deformation schedule	58

5.3.2 Cooling schedules	60
5.3.3 Thermal profile of TMCR	61
5.3.4 FLOW CURVES	62
5.3.5 Change in length during TMR	65
5.4 Microstructure of physical simulation	68
5.5 TMCR of the pilot rolling and salt bath treatment	
5.6 Microstructure of pilot rolling and salt bath treatment	71
5.7 Tensile Test (pilot rolling and salt bath treatment	72
5.8 Erichsen Test Results	77
Results and discussion :Part 2: FMDP Steel	79
5.9 Thermodynamic - Kinetic Calculations and Alloy Design	80
5.10 TMCR	83
5.11 Microstructure features	84
5.11.1 Effect of coiling temperature	90
5.11.2 Effect of isothermal ferrite holding IFH time	90
5.11. 3 Effect of Finishing rolling temperature FRT	91
5.12 Tensile test	91
Results and discussion: Part 3 Flow behavior of FMDP Steel	93
5.13 Numerical analysis of flow behavior	94
5.14 Results and analysis	96
5.14.1 Flow stresses	96
5.14.2 Mean flow stress predicted from mill data	
5.14.3 Mean flow stress predicted from physical simulation	98
5.14.4 Grain size	99

Chapter 6: Conclusions and future work	100
6.1 conclusions	101
6.2 Future work	102
References	103

List of Figures

Figure 2.1: The processing routes for the production of DP steel.

Fig. 2.2: lay out of CSP

Figure 2.3: shows the influence of thermal cycles on the phase transformations in AHSS

Fig.2.4: The influence of the major alloying elements and thermal cycles on the phase transformations in AHSS

Fig. 2.5: Influence of Nb addition on the processing route of hot strip DP steels

Fig.2.6 Origin of peritectic crack formation and segregation

Fig.2.7: Influence of carbon content and casting rate on surface crack-formation

Fig.2.8 classification of flow stresses curves for different metallurgical phenomena

Fig.2.9 Thermomechanical processing of steel: rough deformation stage where recrystallization is complete and finish deformation stage wherein pancaking structure formed in absence of recrystallization phenomena.

Fig.3.1: Relation between the process parameters controlling the development of DP steel

Fig. 4.1 Dilatometer setup of the Bähr 805 A/D for dilatation tests

Fig. 4.2 (a) Experimental flat compression setup and (b) position of the flat compression sample in the chamber inside the induction coil of the deformation simulator.

Fig. 4.3 Specimen's dimension for flat compression test.

Fig.4.4: schematic representation of different stages during the pilot hot rolling and subsequent salt bath

Fig. 4.5 Laboratory reversing mill for hot rolling simulation and a picture of plates during roughing rolling process

Fig. 4.6 Flat compression specimens before rolling and after hot rolling simulation as well as after machining

Fig.5.1 Peritectic region of the tested DP alloys.

Fig.5.2 Dependence of the concentration of alloying elements on the austenite percentage: (a) DP_1 , (b) DP_2 (c) DP_3 and (d) DP_4